

WAAS CH 42939 W22B	APP CRS 213°	Rwy Idg TDZE Apt Elev	10000 642 645
--	------------------------	-----------------------------	--

RNAV (GPS) Y RWY 22R
DETROIT METRO WAYNE COUNTY (DTW)


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 1100 then climbing right turn to 4000 direct DOHNT and hold.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 135.0 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CLNC DEL 120.65	CPDLC
--------------------------	--	-------------------------------------	---	---------------------------	-------

RADAR REQUIRED



ELEV 645 D TDZE 642		1100 4000 DOHNT		VGSi and RNAV glidepath not coincident (VGSi Angle 3.00°/TCH 71).	
		*LNAV only.		TAYUL MMOTR GRDCY	
		ANGGL WONDR EMINN		213° 4000	
		*1.1 NM to (CFBJN)		4000 4000 4000	
		1.1 NM 3.0 NM 3.1 NM 3.1 NM 3.1 NM 3.1 NM 2 NM		GP 3.00° TCH 55	
CATEGORY		A		B	
LPV DA		892/24		250 (300-1/2)	
LNAV/VNAV DA		1050/45		408 (500-3/4)	
LNAV MDA		1060/24		1060/40 418 (500-3/4)	
CIRCLING		1180-1 535 (600-1)		1180-1 1/2 535 (600-1 1/2)	
				1240-2 595 (600-2)	

EC-1, 13 JUL 2023 to 10 AUG 2023

EC-1, 13 JUL 2023 to 10 AUG 2023