


WAAS CH 63111 W17A	APP CRS 172°	Rwy Idg TDZE Apt Elev	5001 651 651
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 17

MANITOWOC COUNTY (MTW)

RNP APCH.	MALSR	MISSED APPROACH: Climb to 3000 direct HEMTI and hold.
▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 7/8 SM.		

AWOS-3PT 123.775	GREEN BAY APP CON ★ 120.2 338.2	UNICOM 122.8 (CTAF)
----------------------------	---	-------------------------------



4 NM Holding Pattern HALUV				
6000 ← 352° 3000 → 172°				
GP 3.00° TCH 44				
2000				
7.2 NM 2.6 NM 1.5 NM				
CATEGORY	A	B	C	D
LPV DA		851-½	200 (200-½)	
LNAV/VNAV DA		942-½	291 (300-½)	
LNAV MDA	1180-½	529 (600-½)	1180-1	529 (600-1)
CIRCLING	1200-1	549 (600-1)	1420-2¼ 769 (800-2¼)	1480-2¾ 829 (900-2¾)

