

WAAS CH <b>42701</b> <b>W17A</b>	APP CRS <b>173°</b>	Rwy Idg <b>6014</b> TDZE <b>1351</b> Apt Elev <b>1354</b>
--	------------------------	---

RNAV (GPS) RWY 17R

CLARENCE E PAGE MUNI (R/C/E)


▼

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Wiley Post altimeter setting and increase all DA 29 feet and all MDA 40 feet and increase LPV all Cats visibility ¼ mile. VDP NA when using Wiley Post altimeter setting.

⚠

MISSED APPROACH: Climb to 3800 direct JEBGO and hold.

AWOS-3 <b>125.05</b>	OKE CITY APP CON <b>124.6 266.8</b>	UNICOM <b>123.0 (CTAF)</b>
-------------------------	--	-------------------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident. (VGSI Angle 3.00/TCH 52).		3800	JEBGO
GP 3.00° TCH 52		CATKI		BLAZO	HESVA 3.1 NM to RW17R
		3000		*2380	*1.1 NM to RW17R
		6.1 NM		1.9 NM	2 NM
				1.1 NM	
CATEGORY	A	B	C	D	
LPV DA	1601-¾ 250 (300-¾)			NA	
LNAV MDA	1760-1	409 (500-1)	1760-1¼ 409 (500-1¼)	NA	
CIRCLING	1800-1 446 (500-1)	1820-1 466 (500-1)	1840-1½ 486 (500-1½)	NA	

