


RNAV (GPS) RWY 5

SHENANDOAH VALLEY RGNL (SHD)

<p>RNP APCH.</p> <p>▼ For inoperative MALS R when using Charlottesville altimeter setting, increase LPV visibility to 1¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. Baro-VNAV and VDP NA when using Charlottesville altimeter setting. When local altimeter setting not received, use Charlottesville altimeter setting and increase all DA 130 feet and all MDA 140 feet. Increase LPV all Cats visibility ¼ SM, LNAV/VNAV all Cats ½ SM, LNAV Cat C/D ¼ SM, Circling Cat C ½ SM and Cat D ¼ SM.</p>	<p>MALS R</p> 	<p>MISSED APPROACH: Climb to 5200 direct HAPED and left turn via track 304° to JATIR and left turn via track 199° to GABEL and hold.</p>
--	---	--

NE-3, 13 JUL 2023 to 10 AUG 2023

CATEGORY	A	B	C	D
LPV DA	1384-1/2	200 (200-1/2)		
RNAV/VNAV DA	1563-3/4	379 (400-3/4)		
RNAV MDA	1620-1/2 436 (500-1/2)	1620-3/4 436 (500-3/4)	1620-1 436 (500-1)	
CIRCLING	1660-1 459 (500-1)	1760-1 559 (600-1)	1900-2 699 (700-2)	2060-2 859 (900-2 3/4)

RNAV (GPS) RWY 5