

APP CRS  
**007°**

Rwy Idg  
**6869**

TDZE  
**14**

Apt Elev  
**14**

**RNAV (RNP) RWY 1**

RONALD REAGAN WASHINGTON NTL (DCA)

**▽**

For uncompensated Baro-VNAV systems, procedure NA below -10°C (14°F) or above 48°C (120°F). RF required. GPS required. Missed approach requires RNP less than 1.0. For inop ALS, increase RNP 0.30 all Cats visibility to 1¼ mile.

ALSF-2

MISSED APPROACH:

(Do not exceed 185K until FIVUD) Climb to 2200 left turn to FIVUD and on track 327° to HESLO and on track 327° to GTN NDB and hold.

D-ATIS <b>132.65</b>	POTOMAC APP CON <b>119.85 239.25</b> (WEST/SOUTH) <b>124.2 360.8</b> (EAST)	WASHINGTON TOWER <b>119.1 257.6</b>	GND CON <b>121.7 257.6</b>	CLNC DEL <b>128.25</b>	CPDLC
-------------------------	---	--	-------------------------------	---------------------------	-------

MISSED APCH FIX

GEORGETOWN GTN

Prohibited area (P-56) 1.5 NM north of DCA- avoid surface to 18000 MSL.

ELEV 14

TDZE 14

REIL Rwy 4, 22, 15 and 33

HIRL Rwy 1-19 and 15-33

MIRL Rwy 4-22

TDZ/CL Rwy 1

2200

FIVUD

HESLO

GTN

BADDN

MRION

RW01

1600

2500

GP 3.00°

TCH 54

4.8 NM

5.8 NM

CATEGORY	A	B	C	D
RNP 0.30 DA	552/60 538 (600-1¼)			

**AUTHORIZATION REQUIRED**

WASHINGTON, DC

Amdt 1B 26APR18

RONALD REAGAN WASHINGTON NTL (DCA)

38°51'N-77°02'W

**RNAV (RNP) RWY 1**