BERCLAIR, TEXAS RNAV (GPS) RWY 29 Rwy Idg 8000 APCH CRS TDŹE 285 285° Arpt Elev AL-2440 [USN] **GOLIAD NOLF** (KNGT) 322 RNP APCH - DME/DME RNP-0.3 NA MISSED APPROACH: Climb to 900 then climbing right turn to When local altimeter setting not received, use Beeville Muni 4000 direct SWEEN and hold, continue climb-in-hold to 4000. altimeter setting. ASOS CTAF 353.675 132.875 307.075 /ICTORIA (IAF) sòwis (FAF) Max holding **BOMRS** alt 8000 **∧** 307 Min holding alt 4000 5 NM (IF/IAF) 285°, SWEEN SWEEN is a fly-over fix when used as a missed approach THREE RIVERS clearance limit. THX 4000 0950 RW29 (38.1) (IAF) 2300 **TEMKN** 536 US NAVY Training Wing Four Use Only EMERG SAFE ALT 100 NM 11,100 4000 SWEEN 285 VDP NA with Beeville Muni altimeter setting. **ELEV** 322 **TDZE SWEEN BOMRS** 4000 .8 NM to 285° to RW29 RW29 RW29 2200 CATEGORY В C D 580-1 295 (300-1) LNAV MDA 760-1 880-2 780-1 780-11/2 **C** CIRCLING 438 (500-1) 458 (500-11/2) 558 (600-2) 458 (500-1) BEEVILLE MUNI ALTIMETER SETTING MINIMA

**C** CIRCLING BERCLAIR, TEXAS Amdt 2 05NOV20 800-1

478

LNAV MDA

28°37′N-97°37′W

880-2

558 (600-2)

(400-1)

800-11/2

478 (500-11/2)

640-1

(500-1)

355

GOLIAD NOLF

to 10 AUG 2023

SC-3, 13 JUL 2023

HIRL Rwy 11-29, 17-35

TDZL Rwy 11-29, 17-35