

WAAS
CH **70534**
W27A

APP CRS
274°

Rwy Idg **4000**
TDZE **1146**
Apt Elev **1150**

RNAV (GPS) RWY 27

ROSCOMMON COUNTY/BLODGETT MEML (HTL)

When local altimeter setting not received, use Gaylord altimeter setting and increase all MDAs 120 feet and visibility Cat C/D ½ SM. DME/DME RNP-0.3 NA. Procedure NA at night.

Helicopter visibility reduction below 1 SM NA. Circling NA to Rwy's 18, 36.

MISSED APPROACH:
Climb to 3300 direct
FISTU and hold.

ASOS 118.05	MINNEAPOLIS CENTER 125.475 269.45	UNICOM 122.8 (CTAF) 0
-----------------------	---	---------------------------------

ELEV 1150		TDZE 1146		
<div><div><div><div>3300</div><div>FISTU</div><div>Visual Segment - Obstacles</div></div><div><div>4000 X 75</div><div>27</div><div>274°</div><div>2200 X 100</div><div>36</div></div></div><div><div>HILOT</div><div>2.5 NM to RW27</div><div>COVLA</div><div>3000</div><div>1980</div><div>2.5 NM</div><div>3.2 NM</div><div>6.9 NM</div><div>HESER</div><div>4 NM Holding Pattern</div><div>094°</div><div>274°</div><div>3300</div></div></div>				
CATEGORY	A	B	C	D
LP MDA	1540-1	394 (400-1)	1540-1¼	394 (400-1¼)
LNAV MDA	1560-1	414 (500-1)	1560-1¼	414 (500-1¼)
CIRCLING	1600-1	450 (500-1)	1700-1½ 550 (600-1½)	1820-2 670 (700-2)

HOUGHTON LAKE, MICHIGAN

Amtd 1D 24FEB22

ROSCOMMON COUNTY/BLODGETT MEML (HTL)

44°22'N-84°40'W

RNAV (GPS) RWY 27