


WAAS CH 93731 W31A	APP CRS 319°	Rwy Idg 4399 TDZE 1943 Apt Elev 1944
--	------------------------	---


RNAV (GPS) RWY 31

MANDAN RGNL/LAWLER FLD (Y19)

ASR  Baro-VNAV NA when using Bismarck altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Bismarck altimeter setting and increase all DA 54 feet and LNAV/VNAV all Cats visibility $\frac{1}{8}$ mile, increase all MDA 60 feet and LNAV Cat C/D visibility $\frac{1}{8}$ mile and Circling Cat D $\frac{1}{4}$ mile. Helicopter visibility reduction below $\frac{3}{4}$ SM NA. Circling to Rwy 4 and 22 NA.

MISSED APPROACH: Climb to 4600 direct ZUPJA and on track 249° to SAILM and hold.

AWOS-3 118.225	BISMARCK APP CON ★ 126.3 298.9	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



CATEGORY	A	B	C	D
LPV DA	2193-1 250 (300-1)			
RNAV/VNAV DA	2220-1 277 (300-1)			
RNAV MDA	2300-1 357 (400-1)			
C CIRCLING	2360-1 416 (500-1)	2460-1 516 (600-1)	2460-1½ 516 (600-1½)	2560-2 616 (700-2)