

WAAS CH <b>86216</b> <b>W17A</b>	APP CRS <b>175°</b>	Rwy Idg <b>5501</b> TDZE <b>1433</b> Apt Elev <b>1433</b>
--	------------------------	---

RNAV (GPS) RWY 17  
ALTUS/QUARTZ MOUNTAIN RGNL (AXS)

**V** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Hobart Rgnl altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Hobart Rgnl altimeter setting and increase LPV DA to 1754 feet and LNAV/VNAV DA to 1997 feet and increase all MDA 80 feet. Increase LPV, LNAV/VNAV all Cats and Circling Cat C visibility  $\frac{1}{4}$  mile, increase LNAV Cat C visibility  $\frac{1}{8}$  mile.

ODALS



**MISSED APPROACH:** Climb to 2000 then climbing right turn to 4000 direct ADOBE and hold.

AWOS-3PT <b>118.825</b>	ALTUS APP CON★ <b>125.1 353.7</b>	UNICOM <b>122.8</b> (CTAF) <b>0</b>
----------------------------	--------------------------------------	--

