

WAAS CH 58326 W11A	APP CRS 110°	Rwy Idg TDZE Apt Elev 8900 7096 7096
--	------------------------	--

RNAV (GPS) RWY 11


RALPH WENZ FLD (PNA)

▼ Baro-VNAV NA. When local altimeter setting not received, use Big Piney altimeter setting and increase LPV DA to 7404 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 7413 feet and all visibilities ¼ SM; increase all MDA 60 feet and LNAV Cat C/D visibility ¼ SM. Circling NA south of Rwy 11/29. DME/DME RNP- 0.3 NA. VDP NA with Big Piney altimeter setting.

ODALS

MISSED APPROACH: Climb to 10000 direct FEDPA and on track 194° to SEYTO and hold.

AWOS-3 118.325	SALT LAKE CENTER 128.35 239.25	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 2.83/TCH 40).					10000 ↑	FEDPA ✦	fr 194°	SEYTO △	ELEV 7096	TDZE 7096		
VACSU 10000 GP 3.00° TCH 55					UBUYPY HONLI DOYED 3.5 NM to RW11 *1.5 NM to RW11 RW11 *LNAV only.							
9400 9100 *8260					4.5 NM 2.1 NM 2.6 NM 2 NM 1.5 NM							
CATEGORY	A	B	C	D								
LPV DA	7346-¾				250 (300-¾)							
LNAV/ VNAV DA	7355-¾				259 (300-¾)							
LNAV MDA	7620-1 524 (600-1)		7620-1½ 524 (600-1½)									
CIRCLING	7640-1 544 (600-1)		7840-2¼ 744 (800-2¼)		7980-3 884 (900-3)		MIRL Rwy 11-29 ① REIL Rwy 11 and 29 ①					