


APP CRS	Rwy Idg	5009
317°	TDZE	480
	Apt Elev	494


RNAV (GPS) RWY 32
KOSCIUSKO-ATTALA COUNTY (OSX)

RNP APCH - GPS	MISSED APPROACH: Climb to 2100 direct JINED and hold.
Rwy 32 helicopter visibility reduction below 1 SM NA. Procedure NA at night. Use Philadelphia altimeter setting; when not received, use Greenwood altimeter setting and increase all MDAs 80 feet, increase visibility LNAV Cat C ½ SM and Circling Cat C ¾ SM.	

MPE AWOS-3P 118.725	MEMPHIS CENTER 132.75 350.25	CTAF 122.9 0
------------------------	---------------------------------	-----------------



ELEV 494	TDZE 480
----------	----------



2100	JINED	VGSI and descent angles not coincident (VGSI Angle 3.50/TCH 49).	GUDRE	4 NM Holding Pattern
				137° → 2200
				← 317°
				2100
				317°
				4.9 NM
				6 NM
CATEGORY	A	B	C	D
LNAV MDA	960-1	480 (500-1)	960-1 ¾ 480 (500-1 ¾)	NA
CIRCLING	1020-1	526 (600-1)	1160-1 ¾ 666 (700-1 ¾)	NA