

WAAS CH <b>93616</b> <b>W17A</b>	APP CRS <b>171°</b>	Rwy Idg <b>5705</b> TDZE <b>93</b> Apt Elev <b>101</b>
--	------------------------	--

RNAV (GPS) RWY 17  
LOWCOUNTRY RGNL (RBW)

**▼** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Charleston Intl/AFB altitude setting.

**▲** DME/CMD RNP-0.3 NA. When local altimeter setting not received, use Charleston AFB/Intl altimeter setting: increase LPV DA to 421 feet and LNAV/VNAV DA to 587 feet and all MDA 80 feet; increase LPV visibility all Cats ½ mile; increase LNAV/VNAV visibility all Cats, LNAV Cats C/D, and Circling Cat D visibility ¼ mile; increase Circling Cat C visibility ½ mile.

**MISSED APPROACH:**  
Climb to 2100 direct  
LATNY and on track 081°  
to CIGLO and track 003°  
to LAMKE and hold.

AWOS-3 <b>118.725</b>	CHARLESTON APP CON <b>120.7 306.925</b>	UNICOM <b>122.8 (CTAF) ①</b>
--------------------------	--	---------------------------------

