DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. When local altimeter

setting not received, use Williston Muni altimeter setting and increase Cat C MDA 80 feet Climb to 2000 direct A NA and increase visibility Cat C ¼ SM. Circling to Rwy 4/13/31 NA at night. UGLUF and hold. AWOS-3PT JACKSONVILLE CENTER UNICOM X6Ø AWOS-3T 120,775 127.8 352.0 118.425 122.8 (CTAF) (**ALVIN** (IAF) ZOTRO (IF/IAF) HULEL John (IAF) **GATORS** 2100 **GNV** 278° (32)(FAF) WIRET Procedure NA for arrival at GNV VORTAC via V579 eastbound. **1**346 MISSED APCH FIX 1 ∆ 549 4 NM MSA RW 22 25 Ny ELEV 42 229° to RW22 2100 \bigcirc

2000 UGLUF 4 NM HULEL Holding Pattern WIRET 2000 3.04° RW22 TCH 56 1600 4.7 NM 6.1 NM CATEGORY MIRL Rwys 4-22 and 13-310 660-13/4 740-21/4 CIRCLING 620-1 578 (600-1)

REIL Rwys 13 and 31 CROSS CITY, FLORIDA Orig-B 30DEC21

APP CRS

229°

V

SE-3, 13 JUL 2023 to 10 AUG 2023

TDŻE

Apt Elev

N/A

CROSS CITY (CTY) RNAV (GPS)-B

698 (700-2 1/4)

618 (700-13/4)

CROSS CITY (CTY)

MISSED APPROACH:

SE-3, 13 JUL 2023 to 10 AUG 2023