

|  |                        |   |             |
|--|------------------------|---|-------------|
| WAAS<br>CH <b>86430</b><br><b>W32A</b> | APP CRS<br><b>321°</b> | Rwy Idg<br>TDZE <b>1028</b><br>Apt Elev <b>1034</b> | <b>3999</b> |
|--|------------------------|---|-------------|

RNAV (GPS) RWY 32

MONTEVIDEO-CHIPPEWA COUNTY (MVE)

⚠

Circling to Rwy 14 NA at night. Baro-VNAV NA when using Granite Falls altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -30°C (-22°F) or above 54°C (130°F). When local altimeter setting not received, use Granite Falls altimeter setting and increase LPV DA to 1270 feet; increase LNAV/VNAV DA to 1464 feet and increase visibility all Cats ½ SM; increase all MDAs 40 feet and LNAV visibility Cats C/D ¼ SM and Circling visibility Cats C/D ¼ SM. DME/DME RNP -0.3 NA. Circling to Rwy 3-21 NA. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:

Climb to 3400 direct ZARTU and hold.

|                            |  |                                 |
|----------------------------|--|---------------------------------|
| AWOS-3PT<br><b>119.675</b> | MINNEAPOLIS CENTER<br><b>125.5 323.1</b> | UNICOM<br><b>122.8 (CTAF) 0</b> |
|----------------------------|--|---------------------------------|

MISSED APCH FIX

4 NM

141°

321°

ZARTU

MSA RW32 25 NM

3400

RW32

1159±

1387

WUMPI

2.5 NM to RW32

1490

1211

(FAF) ZATVU

2600

321°

(IF/IAF) YIBUG

4 NM

3300

060°

(18.3)

RISLE

3300

226°

(21.9)

FITAS

1572

REDWOOD FALLS RWF

(IAF)

|           |           |
|-----------|-----------|
| ELEV 1034 | TDZE 1028 |
|-----------|-----------|

14

32

321°

0.5% UP

2361 X 165

3999 X 75

0.4% UP

REIL Rws 14 and 32

MIRL Rwy 14-32

|              |                        |                  |                        |        |                      |
|--------------|------------------------|------------------|------------------------|--------|----------------------|
| 3400         | ZARTU                  | WUMPI            | ZATVU                  | YIBUG  | 4 NM Holding Pattern |
| * LNAV only  |                        | 2.5 NM to RW32   |                        |        |                      |
|              |                        | * 1.2 NM to RW32 |                        |        |                      |
|              |                        | 1860*            |                        |        |                      |
|              |                        | 1.2 NM           | 1.3 NM                 | 2.3 NM | 6 NM                 |
| CATEGORY     | A                      | B                | C                      | D      |                      |
| LPV DA       | 1234-1 206 (200-1)     |                  |                        |        |                      |
| LNAV/VNAV DA | 1428-1 ¾ 400 (400-1 ¾) |                  |                        |        |                      |
| LNAV MDA     | 1420-1 392 (400-1)     |                  | 1420-1 ¾ 392 (400-1 ¾) |        |                      |
| CIRCLING     | 1560-1 526 (600-1)     |                  | 1770-1 ¾ 666 (700-1 ¾) |        | 1700-2 666 (700-2)   |

MONTEVIDEO, MINNESOTA

Orig-B 07OCT21

MONTEVIDEO-CHIPPEWA COUNTY (MVE)

44°58'N-95°43'W

RNAV (GPS) RWY 32