

WAAS CH <b>72621</b> <b>W28A</b>	APP CRS <b>281°</b>	Rwy Idg TDZE <b>1253</b> Apt Elev <b>1253</b>
--	------------------------	---

RNAV (GPS) RWY 28

BEAVER COUNTY (BVI)

RNP APCH.

Baro-VNAV and VDP NA when using Pittsburgh Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 26°C (78°F). When local altimeter setting not received, use Pittsburgh Intl altimeter setting; increase all DA 50 feet; increase all MDAs 60 feet and visibility LNAV Cats C and D ¼ SM. Circling Rwy 28 NA at night. Rwy 28 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct WOBUX and hold.

ATIS  
**118.35**

PITTSBURGH APP CON  
**124.75 338.2**

BEAVER COUNTY TOWER ★  
**120.3 (CTAF) 0**

GND CON  
**121.8**

CLNC DEL  
**124.85**  
(when twr closed)

MISSED APCH FIX  
4 NM

ELEV 1253

TDZE 1253

3000 WOBUX

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 43).

4 NM Holding Pattern

\*LNAV only.

WUBMA 2.5 NM to RW28

ZILET 3000

JEDUV

281°

101°

3000

GP 3.10° TCH 60

CATEGORY	A	B	C	D
LPV DA		1512-1	259 (300-1)	
LNAV/ VNAV DA		1580-1	327 (400-1)	
LNAV MDA	1660-1	407 (500-1)	1660-1½ 407 (500-1½)	
CIRCLING	1720-1	467 (500-1)	1720-1½ 467 (500-1½)	1820-2 567 (600-2)