

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (129°F). Procedure NA for V3 Eastbound arrivals at BIPIN. CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916. SKIPP 197 196 121.7 336.45 121.2 357.4 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (129°F). Procedure NA for V3 Eastbound arrivals at BIPIN.	
RNP APCH MISSED APPROACH: Climb to 1600 direct HIGIB, track 291 and hold. ATIS * APP CON 124.025 313.7 NAVY KEY WEST TOWER * GND CON 121.7 336.45 121.2 357.4 ATIS * STAN STAN	° to SKIPP ASR/PAR
ATIS * APP CON 124.025 313.7 NAVY KEY WEST TOWER * GND CON 121.7 336.45 121.2 357.4 For uncompensated Baro-VNAV systems, LINAV/NAV NA below -15°C (5°F) or above 54°C (129°F). Procedure NA for V3 Eastbound arrivals at BIPIN. CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916. [R2916] [R2916] [A] [A] [A] [A] [A] [A] [A] [
307.025 124.025 313.7 118.575 340.25 121.7 336.45 121.2 357.4 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (129°F). Procedure NA for V3 Eastbound arrivals at BIPIN. CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916. R2916 A 1600 1600 1600 1600 1600 1600	
Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (129°F). Procedure NA for V3 Eastbound arrivals at BIPIN. CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916. [R2916] A 1600 1600 2772	50
CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916. R2916 R2916 A 1600 772	50
CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916. R2916 A 1600 772	50
CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916. R2916 \(\Lambda \) 1049 \(\Lambda \) 1600 \(\Lambda \) 2772	50
1600 1600 1600	
1600 A 272°	
W. 101 IIII 101 IIII	(IAF)
(IAI)	ΒΊΡΙŃ
RW26	
406 KEY	, -
WEST A INTL 200	6 25 Ny
[15,0	00
	-)
	<i></i>
TIGHOUS US ADIZ	
EMERG SAFE ALT 100 NM 15,000	
1/00	
Trigib tr	TDZE 6
↑ ↑ 291° HEKEM CEXIG	∧ 126
263° 1600	259
RW26 RW26 259° 1600	T-P2
GP 3.00° TCH 45	BCN TWR
4.9 NM (A) (B) (C) (C) (C) (C) (C) (C) (C) (C) (C) (C	, x
CATEGORY A B C D	3
LNAV/VNAV DA 291-% 302-% 310-% 321-% 296 (300-%) 304 (400-%) 315 (400-%)	
LNAV MDA 420-1 414 (500-1) 420-11/8 414 (500-11/8) 440-1 500-1 500-11/2 560-2	
GIRCLING 440-1 300-1 300-1 300-1 300-1 300-1 300-2 HIRL all Rwys	

KEY WEST, FLORIDA

24°34'N - 81°41'W

SE-3, 13 JUL 2023 to 10 AUG 2023