

WAAS
CH **86537**
W11A


APP CRS
116°

Rwy Idg
TDZE **718**
Apt Elev **722**

RNP APCH:
▼ When local altimeter setting not received, use Champaign/Urbana altimeter setting and increase all DA 82 feet, increase all MDA 100 feet, and increase LPV all Cats visibility ⅛ mile, LNAV/VNAV all Cats visibility ⅜ mile, LNAV Cats C and D and Circling Cat C visibility ¼ mile, and Circling D visibility ½ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Baro-VNAV and VDP NA when using Champaign/Urbana altimeter setting. Circling NA to Rwys 18 and 36.

MISSED APPROACH:
Climb to 1200 then climbing left turn to 3000 direct NIBIE and hold.

ASOS 118.475	CHAMPAIGN APP CON ★ 132.85 290,225	UNICOM 122.7 (CTAF) 0
-----------------	---------------------------------------	--------------------------



4 NM Holding Pattern

GP 3.00° TCH 45

WUBTA 3000

YAYSU 2400

ZOSIB 2.9 NM to RW11

RW11 809

NIBIE

* LNAV only.

6 NM 2.3 NM 1.8 NM 1.1 NM

CATEGORY	A	B	C	D
LPV DA	918-3/4 200 (200-3/4)			
LNAV/VNAV DA	1175-15/8 457 (500-15/8)			
LNAV MDA	1120-1 402 (400-1)		1120-11/8 402 (400-11/8)	
CIRCLING	1160-1 438 (500-1)	1180-1 458 (500-1)	1240-11/2 518 (600-11/2)	1380-2 658 (700-2)

ELEV 722 TDZE 718

MIRL Rwy 6-24 1
HILL Rwy 11-29 1
REIL Rws 6, 11, and 24 1