

APP CRS
311°

Rwy Idg
TDZE
Apt Elev
7257
36
36

RNAV (RNP) Z RWY 31
VALLEY INTL (HRL)

▼

For uncompensated Baro-VNAV systems, procedure NA below 2°C (36°F) or above 54°C (130°F). GPS Required. For inop ALS, increase RNP 0.17 all Cats visibility to ½ SM, and RNP 0.30 all Cats visibility 1 SM.

MALSR

MISSED APPROACH: Climb to 2000 on track 311° to CAKOB and hold.

ATIS 124.85	VALLEY APP CON 120.7 279.5	HARLINGEN TOWER ★ 119.3 (CTAF) 317.6	GND CON 121.7	UNICOM 122.95
-----------------------	--------------------------------------	--	-------------------------	-------------------------

RADAR REQUIRED

ELEV 36 D TDZE 36

MIRL Rwy 17L-35R
REIL Rwys 13 and 17L
HIRL Rwys 13-31 and 17R-35L

2000 tr 311° CAKOB

See Planview for multiple IF locations.

DACAY 1100

RWY 31 311° 1100

GP 3.00° TCH 55

3.2 NM

CATEGORY	A	B	C	D
RNP 0.17 DA		310-½	274 (300-½)	
RNP 0.30 DA		360-⅝	324 (400-⅝)	

AUTHORIZATION REQUIRED

HARLINGEN, TEXAS
Amdt 1 02MAR17

26°14'N-97°39'W

VALLEY INTL (HRL)
RNAV (RNP) Z RWY 31