

APP CRS
072°

Rwy ldg
TDZE
643

Apt Elev
643

RNAV (GPS) RWY 7

MASON COUNTY (3I2)

RNP APCH - GPS.

Circling NA NW of Rwy 7-25. Rwy 7 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Athens/Albany, OH altimeter setting and increase all MDA 80 feet. Straight-in and Circling NA at night to Rwy 7.

MISSED APPROACH:
Climb to 2700 direct HAYVU and hold.

AWOS-3
119.675

HUNTINGTON APP CON
128.4 270.1

UNICOM
122.8 (CTAF) 0

The main enroute chart displays the flight path from WAMAX to RW07. Key features include:

- WAMAX (NoPT) 3200**: Initial altitude and holding pattern (4 NM, 252°/072°).
- WAMAX (IF/IAF) 3200 NoPT**: Intermediate altitude and holding pattern (4 NM, 252°/072°).
- IMOPE (FAF) 2400**: Final approach fix at 2400 feet.
- Altitudes**: Various altitudes marked along the path, including 3200, 2400, 1578, 964, 1129, 1009, 1144, 1143, 1129, 1113, 1672, 1202±, and 1685.
- Navigation Aids**: VOR/DME stations for WAMAX (3200), EYMED (3200), and CULAG (3200).
- Obstacles**: Obstacle symbols with MSL and AGL altitudes.
- Distance Markers**: 30 NM to WAMAX, 30 NM to EYMED, 30 NM to CULAG, and 4 NM to RW07.

4 NM Holding Pattern

WAMAX

VGSi and descent angles not coincident (VGSi Angle 3.00/TCH 44).

2700 HAYVU

3200

252°

072°

072°

IMOPE

2400

3.04°

TCH 40

RW07

6.2 NM

5.3 NM

CATEGORY	A	B	C	D
LNNAV MDA	1880-1¼ 1237 (1300-1¼)	1880-1½ 1237 (1300-1½)	1880-3	1237 (1300-3)
CIRCLING	1880-1¼ 1237 (1300-1¼)	1880-1½ 1237 (1300-1½)	1880-3	1237 (1300-3)

REIL Rwy 7 and 25 0

MIRL Rwy 7-25 0

POINT PLEASANT, WEST VIRGINIA

Orig-A 14JUL22

38°55'N - 82°06'W

MASON COUNTY (3I2)

RNAV (GPS) RWY 7