



WAAS CH 53531 W26A	APP CRS 260°	Rwy Idg TDZE 4659 Apt Elev 4729
--	------------------------	---

RNAV (GPS) RWY 26L
PUEBLO MEML (PUB)

RNP APCH-GPS. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV ▲ NA below -22°C or above 54°C.			MISSED APPROACH: Climb to 7000 direct MERTZ and hold.		
ATIS 125.25	DENVER APP CON ★ 120.1 290.5	PUEBLO TOWER ★ 119.1 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 120.9	UNICOM 122.95



ELEV 4729	D TDZE 4659
-----------	-------------



HIRL Rwy 8R-26L	MRL Rws 17-35 and 8L-26R	REIL Rws 8L, 17, 26L, 26R and 35
-----------------	--------------------------	----------------------------------

7000 ↑		MERTZ 		HELER		6 NM Holding Pattern	
*LNAV only		*1.4 NM to RW26L		JKTA 6600		080° → 7000 ← 260°	
RW26L		↓		6600		GP 3.00° TCH 60	
1.4		4.5 NM		6.2 NM			
CATEGORY	A	B	C	D			
LPV DA	4859-3/4 200 (200-3/4)						
LNAV/ VNAV DA	4979-1 320 (300-1)						
LNAV MDA	5100-1	441 (400-1)	5100-1 3/8	441 (400-1 3/8)			
CIRCLING	5340-1	611 (700-1)	5580-2 1/2 851 (900-2 1/2)	5800-3 1071 (1100-3)			