

WAAS CH 72602 W13A	APP CRS 131°	Rwy Idg 9001 TDZE 922 Apt Elev 958
--	------------------------	---

RNAV (GPS) RWY 13

DES MOINES INTL (DSM)

▼

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.
For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4000 and LNAV Cats C and D visibility to RVR 4500.
RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct CYCLN and hold.

ATIS 119.55	DES MOINES APP CON 123.9 307.15	DES MOINES TOWER 118.3 257.8	GND CON 121.9 348.6	CLNC DEL 134.15 317.55
-----------------------	---	--	-------------------------------	----------------------------------

4 NM

311°

131°

(IF/IAF) WATY

2600

131°

(FAF) CLIVE

TILTH 1.7 NM to RW13

977±

1104

1065

1456

2004

30 NM to WATY (NoPT)

4000

3500

221°

10 NM to WATY

041°

10 NM to WATY

30 NM to WATY

4000

3500

131°

4 NM

CYCLN

ELEV 958 D TDZE 922

REIL Rwy 23
TDZ/CL Rwy 31
HIRL Rwys 13-31 and 5-23

WATY					3000	CYCLN		
4 NM Holding Pattern					* LNAV only			
3500 ← 311°					* 0.9 NM to RW13			
GP 3.00° TCH 56					RW13			
2600					* 1500			
8.2 NM					0.8 NM			
3.4 NM					0.9 NM			
CATEGORY	A	B	C	D				
LPV DA#	1122/24 200 (200-½)							
LNAV/VNAV DA	1172/24 250 (300-½)							
LNAV MDA	1240/24 318 (300-½)							
CIRCLING	1420-1	462 (500-1)	1600-1¾ 642 (700-1¾)	1760-2½ 802 (900-2½)				

DES MOINES, IOWA
Amdt 2A 29MAR18

41°32'N-93°40'W

DES MOINES INTL (DSM)

RNAV (GPS) RWY 13