RNAV (GPS) RWY 28
CLAYTON MUNI (11A)

WAAS CH 82536 W28A	APP CRS 281°	Rwy ldg 5010 TDZE 435 Apt Elev 435

RNP APCH - GPS.

Rwy 28 helicopter visibility reduction below ¾ SM NA. Use Eufaula altimeter setting; when not received, use Troy altimeter setting.

NA

MISSED APPROACH: Climb to 2200 direct YARCU and hold.

EUF ASOS	CAIRNS APP CON ★	CTAF
128.325	121.1 319.25	122.9 L



ELEV 435 TDZE 435



REIL Rwys 10 and 28
HIRL Rwy 10-28 L

2200 YARCU

VGSI and descent angles not coincident (VGSI Angle 3.75/TCH 37).

4 NM Holding Pattern



CATEGORY	A	B	C	D
LP MDA	1140-1 705 (800-1)		1140-2 705 (800-2)	
LNAV MDA	1140-1 705 (800-1)		1140-2 705 (800-2)	
C CIRCLING	1180-1 745 (800-1)		1180-2¼ 745 (800-2¼)	1300-2¾ 865 (900-2¾)

SE-4, 13 JUL 2023 to 10 AUG 2023
SE-4, 13 JUL 2023 to 10 AUG 2023