WAAS

W35A

RNP APCH

A NA

CH 82443

VANCE APP CON ★

126.75 346.325

4400

1274

1274

Baro-VNAV NA. Use Vance AFB allimeter setting; when not received, use Watonga allimeter setting; increase all MDA 40 feet, and increase LP and LNAV visibility Cats C/D 1/8 SM.

Procedure NA at night. Rwy 35 helicopter visibility reduction below 1 SM NA.

Rwy Idg

Apt Elev

TDZE

APP CRS

357°

KEND ATIS★

NM to ZABIA

115.4 263.15

SC-1, 13 JUL 2023 to 10 AUG 2023

3600

CIRCLING

GETLE

RNAV (GPS) RWY 35

FAIRVIEW MUNI

MISSED APPROACH: Climb to 3600 direct to GETLE and hold.

UNICOM 122.8 (CTAF) MISSED APCH FIX

> 4 NM -**GETLE**

Holding Pattern ZABIB HEKIX 8000 3600 YEXFU ≤3.00° 2.3 NM to TCH 40 **RW35 RW35** 3200 2040 5.1 NM **CATEGORY** 1800-11/2 MDA 1800-1 526 (600-1) 526 (600-11/2) 666 (700-1) 1940-1% LNAV MDA 1940-1 666 (700-1%)

2020-1

746 (800-1)

HOLD 8000

RW35

FAIRVIEW, OKLAHOMA Orig 05DEC19

MIRL Rwy 17-35

357°

FAIRVIEW MUNI (6K4) RNAV (GPS) RWY 35

2180-3

906 (1000-3)

2020-21/4

746 (800-21/4)

4 NM

1940-1

666 (700-1)