

WAAS CH 99417 W17A	APP CRS 173°	Rwy Idg TDZE 1553 Apt Elev 1563
--	------------------------	---


RNAV (GPS) RWY 17

HOBART RGNL (HBR)


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 45°C (113°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Altus/Quartz Mountain Rgnl altimeter setting and increase all DA 71 feet and all MDA 80 feet, increase LPV and LNAV/VNAV all Cats, LNAV Cats C and D and Circling Cat C visibility ¼ mile. Baro-VNAV NA when using Altus/Quartz Mountain altimeter setting. VDP NA with Altus/Quartz Mountain altimeter setting.



MISSED APPROACH: Climb to 4000 direct DOMLE and hold.

ASOS 133.325	ALTUS APP CON ★ 125.1 353.7	UNICOM 122.8 (CTAF)
------------------------	---------------------------------------	-------------------------------



ELEV 1563	TDZE 1553
-----------	-----------



4000 ↑		DOMLE 		4 NM Holding Pattern	
*LNAV only.		FOMOK 2.1 NM to RW17		BIPGE	
		IGIPY 3200		353° → 3400 ← 173°	
RW17		2240*		GP 3.00° TCH 35	
1.6 0.5 2.9 NM 7 NM		3200			
CATEGORY	A	B	C	D	
LPV DA	1803-1		250 (300-1)		
LNAV/ VNAV DA	1900-1¼		347 (400-1¼)		
LNAV MDA	2080-1	527 (600-1)	2080-1½ 527 (600-1½)	2080-1¾ 527 (600-1¾)	
CIRCLING	2080-1	517 (600-1)	2320-2¼ 757 (800-2¼)	2460-3 897 (900-3)	

SC-1, 13 JUL 2023 to 10 AUG 2023

SC-1, 13 JUL 2023 to 10 AUG 2023