À

SE-1, 13 JUL 2023 to 10 AUG 2023

WAAS CH 78209 W20A POOR 206° Rwy Idg 1020 1020 1028

RNAV (GPS) RWY 20 MOREHEAD-ROWAN COUNTY CLYDE A THOMAS RGNL (SYM)

MOREHEAD-ROWAN COUNTY CLYDE A THOMAS RGNL (S.Y.I NAV/VNAV NA below -17°C (2°F) or above

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Mount Sterling altimeter setting. When local altimeter setting not received, use Mount Sterling altimeter setting; increase all DA 50 feet and all MDA 60 feet; increase LPV and LNAV/VNAV all Cats visibility ½ mile, LNAV Cats C/D visibility ½ mile, and Circling Cats C/D visibility ½ mile.

MISSED APPROACH: Climb to 3600 direct CIPUL and hold.

setting: increase all DA 50 feet and all MDA 60 feet; increase LPV and LNAV/VNAV all Cats visibility ½ mile, LNAV Cats C/D visibility ½ mile, and Circling Cats C/D visibility ½ mile.					
AWOS-3 119.95		NAPOLIS CENTER .225 360.725		UNICOM 122.7 (CTAF) (
MISSED APCH FIX CIPUL V A NM ELEV 1028 TDZE 1020 206°	1039 //	4 NM (IF/IAF) IDABE (FAF) SOVSE UNICI 3 NM to RW20 W20 380	30 Vily	JOABE 3600 JOABE	-2960
OZ \$ 0	*LNAV only	UNICI 3 NM to RW20 *1.2 NM to RW20	SOVSE 2900 7	02 06° 20	4 NM Holding Pattern 26°
5500 × 100	7, K	*20 1.2 NM 1.8 NM -2.8 N			GP 3.00° TCH 40
vi Talan	CATEGORY	A A	В	C	D
	LPV DA	1270-7/8 250 (300-7/6)			
1120± ∧ ø	LNAV/ VNAV DA	1453-1½ 433 (500-1½)			
3	LNAV MDA	1440-1 4	120 (500-1)	1440-11/4	420 (500-1¼)
MIRL Rwys 2-20 C REIL Rwys 2 and 20 C	C CIRCLING	1520-1 49	2 (500-1)	1760-2 732 (800-2)	1820-2½ 792 (700-2½)