

APP CRS	Rwy Idg	10014
063°	TDZE	258
	Apt Elev	298

RNAV (RNP) Z RWY 6R

GUAM INTL (GUM)(PGUM)

▼

For uncompensated Baro-VNAV systems, procedure NA below 19°C (66°F) or above 48°C (119°F). GPS required.
*Missed approach requires a minimum climb of 285 feet per NM to 1400.

MALSR

MISSED APPROACH:

Climb to 3000 via track 063° to CIBOL and hold.

ATIS	GUAM CERAP	AGANA TOWER	GND CON	CLNC DEL
119.0	119.8 269.0	118.1 340.2	121.9 336.4	121.9

WUVEN 16000

3000 (35.9)

164°

Procedure NA for arrivals at WUVEN via A597 northwest bound.

Procedure NA for arrivals at PULEE via G467 R596 westbound.

(IAF) PULEE 13300

3000 102° (32.7)

(IAF) RASPE 4600 210K

3000 153° (5.1)

(IF) DALPE

2000 063° (7)

(FAF) FISON 724 1190

063° (5.3)

Λ 412

RW06R

Λ 812

Λ 412

MISSED APCH FIX

4 NM

063°

243°

CIBOL

MSA RW06R 2.5 NM

2600

• 1332

(IAF) BURLE 8100

3000 333° (9.9)

3000 337° (28.6)

Procedure NA for arrivals at ASADE via B586 southeast bound.

ASADE 15100

ELEV 298	D	TDZE 258
----------	---	----------

Procedure Turn NA

DALPE

3000

063°

2000

FISON

3000

CIBOL

GP 3.00° TCH 55

7 NM

5.3 NM

tr 063°

CATEGORY	A	B	C	D
RNP 0.30* DA		508-½	250 (300-½)	
RNP 0.30 DA		656-1	398 (400-1)	

AUTHORIZATION REQUIRED

341±

0.5% UP

0.7% DOWN

12014 X 150

10014 X 150

0.8% UP

0.6% DOWN

270±

242

554

TWR 352

063°

HIRL all Rwy's

GUAM, GU

Orig-C 15DEC11

13°29'N-144°48'E

GUAM INTL (GUM)(PGUM)

RNAV (RNP) Z RWY 6R