WAAS CH 62815 W32A	APP CRS 325°	Rwy ldg 6602 TDZE 1099 Apt Elev 1099

RNAV (GPS) RWY 32
ITHACA TOMPKINS INTL (ITH)

RNP APCH.

Circling NA to Rwys 15 and 33. Inop table does not apply to LNAV Cat A. Rwy 32 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Elmira altimeter setting and increase all DA 84 feet and all MDA 100 feet. For inop MALSR, increase LNAV Cat B visibility ¼ mile. For inop MALSR, when using Elmira altimeter setting, increase LPV all Cats visibility to RVR 6000, and increase LNAV Cat B visibility to 1½.

-19°C

MALSR

MISSED APPROACH: Climb to 3700 direct STATN and on track 282° to VAFKU and hold.

ATIS	ELMIRA APP CON ★	ITHACA TOWER ★	GND CON	CLNC DEL	UNICOM
125.175	124.3 257.8	119.6 (CTAF) L	121.8	121.8	122.95



ELEV 1099 D TDZE 1099



HIRL Rwy 14-32 L



CATEGORY	A	B	C	D
LPV DA	1385/40 286 (300-¾)			
LNAV MDA	2300/60 1201 (1300-1¼)		2300-2½ 1201 (1300-2½)	
C CIRCLING	2300-1¼ 1201 (1300-1¼)	2300-1½ 1201 (1300-1½)	2300-3 1201 (1300-3)	2440-3 1341 (1400-3)

NE-2, 13 JUL 2023 to 10 AUG 2023