

WAAS  
CH **99334**  
**W04A**

APP CRS  
**038°**

Rwy Idg  
TDZE  
Apt Elev

**4204**  
**1376**  
**1379**

EL DORADO/CAPT JACK THOMAS MEML (EQA)

RNAV (GPS) RWY 4

EL DORADO/CAPT JACK THOMAS MEML (EQA)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Colonel James Jabara altimeter setting and increase all DA 51 feet and all MDA 60 feet. Baro-VNAV NA when using Colonel James Jabara altimeter setting.

MISSED APPROACH: Climb to 3100 direct SMALE and hold.

AWOS-3P  
**120.875**

WICHITA APP CON  
**134.8 269.1**

UNICOM  
**122.8 (CTAF) 0**

INDIC

Procedure NA for arrivals at INDIC on V12 northeast bound.

MSA RW04 25 NM

3600

4 NM

038°

218°

SMALE

1809

1570

1408

1479±

RW04

WINUS 1.4 NM to RW04

(FAF) JIKAK

(IF/IAF) CERVK

(IF/IAF) ENBEW

3000 NoPT (6)

3000 (4.8)

3000 NoPT (6)

4 NM

218°

038°

128°

ASOSE

OBDRAW

3100

243°

116.9°

4 NM Holding Pattern

CERVK

JIKAK

3000

3100

SMALE

\*LNAV only

WINUS 1.4 NM to RW04

RW04

\*1860

GP 3.00°

TCH 40

4.8 NM

3.6 NM

1.4 NM

CATEGORY	A	B	C	D
LPV DA	1576-1	200 (200-1)	NA	
LNAV/VNAV DA	1626-1	250 (300-1)	NA	
LNAV MDA	1740-1	364 (400-1)	NA	
CIRCLING	1820-1 441 (500-1)	1960-1 581 (600-1)	NA	

HIRL Rwy 4-22 and 15-33 0

EL DORADO, KANSAS

EL DORADO/CAPT JACK THOMAS MEML (EQA)

Amtd 1A 11DEC14

37°46'N-96°49'W

RNAV (GPS) RWY 4