

WAAS CH 56637 W25A	APP CRS 248°	Rwy Idg TDZE 966 Apt Elev 966
--	------------------------	---

RNAV (GPS) RWY 25

BLOYER FLD (Y72)

NA

DME/DME RNP-0.3 NA. Use Camp Douglas altimeter setting; when not received, use Sparta/Fort McCoy altimeter setting and increase all MDA 20 feet. Helicopter visibility reduction below 1 SM NA. Procedure NA at night.

MISSED APPROACH:
Climb to 3000 direct FOSAT and hold.

VOLK APP CON ★ 135.25 244.875	VOLK CTAF 127.5	CTAF 122.9
---	---------------------------	----------------------

The main chart displays the RNAV (GPS) RWY 25 approach. Key features include:

- Restricted Areas:** R-6901A (1690± A), R-6901B (1543 A), and R-6904A.
- Mobility Obstacle Areas (MOA):** FALLS 1 MOA, VOLK WEST MOA, and VOLK SOUTH MOA.
- Altitudes:** 1282 A, 1077± (FAF) FIDPA, 2500 (S), 1202±, 1225±, 1512 A, 1939 A, 1826 A, and 2170 A.
- Navigation Aids:** FOSAT (068°/248°), GLAKE (158°/338°), and GLAKE (NoPT) (158°/338°).
- Distances:** 30 NM to GLAKE, 4 NM, and 30 NM to GLAKE (NoPT).
- Notes:** When restricted areas R-6901B active (hot/in use) procedure may not be available.

ELEV 966	TDZE 966
----------	----------

The detailed chart shows the descent and holding patterns for RWY 25:

- Descent:** 3900 X 75, 248° to RW25, 3000 FOSAT, 2500 FIDPA, 248° to 3000.
- Angles:** ≤ 3.00° TCH 40.
- Distances:** 4.7 NM, 5 NM, 4 NM.
- Holding Pattern:** 4 NM Holding Pattern at 3000.
- Table:**

CATEGORY	A	B	C	D
LP MDA	1440-1	474 (500-1)	1440-1 ³ / ₈ 474 (500-1 ³ / ₈)	NA
LNAV MDA	1480-1	514 (600-1)	1480-1 ³ / ₈ 514 (600-1 ³ / ₈)	NA
CIRCLING	1540-1 574 (600-1)	1560-1 594 (600-1)	1660-2 694 (700-2)	NA

MIRL Rwy 7-25
REIL Rwy 7 and 25

TOMAH, WISCONSIN

Orig 10DEC15

43°59'N-90°29'W

BLOYER FLD (Y72)

RNAV (GPS) RWY 25