TITUSVILLE, FLORIDA AL-8000 (FAA) 23054 WAAS 15001 Rwy Idg RNAV (GPS) RWY 15 APP CRS CH 50534 TDŹE 155° SPACE FLORIDA LAUNCH AND LANDING FACILITY (${
m TTS}$) Apt Elev W15A ALSF-2 MISSED APPROACH: Climb to 800, then climbing left turn V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Inop table does not apply. **A P** Α to 2500 direct EARTH and hold. ORLANDO APP CON NASA TOWER * **GND CON** 134.95 281.425 128.55 (CTAF) 284.0 121,75 RADAR REQUIRED EARTH ROCII Max 250K (FAF) STARS RW15 25 NZ 3000 105 ± R-2935 RW15 \bigcirc 397 R-2932 R-2933 **ELEV** TDZE 8 CAPE CANAVERAL SFS SKID STRIP -155° **ROCIT** 800 2500 **EARTH** 2500 **STARS** 1500 * LNAV only * 0.9 NM to RW1.5 RW15 GP 3.00° 1500 TCH 55 CATEGORY В Е LPV DA 208-1 200 (200-1) INAV/ DA 286-1 278 (300-1) VNAV LNAV MDA 360-1 352 (400-1)

C CIRCLING

420-1

411 (500-1)

460-1

940-23/4

451 (500-1) 931 (1000-23/4)

HIRL Rwy 15-33

940-3 931 (1000-3)

to 10 AUG 2023

13 JUL 2023

SE-3,