

WAAS CH 45515 W01A	APP CRS 006°	Rwy Idg 7002 TDZE 39 Apt Elev 50
--	------------------------	---

RNAV (GPS) RWY 1
SAVANNAH/HILTON HEAD INTL (SAV)


RNP APCH.




For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F).

MISSED APPROACH: Climb to 2500 direct SUTME and hold.

ATIS 123.75	SAVANNAH APP CON★ 120.4 353.775	SAVANNAH TOWER★ 125.975 (CTAF) 0 257.8	GND CON 121.9 348.6	CLNC DEL 119.55 291.775	UNICOM 122.95
----------------	------------------------------------	---	------------------------	----------------------------	------------------



ELEV	50	D	TDZE	39
------	----	----------	------	----



VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 74).

***LNAV only.**

SUTME

4 NM Holding Pattern

TERBE

MIZLU

RWY 01

1.3 NM to RWY 01

1.3 NM

4.6 NM

6.3 NM

2500

2000

2000

186°

006°

GP 3.00°

TCH 57

CATEGORY	A	B	C	D
LPV DA	239/40 200 (200-¾)			
LNAV/VNAV DA	384/60 345 (400-1¼)			
LNAV MDA	520/55 481 (500-1)		520-1⅜ 481 (500-1⅜)	
C CIRCLING	520-1 470 (500-1)		740-2 690 (700-2)	740-2¼ 690 (700-2¼)