

WAAS CH 48937 W31A	APP CRS 304°	Rwy Idg TDZE Apt Elev	3300 992 993
----------------------------------------	------------------------	-----------------------------	-----------------------------------------

RNAV (GPS) RWY 31

GLENCOE MUNI (GYL)


⚠

Baro-VNAV NA when using Hutchinson altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME DME/RNP-0.3 NA. VDP NA with Hutchinson altimeter setting. When local altimeter setting not received, use Hutchinson altimeter setting and increase all DA 43 feet and all MDA 60 feet, increase LPV and LNAV/VNAV Cat A/B visibility ½ mile.

⚠

MISSED APPROACH: Climb to 3000 direct AKIRE and hold.

AWOS-3 119.625	MINNEAPOLIS APP CON 134.7 284.7	UNICOM 122.8 (CTAF) 📶
--------------------------	-------------------------------------------	----------------------------------------



ELEV 993	TDZE 992
----------	----------

3000

AKIRE

* LNAV only

WELIK

1.7 NM to RW31

TUPUY

2600

OYITE

4 NM Holding Pattern

13

12

11

10

9

8

7

6

5

4

3

2

1

3000 X.75

304° to RW31

1560*

1 NM to RW31

1 NM

0.7

3.2 NM

6.1 NM

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	1242-7/8	250 (300-7/8)	NA	NA
LNAV/VNAV DA	1253-7/8	261 (300-7/8)	NA	NA
LNAV MDA	1360-1	368 (400-1)	NA	NA
C CIRCLING	1420-1 427 (500-1)	1480-1 487 (500-1)	NA	NA

REIL Rwy 13 and 31 **📶**

MIRL Rwy 13-31 **📶**