

WAAS CH 53615 W29A	APP CRS 284°	Rwy Idg TDZE 96 Apt Elev 107
--	------------------------	--

RNAV (GPS) RWY 29
JESUP-WAYNE COUNTY (JES)


RNP APCH.

Baro-VNAV and VDP NA when using Savannah/Hilton Head Intl altimeter setting.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). Rwy 29 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Savannah/Hilton Head Intl altimeter setting: increase LPV DA to 485 and LNAV/VNAV DA to 542; increase all MDA 140 feet and visibility LNAV Cat C ¾ SM, Cat D ½ SM, and Circling Cat C/D ½ SM. Inop table does not apply to LPV and LNAV/VNAV all Cats and LNAV Cats A/B. For inop ALS, increase LNAV Cat C visibility to 1½ SM. For inop ALS when using Savannah/Hilton Head Intl altimeter setting, increase LPV all Cats visibility to 1½ SM and LNAV/VNAV all Cats visibility to 1¾ SM.

MALSF

MISSED APPROACH:
Climb to 2700 direct KOGSE and hold.

AWOS-3PT 118.125	JACKSONVILLE CENTER 126.75 277.4	UNICOM 122.8 (CTAF)
----------------------------	--	-------------------------------



ELEV 107 TDZE 96

MIRL Rwy 11-29

2700 KOGSE

284° to RWY29

5500 X 100

0.7% UP

2700


284°

1700

104°

2700

GP 3.00° TCH 45

2700 ↑	KOGSE ✱	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 37).			4 NM Holding Pattern	
						
CATEGORY		A	B	C	D	
LPV	DA	364-1		268 (300-1)		
LNAV/ VNAV	DA	421-1¼		325 (400-1¼)		
LNAV	MDA	500-1 404 (400-1)				500-1¼ 404 (400-1¼)
CIRCLING		520-1 413 (500-1)	560-1 453 (500-1)	780-2 673 (700-2)	780-2¼ 673 (700-2¼)	

SE-4, 13 JUL 2023 to 10 AUG 2023

SE-4, 13 JUL 2023 to 10 AUG 2023