

WAAS CH 78135 W18A	APP CRS 179°	Rwy Idg TDZE Apt Elev	6000 1350 1350
----------------------------------------	------------------------	-----------------------------	-------------------------------------------

RNAV (GPS) RWY 18

FRENCH VALLEY (F70)



▼

NA

DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA with Ramona altimeter setting. Circling NA west of Rwy 18-36. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). When local altimeter setting not received use Ramona altimeter setting: increase LPV DA to 1685 feet and all visibilities ¼ mile, LNAV/VNAV DA to 1955 feet and all visibilities ¾ mile, all MDA 80 feet and LNAV visibility Cat B ¼ mile, Cat C ½ mile, and Circling visibility Cat C ¼ mile. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2500 then climbing right turn to 5000 direct JESEX and hold.

AWOS-3 119.025	MARCH APP CON* 133.5 306.975	UNICOM 122.8 (CTAF)
--------------------------	----------------------------------------	-------------------------------



2500	5000	JESEX				
* LNAV only		DISEY 3.8 NM to RW18	DANNN 3500	ECULU	TIQMU	5 NM Holding Pattern
RW18		*1.2 NM to RW18	2600*	3500	3800	4600
1.2 NM		2.6 NM	2.8 NM	2.2 NM	5.1 NM	
GP 3.00° TCH 40						
CATEGORY		A		B	C	D
LPV	DA	1600-7/8		250 (300-7/8)	NA	
LNAV/ VNAV	DA	1871-13/4		521 (600-13/4)	NA	
LNAV	MDA	1780-1	430 (500-1)	1780-11/4 430 (500-11/4)		NA
C	CIRCLING	2020-1	670 (700-1)	2060-2 710 (800-2)		NA