

APP CRS
170°

Rwy Idg
TDZE
Apt Elev

7800
499
501

RNAV (RNP) Z RWY 17L

LOUISVILLE MUHAMMAD ALI INTL (SDF)


RNP AR APCH.

▼ For uncompensated Baro-VNAV systems, procedure NA below -14°C or above 54°C. For inop ALS, increase RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized, except for arrivals at CHUWE, KAEDN, ALANB, and COBLR.

MALSR

MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 direct ILL VORTAC and hold, continue climb-in-hold to 3000.

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6	CLNC DEL 126.1 275.8	CPDLC
--------------------------	--------------------------------------------	----------------------------------------	-------------------------------	--------------------------------	-------



ELEV 501

TDZE 499

D

HIRL all Rwys

TDZ/CL Rwys 17L, 17R, 35L and 35R

VGSI and RNAV glidepath not coincident (VGSI Angle 3.32/TCH 71).

1000

3000

ILL

See planview for multiple IF locations.

2500

170°

GP 3.00°

TCH 55

6.1 NM

RWY 17L

CATEGORY	A	B	C	D
RNP 0.30 DA	936/50		437 (500-1)	

AUTHORIZATION REQUIRED