

WAAS CH 86913 W36A	APP CRS 357°	Rwy Idg 5135 TDZE 8 Apt Elev 8
--	------------------------	---


RNAV (GPS) RWY 36L

LAKEFRONT (NEW)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting: increase LPV DA to 369 feet, LNAV/VNAV DA to 460 feet and all visibilities ½ mile; increase all MDA 40 feet and Circling Cat D visibility ¼ mile. VDP and Baro-VNAV NA when using Louis Armstrong New Orleans Intl altimeter setting.

MISSED APPROACH: Climb to 2100 direct PNDAR and via track 064° to SNAKI and hold.

ATIS 124.9	NEW ORLEANS APP CON NORTH 133.15 290.3 SOUTH 123.85 256.9	LAKEFRONT TOWER ★ 118.95(CTAF) 0	GND CON 121.7	CLNC DEL 127.4
----------------------	---	--	-------------------------	--------------------------



ELEV 8	TDZE 8
MIRL Rwy 18R-36L	
MIRL Rwy 9-27 and 18L-36R	
REIL Rwy 9, 18L, 36L and 36R	

2100	PNDAR	tr 064°	SNAKI	Procedure Turn NA
*LNAV only.				
FIRMA 2.2 NM to RW36L				
HEBOT				
TOYBO				
GODRD				
RW36L				
*1.7 NM to RW36L				
1.7 NM 0.5 NM 2.9 NM 3.1 NM 3 NM				
CATEGORY	A	B	C	D
LPV DA	340-1⅛ 332 (400-1⅛)			
LNAV/VNAV DA	431-1⅜ 423 (500-1⅜)			
LNAV MDA	600-1 592 (600-1)		600-1¾ 592 (600-1¾)	
CIRCLING	600-1 592 (600-1)		700-2 692 (700-2) 820-2¾ 812 (900-2¾)	

