

IEEE 802.1X: Architecture, Security Considerations, and Identity-Based Network Access

Marina Schwerz Bon¹, Pedro Boeira Webber¹

¹Universidade do Vale do Rio dos Sinos (UNISINOS)
Porto Alegre – RS – Brazil

Abstract. *IEEE 802.1X is a port-based network access control protocol that plays a key role in identity-driven network security. It ensures that only authenticated users or devices can access network resources, providing a strong foundation for securing both wired and wireless enterprise environments. This article presents an analysis of 802.1X, including how it functions, integration with the Extensible Authentication Protocol (EAP), and key characteristics such as the three-party authentication model. Drawing from peer-reviewed literature, official standards, and technical case studies, the article examines the protocol's security aspects. Additionally, a real-world case study is used to illustrate the challenges and solutions involved in implementing 802.1X. Finally, limitations and challenges are discussed, offering a critical view of the protocol's applicability in modern access and identity management scenarios.*

1. Introduction

IEEE 802.1X is an IEEE standard for port-based network access control that plays a pivotal role in modern network access and identity management. In essence, 802.1X enables network administrators to restrict network access ports to authenticated and authorized devices. By doing so, preventing unauthorized clients from communicating on the network [IEE 2020]. It provides a framework for authenticating devices (or users) at the point of network attachments (such as a switch port or Wi-Fi access point) before granting access to network services. By requiring devices to present credentials and be verified by an authentication server, 802.1X helps ensure that only known or trusted identities gain access to network resources, supporting organizational security and identity management objectives.

Moreover, IEEE 802.1X is not an authentication algorithm by itself, but a framework that encapsulates the EAP for use on local area networks [Krishnaveni and Haripriya 2024a]. This means 802.1X can support a variety of authentication methods (such as passwords, certificates, or one-time tokens) through EAP, making it a flexible choice for identity-based network access control. Moreover, its relevance has grown with the rise of Wi-Fi and wired LAN security, where it is used to implement mechanisms like WPA2-Enterprise for Wi-Fi and to secure wired Ethernet ports in office networks. In summary, 802.1X serves as a critical link between network access and identity verification, ensuring that network connectivity is tied to a successful authentication and authorization mechanism [IEE 2020].

2. Methodology

This article's research was conducted with a focus on scholarly and standards-based sources to ensure accuracy and credibility. We began by consulting the primary technical

standards and documents for 802.1X and related protocols. The official IEEE 802.1X standard (in its latest revision) was a key reference point, providing authoritative definitions and descriptions of the protocol’s architecture [IEE 2020]. In addition, relevant RFCs were reviewed, given that 802.1X relies on the Extensible Authentication Protocol.

Beyond standards documents, we performed literature searches in academic databases to find peer-reviewed articles examining 802.1X or closely related security protocols. Keywords such as “802.1X authentication,” “port-based network access control,” and “EAP security” were used to locate relevant papers. Moreover, we identified an influential early security analysis of 802.1X from 2002, as well as a recent (2023) study on 802.1X in enterprise Wi-Fi, to ensure our article acknowledges both the origins and current state of knowledge. In all cases, Wikipedia or non-scientific websites were avoided; instead, we relied on primary standards (IEEE, IETF) and scholarly publications to build the content. Each source was evaluated for its relevance and authority: standards for protocol specifications, and academic papers for analysis. This methodology ensures that the article is grounded in technical information and trusted articles.

3. Literature Review

Several works in the literature have discussed IEEE 802.1X and related authentication frameworks, providing points of comparison for our research. One of the earliest comprehensive analyses of 802.1X’s security was by Mishra and Arbaugh (2002), who examined the protocol in the context of Wi-Fi networks. In their technical report, the authors identified design weaknesses that could be exploited for man-in-the-middle and session hijacking attacks, concluding that the combination of 802.1X with the 802.11 wireless standard did not provide sufficient security without modifications. Moreover, they pointed out that lacking mutual authentication in some EAP methods and the absence of cryptographic protection allowed an attacker to hijack sessions even after a successful authentication. Their work prompted a “security rethink” [Krishnaveni and Haripriya 2024b]. In fact, many improvements in later revisions of 802.1X (and in Wi-Fi security such as WPA2) addressed the issues of missing message integrity and authentication which their analysis brought to light. For example, their recommendation to add message authenticity checks for EAP was influential in the development of protections like 802.11i/WPA2’s cryptographic handshakes and enhancements in the 802.1X protocol.

More recently, researchers have studied 802.1X in the context of modern enterprise networks and user behavior [Palamà et al. 2023] provides an analysis focusing on WPA-Enterprise Wi-Fi (which relies on 802.1X for authentication) and the human factors of security. In their study, they conducted experiments with university students to see how users and devices respond to rogue access points in an education roaming network. Which revealed practical weaknesses such as even when 802.1X is properly implemented, user misconfiguration or unawareness can undermine security. Additionally, in a controlled experiment, an attacker was able to steal user credentials (Eduroam logins) from roughly one-third of tested students by impersonating a legitimate network [Palamà et al. 2023]. The study highlighted that many users fail to notice or act upon security warnings (such as invalid certificates). This complements technical analyses by showing that real-world deployments of 802.1X are only as secure as their weakest link – which often includes user training and device configuration.

Additional references provide foundational and technical perspectives on the IEEE 802.1X standard and its implementation. Aiello (1991) provides a security analyses of the IEEE 802.1X standard, detailing the potential risks associated with the protocol in its early stages of development [Aiello 1991]. Silva (2012) presents a case study focused on the application of IEEE 802.1X in the Ethernet network of the Legislative Chamber of the Federal District (CLDF), exploring its practical deployment and challenges in a governmental setting [da Silva 2012]. Kachhara and Kumar (2018) investigate the implementation of the IEEE 802.1X port-based authentication mechanism in Ethernet environments, discussing the system's performance and its suitability for various use cases [Kachhara and Kumar 2018]. Agarwal and Wang (2005) analyze the performance impact of security protocols, including IEEE 802.1X, in wireless local area networks, highlighting its potential effects on overall system performance and providing insights into optimizing security measures [Agarwal and Wang 2005].

In comparison to these works, our article focuses on a more comprehensive analysis of the protocol, documenting features, technical aspects, and security considerations. [Krishnaveni and Haripriya 2024b]'s work was vulnerability-driven, focusing on breaking the protocol in specific scenarios, while [Palamà et al. 2023]'s work is an applied security study highlighting deployment troubles. By contrast, we aim to synthesize information from standards and multiple studies to present a cohesive overview of 802.1X and how it works alongside EAP.

4. Characteristics

In the following section characteristics of the 802.1x protocol will be analysed and discussed.

Port-Based Access Control: The fundamental characteristic of 802.1X is that it enforces authentication on ports at the link layer. Moreover, when 802.1X is enabled on a network interface, that interface will not forward traffic until the connecting device has authenticated. 802.1X defines two logical portions of the port: an “uncontrolled port”, which only allows authentication exchange traffic (EAP messages), and a “controlled port”, which carries normal user data but is blocked until authentication succeeds [Vollbrecht et al. 2004]. If a device fails to authenticate, the controlled port remains closed, preventing access to the network. This port-based mechanism works because it takes into consideration that at layer 2, all network access funnels through an entry point (a port) that can be locked or unlocked based on identity verification.

Three-Party Authentication Model: IEEE 802.1X uses a three-party model consisting of a device or user, Authenticator, and Authentication Server. The device is attempting to gain network access. The authenticator is the network device controlling the port that handles communication between the device and the network. The authenticator acts as an intermediary: it does not decide whether a user is allowed access, but sends credentials to the authentication server so it can validate them. This architecture separates duties: the Authenticator “gates” the port and enforces policy, the device is the requester, and the Authentication Server performs the validation [Kumar 2015]. The benefit of this design is scalability and centralization of identity management.

Use of EAP: The 802.1X protocol does not rely on a single authentication method. Instead, it uses EAP as a flexible framework that supports various authentication tech-

niques, known as “EAP methods.”, this design allows 802.1X to support different authentication mechanisms, such as passwords, certificates, or tokens—without requiring changes to the protocol itself. According to the standard’s architecture, the 802.1X-controlled port remains closed until a complete and successful EAP authentication exchange has occurred [IEE 2020].

Network Agnosticism and Extensibility: 802.1X was originally developed for wired Ethernet ports, but it was designed to work across different types of network media. It quickly became the standard for authentication in wireless networks as well, especially through its integration with IEEE 802.11i for Wi-Fi security. The protocol’s port-based access model can be applied to any MAC-layer technology that supports enabling or disabling a port. Because of this flexibility, 802.1X is now used in many environments: from wired office networks, to enterprise Wi-Fi, and even in VPNs. One reason for its wide use is its simplicity—it only requires a basic message exchange using EAP and a port machine. The specific access policies are left to the network configuration or extended standards [Kumar 2015].

In summary, the key features of 802.1X can be characterized as: port-based access enforcement (controlled vs uncontrolled port logic), a three-party authentication architecture separating device/user, authenticator, and auth server, the use of EAP for a authentication method support, and works across various network types and can be easily adapted to different security policies, allowing it to serve as a general solution for network access across technologies. These features make 802.1X essential for secure, identity-based network access.

5. Technical Analysis of 802.1X

In the 802.1X authentication process, three main parts work together: the device, the network port (authenticator), and the authentication server, as illustrated in Figure 1. The authentication process begins when the device sends an EAPOL-Start (Extensible Authentication Protocol over LAN) message to signal its intention to authenticate. EAPOL is a protocol used specifically in LAN environments to carry EAP messages between the device and the authenticator. The authenticator replies with an EAP-Request/Identity message, asking for the device’s identity. The device then responds with an EAP-Response/Identity, which the authenticator encapsulates into a RADIUS or Diameter message and forwards to the authentication server [IEE 2018].

During this initial exchange, the port remains locked. If the server approves the device, it sends an EAP-Success message. If authentication fails, it sends an EAP-Failure, and the port stays blocked. Many systems also re-check the connection from time to time, in order to re-authentication and maintain security or update encryption keys. When the device disconnects, it can send an EAPOL-Logoff message so the port closes immediately [Vollbrecht et al. 2004].

Protocols like RADIUS (Remote Authentication Dial-In User Service) or Diameter (a more advanced alternative) are used to carry EAP messages between the authenticator and authentication server.

Another technical aspect is how 802.1X is also involved in managing encryption keys after authentication. In wireless networks using WPA2, once a device successfully authenticates using 802.1X, it starts a 4-way handshake to generate encryption




Figure 1. 802.1X three-party authentication flow using EAP and RADIUS/Diameter.

keys for secure communication. Figure 2 illustrates how the device and authenticator exchange EAPOL messages, and how the authenticator communicates with the authentication server using RADIUS. It also includes the 4-way handshake, which sets up encryption keys after the device is successfully authenticated. Moreover, 802.1X not only controls who gets access to the network, but also helps create the encryption keys used to protect data after access is granted. By handling both access and encryption, 802.1X plays a key role in keeping networks secure.

6. 802.1X VS EAP Protocol

It's important to understand the difference between IEEE 802.1X and EAP, as they are often confused. EAP itself is not tied to any specific network technology or encryption system. It was originally designed for point-to-point links, like dial-up connections using PPP.

The protocol provides a standard format for sending authentication messages, such as Requests, Responses, Success, and Failure, and allows different “EAP methods” to be used. These methods define how credentials are verified. For example, one method might ask for a password, while another could use certificates with a TLS handshake. Since EAP is media-independent, it requires a transport mechanism to work over various types of networks. In PPP connections, it runs directly over the link. In IP-based networks, it is typically carried within protocols like RADIUS or Diameter. In local area networks (LANs), IEEE 802.1X was created to provide a way to securely transport EAP messages. In short, EAP handles the authentication dialogue, while 802.1X provides the structure to deliver that dialogue over wired or wireless LANs, connecting the device to the authentication server.

Importantly, the 802.1X standard does not define any authentication method itself, all of which is handled by EAP. As one source describes it: “802.1X is not an authentication protocol but a wrapping of an existing authentication framework” [Kumar 2015]. That underlying framework is EAP, as defined in RFC 3748 [Vollbrecht et al. 2004]. What 802.1X adds is the port control logic and the enforcement mechanism around the EAP exchange. Each protocol has a distinct role




Figure 2. 802.1X authentication over Wi-Fi, showing EAPOL and RADIUS message flow and the final 4-way handshake.

- 802.1X decides when and where authentication happens, for example, when a device connects to a network port. It also handles how authentication messages travel over the local link and what action to take based on the result. It focuses on the state of the network connection, authorized or unauthorized.
- EAP defines what the authentication looks like, it's the actual conversation between the device and the server. This can range from a simple password check to a complex TLS handshake with certificate validation. EAP doesn't care about the network type, it could be used over Ethernet, Wi-Fi, or other links.

Another key difference between 802.1X and EAP lies in their scope. IEEE 802.1X is limited to the local access network. 802.1X handles authentication and opens the port. After that, it remains inactive unless the device disconnects or needs to re-authenticate. In contrast, EAP can be used in many other contexts beyond LAN access. For example, EAP can operate inside tunnel protocols or be used for authentication in 4G/5G mobile networks. In fact, EAP can be used over point-to-point links, VPNs, and other situations that don't involve 802.1X at all. In contrast, 802.1X always depends on EAP to carry out the authentication. Even in its earliest versions, EAP was the actual mechanism used to verify credentials, so without EAP, 802.1X cannot function.

7. Security Aspects

Historically, security has been a critical concern in IEEE 802.11 wireless networks, particularly in the infrastructure mode, where clients communicate through a central entity known as an Access Point (AP). Upon initiating communication, a wireless client (STA) must progress through three defined states with the AP: (1) unauthenticated and unassociated, (2) authenticated and unassociated, and (3) authenticated and associated. These

transitions occur through 802.11 management frames, with authentication and association being prerequisites for data transmission.[Aiello 1991]

The 802.1X framework utilizes the Extensible Authentication Protocol (EAP) to facilitate identity verification between the supplicant (client), the authenticator (AP or switch), and the authentication server (typically RADIUS). The strength of this architecture lies in its adaptability: EAP supports a wide range of authentication methods, including EAP-TLS (certificate-based), EAP-TTLS (tunneled), PEAP (Protected EAP) and one-time password schemes. Among these, EAP-TLS is recognized as the most secure due to its use of mutual certificate authentication and encrypted key exchange.[Kumar 2015]

The primary flaw in the design is the asymmetrical treatment of supplicants and access points in the state machines. As defined by the standard, the authenticator port is in the controlled state only when the session is authenticated. This is not true for the supplicant, whose port is essentially always in the authenticated state. One-way authentication of the supplicant to the access point can expose the supplicant to potential Man-In-The-Middle (on-path) attacks, where an adversary impersonates an access point to the supplicant and simultaneously acts as a client to the legitimate network access point [Aiello 1991].

The 802.1X authenticator state machine accepts only EAP response messages from the supplicant and sends only EAP request messages to the supplicant. Similarly, the supplicant state machine does not send any EAP request messages. Observably, the state machines perform only one-way authentication. The trust assumption embedded in this design is that access points are trusted entities, which is a misjudgment. EAP-TLS does provide strong mutual authentication, but is not mandatory and can be bypassed. Even when EAP-TLS is used, the aforementioned design error can nullify its security guarantees [Aiello 1991].

8. Case Study: Real-World Implementation of 802.1X

The Legislative Chamber of the Federal District (CLDF) conducted a project to implement network authentication using the IEEE 802.1X protocol over its Ethernet infrastructure. The goal was to strengthen access control by ensuring that only authenticated users and devices could access the network [da Silva 2012].

8.1. Environment and Architecture

During the testing phase, the PEAP-MS-CHAPv2 authentication method was used. It proved to be fully functional in the CLDF's environment. Authentication was performed transparently using the same credentials employed by users to log into the institutional domain, thus maintaining a seamless user experience and integration with the Microsoft Active Directory (Windows Server 2008) already in place [da Silva 2012].

Tests were conducted using the native 802.1X supplicants found in Windows Vista and Windows 7, eliminating the need to install additional client software. Authentication occurred at logon, ensuring that network access was granted only after successful identity verification.

8.2. Key Results

- **Transparent operation:** The use of existing domain credentials meant no changes to the user's login process, facilitating user adoption, usability and ac-

ceptability.

- **Low operational cost:** The implementation did not require new hardware or software purchases, only investment in staff training and possibly third-party services for full deployment.
- **Compatibility with current infrastructure:** Leveraging native OS capabilities and existing domain architecture made deployment straightforward.

The CLDF found the implementation of IEEE 802.1X to be technically viable and operationally effective. It adds a significant security layer and aligns with the institution's broader digital modernization efforts. While it does not completely eliminate all access control threats, it makes unauthorized access substantially more difficult and is a strong candidate for formal adoption within the network security policy [da Silva 2012].

9. Challenges and Limitations of 802.1X

Despite its strengths, 802.1X is not a perfect solution. It introduces several challenges, especially in larger, older or heterogeneous environments.

1. **Complexity of Deployment:** Setting up 802.1X requires configuring network switches, supplicants on endpoints, and RADIUS servers. For organizations without existing PKI infrastructure, certificate management becomes a significant hurdle [Kachhara and Kumar 2018].
2. **Legacy Device Support:** Many older devices (printers, VoIP phones, IoT) do not support 802.1X. Workarounds can introduce security gaps that can be exploited.
3. **User Experience Issues:** Users may experience connection delays, credential prompts, or disconnections during certificate expiration or policy updates. This can lead to resistance from non-technical users [Agarwal and Wang 2005].
4. **Maintenance Overhead:** Regular certificate rotation, policy updates, and troubleshooting authentication failures require ongoing administrative effort [Agarwal and Wang 2005].

10. Conclusion

IEEE 802.1X provides port-based access control by binding network access to authenticated identities through a three-party framework. It effectively secures networks by making sure only authorized devices can connect.

The CLDF case study demonstrated 802.1X's effectiveness in restricting access to authenticated users, though challenges like device compatibility and authentication delays remain. Despite these issues, 802.1X is widely regarded as a robust, identity-driven access control method, now used in many security frameworks for protected networks.

In conclusion, the reviewed analysis shows that IEEE 802.1X, despite its implementation challenges and known flaws, remains highly relevant for secure, identity-based network access. Its port-based, credential-driven model is widely adopted (especially in enterprise and sensitive environments) because it enforces that only authenticated devices can join the LAN. With careful deployment (strong EAP methods, backup strategies for unsupported devices, ongoing maintenance and strong access control policies), 802.1X continues to serve as a key building block of contemporary access and identity management.

References

- (2018). IEEE Standard for Port-Based Network Access Control.
- (2020). IEEE Standard for Local and Metropolitan Area Networks—Port-Based Network Access Control. Revision of IEEE Std 802.1X-2010, incorporating 802.1Xbx-2014 and 802.1Xck-2018.
- Agarwal, A. K. and Wang, W. (2005). Measuring performance impact of security protocols in wireless local area networks. In *Proceedings of the 2005 IEEE Workshop on Wireless Networks*, Raleigh, NC, USA. Accessed: 2025-04-25.
- Aiello, W. A. (1991). An initial security analysis of the ieee 802.1x standard. Accessed: 2025-04-25.
- da Silva, R. M. (2012). Estudo de caso: autenticação ieee 802.1x aplicada à rede ethernet da câmara legislativa do distrito federal. Trabalho de conclusão de curso (tcc), Centro Universitário de Brasília (UniCEUB), Brasília, DF. Acessado em 25 de abril de 2025.
- Kachhara, S. and Kumar, K. A. (2018). Implementation of ieee 802.1x port-based authentication mechanism for ethernet. *International Journal of Computer Trends and Technology*, 64(1):17–23. Accessed: 2025-04-25.
- Krishnaveni, M. and Haripriya, P. (2024a). An Analysis of IEEE 802.1X Authentication Protocol and Its Security Issues. *International Journal of Research in Engineering and Science (IJRES)*, 12(2):55–60.
- Krishnaveni, M. and Haripriya, P. (2024b). An analysis of ieee 802.1x authentication protocol and its security issues. *International Journal of Research in Engineering and Science (IJRES)*, 12(2):55–60.
- Kumar, P. (2015). A review of 802.1x-eap authentication for enterprise wlans. *International Journal of Latest Trends in Engineering and Technology (IJLTET)*, 5(3):208–212.
- Palamà, I., Amici, A., Bellicini, G., Gringoli, F., Pedretti, F., and Bianchi, G. (2023). Attacks and vulnerabilities of Wi-Fi Enterprise networks: User security awareness assessment through credential stealing attack experiments. *Computer Communications*, 212:129–140.
- Vollbrecht, J., Carlson, J. D., Blunk, L., Aboba, B. D., and Levkowitz, H. (2004). Extensible Authentication Protocol (EAP). RFC 3748 (Standards Track).