

Near-Eye Purkinje Image Simulation and Capture for Accommodation-Aware Eye Tracking

Abstract

CCS Concepts

- Human-centered computing → Mixed / augmented reality;
- Computing methodologies → Rendering; Computer vision.

Keywords

eye tracking, deep learning, computer graphics

ACM Reference Format:

. 2025. Near-Eye Purkinje Image Simulation and Capture for Accommodation-Aware Eye Tracking. In *Proceedings of SIGGRAPH*. ACM, New York, NY, USA, 4 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

1 Problem

1.1 Challenges of reconstructing Purkinje reflections via 3D Gaussian Splatting (3DGS).

3DGS represents view-dependent appearance by using low-order Spherical Harmonics (SH) [Kerbl et al. 2023], therefore, accurately modeling high-frequency, view-dependent specular appearance remains challenging [Jiang et al. 2024; Tang et al. 2025]. More importantly, P3 and P4 are formed through transmission and reflection across the multiple ocular interfaces of eyes, whereas rasterization-based 3DGS does not explicitly model these secondary optical paths [Wu et al. 2025] (see Fig. X). In addition, Lu et al. [Lu et al. 2020] and Wu et al. [Cornsweet and Crane 1973] show that P3 is formed at a different optical focal plane from P1 and P4, while higher-order Purkinje reflections are relatively weak and therefore more susceptible to defocus and low contrast. Finally, Purkinje locations vary jointly with accommodation, vergence, subject-specific ocular geometry, and camera-illumination configuration [Lu et al. 2020; Ozhan et al. 2023]. Purkinje reflections are better characterized as dynamic optical signals governed by ocular optics rather than stable surface textures, making it difficult for standard 3DGS to reconstruct them consistently with their underlying physical behavior.

2 Introduction

3 Related works

To compare our work with existing eye convergence and accommodation tracking, we review related works from two main areas: physical feature-based experimental designs and virtual eye modeling and neural rendering. To clearly show the technical features of previous works, Table 1 categorizes and compares these methods

based on their hardware setups, algorithms, operating modes, and tracking accuracy.

3.1 Eye Accommodation Tracking

In stereoscopic and near-eye displays, the Vergence-Accommodation Conflict (VAC) [Hoffman et al. 2008] arises when the eyes converge to a virtual 3D depth while the crystalline lens remains focused on the physical display plane. This mismatch can reduce fusion performance and cause visual discomfort. Recent VAC-related depth-perception studies therefore use eye-tracking and controlled optical setups to measure vergence responses under different perceived-depth conditions, highlighting the need for objective and reproducible eye-based measurements in VAC-related experiments [Bontha and Arefin 2024; Sturgeon et al. 2025]. However, vergence alone does not fully describe the accommodative state of the eye. Accommodation is harder to measure directly, especially in compact near-eye systems. Higher-order Purkinje images provide a promising optical cue because they arise from reflections at ocular interfaces, including the crystalline lens surfaces, and vary with the lens geometry during accommodation. Lu et al. [2020] use a multi-camera, multi-LED AR-glasses prototype to track higher-order Purkinje images, extending conventional pupil–corneal-reflection tracking toward accommodation-aware sensing in a near-eye form factor. Ozhan et al. [2023] extend this direction by collecting multi-subject Purkinje measurements and combining a Purkinje imaging setup with a Multi-Layer Perceptron (MLP)-based regression model to estimate dynamic vergence and accommodation across users.

These works suggest that higher-order Purkinje reflections can serve as physically meaningful cues for accommodation-aware eye tracking, but they also reveal a practical challenge: P3 and P4 are faint, easily defocused, and highly sensitive to LED–camera–eye geometry. Motivated by this limitation, we first build a controllable 3D optical eye model to analyze the formation, visibility, and stability of P1–P4 under near-eye infrared imaging conditions.

3.2 Computational Eye Modeling

Computational eye models are widely used to generate labeled data for gaze estimation. UnityEyes, NVGaze, and RIT-Eyes synthesize controllable variations in gaze, ocular geometry, appearance, and illumination for training eye-tracking models [Kim et al. 2019; Nair et al. 2020; Wood et al. 2016]. These systems capture visible eye-region cues effectively, but they primarily target eye rotation, pupil localization, and segmentation rather than accommodation-dependent changes within the crystalline lens.

Neural eye representations improve visual realism and relighting. EyeNeRF combines an explicit eyeball surface with implicit volumetric representations for view synthesis, gaze animation, corneal refraction, and relighting [Li et al. 2022]. Khademi et al. extend a similar hybrid formulation to near-field point sources and structured illumination [Khademi et al. 2026]. However, these methods focus

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

SIGGRAPH, 979-8-4007-1549-5/2025/08

© 2025 Copyright held by the owner/author(s).

ACM ISBN 978-x-xxxx-xxxx-x/YYYY/MM

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

Table 1: Comparison of representative approaches related to vergence and accommodation sensing. Method denotes the primary sensing principle or eye representation, while Estimator denotes the strategy used to infer the target quantity. V/A Target specifies whether accommodation (A), vergence (V), both, or neither are directly estimated in the reported work. Near-eye indicates whether the method is demonstrated in a physical near-eye configuration. Green indicates favorable suitability for compact joint vergence–accommodation tracking, yellow indicates moderate suitability, and red indicates limited suitability.

Ref.	Camera	Illum.	Method	Estimator	V/A Target	Near-eye	Accuracy
[Cornsweet and Crane 1973]	Single	IR	Purkinje	Model-based	Neither	No	High
[Morimoto et al. 2002]	Single	NIR	PCCR	Model-based	Neither	No	Mid
[Sturgeon et al. 2025]	Built-in	Built-in	Gaze	Model-based	V only	Yes	Mid
[Bontha and Arefin 2024]	None	None	Haploscope	N/A	Neither	Yes	N/A
[Lu et al. 2020]	Multiple	IR	Purkinje	Data-driven	Both	Yes	High
[Ozhan et al. 2023]	Single	NIR	Purkinje	Data-driven	Both	No	High
[Nair et al. 2020]	Virtual	RGB/IR	Eye model	N/A	Neither	Synthetic	N/A
[Li et al. 2022]	Multiple	Visible	Eye model	N/A	Neither	No	N/A
[Khademi et al. 2026]	Multiple	Controlled	Eye model	N/A	Neither	No	N/A
[Ahn and Lee 2025]	Single	IR	Purkinje	Data-driven	Neither	No	Mid
[Sharifzadeh 2024]	Virtual	Simulated	Purkinje	Model-based	Neither	No	N/A
[Wu et al. 2022]	Single	IR	Purkinje	Model-based	Neither	No	High
[Lin et al. 2026]	Virtual	Simulated	Eye model	N/A	Neither	Synthetic	N/A

on photorealistic appearance and do not explicitly predict P3/P4 formation or accommodation-dependent internal ocular geometry.

Purkinje-based systems model internal reflections more directly. Wu et al., Idrizović et al., and OpenIrisDPI use P1 and P4 for accurate eye-rotation tracking [Idrizović et al. 2025; Ressmeyer et al. 2026; Wu et al. 2023]. Lu et al. further model higher-order reflections with multiple cameras and infrared LEDs to estimate vergence and accommodation [Lu et al. 2020]. Ozhan et al. simulate P1–P4 across accommodation and vergence states, validate the predictions against real captures, and use the resulting features for dynamic estimation [Ozhan et al. 2023]. Our work follows this direction by using a controllable optical eye model to predict how accommodation, vergence, and LED–camera geometry affect P1–P4 formation.

3.3 Physics-Based Optical Design

Differentiable optical design provides a possible framework for optimizing the illumination and imaging layout of a Purkinje capture system. Na et al. show that image-domain losses can be propagated through differentiable ray tracing to physical optical parameters [Na et al. 2024]. For our system, the same principle could be applied to LED position, camera pose, focal distance, aperture, and field of view.

The optimization criteria should follow the capture behavior of higher-order Purkinje reflections. Lu et al. show that P3 is weaker than P1, lies on a different focal plane, and may leave the camera field of view as gaze changes; their system therefore uses multiple cameras and infrared LEDs [Lu et al. 2020]. Ozhan et al. further show that the camera–LED–eye geometry affects the observed P3/P4 locations and configure the system to improve reflection separation while avoiding vignetting [Ozhan et al. 2023]. These results suggest optimizing P3/P4 visibility, sharpness, field-of-view coverage, and separation from other reflections.

The selected layout must also remain practical to assemble, calibrate, and evaluate at the sensor level. Prior work on replicating

a controllable AR haploscope highlights the implementation challenges of physical optical platforms [Bontha and Arefin 2024] and Wu et al. show that reliable P1/P4 measurement depends on sufficient image resolution and accurate reflection localization [Wu et al. 2023]. These considerations motivate evaluating optical layout, calibration, and sensor-level detectability together.

The present work does not perform end-to-end differentiable optimization. Instead, it uses geometric-optics simulation to compare candidate LED–camera configurations and to predict whether P1–P4 remain visible, sharp, and separable under realizable capture conditions. Differentiable layout optimization and synthetic-to-real adaptation are left as future extensions.

4 Optical Background

4.1 Capturing Purkinje image

Dual Purkinje Image (DPI) tracking can provide higher precision than conventional pupil–corneal-reflection tracking by using the relative motion of P1 and P4 rather than the pupil center [Cornsweet and Crane 1973; Ressmeyer et al. 2026]. However, obtaining reliable Purkinje features from real eye images remains challenging. Wu et al. [Cornsweet and Crane 1973] show that P1 and P4 can be imaged together while P3 is out of focus and P2 largely overlaps with P1; similarly, Ahn et al. [Ahn and Lee 2025] report that P4 is substantially smaller and darker than P1, making its detection less reliable. Therefore, the existence of a valid reflection path does not necessarily guarantee a usable image feature, as its visibility further depends on optical focus, reflection strength, occlusion, and imaging noise [Ahn and Lee 2025; Cornsweet and Crane 1973]. Camera and illumination configuration also affect whether these reflections remain observable across different eye orientations, making Purkinje detectability a joint consequence of ocular geometry and the imaging configuration [Cornsweet and Crane 1973; Lu et al. 2020]. Nevertheless, Purkinje geometry carries useful information about the underlying ocular surfaces, with previous phakometric studies showing that the position and geometry of these reflections can be

used to infer ocular surface curvature and alignment [Barry et al. 2001].

4.2 Simulation-to-capture pipeline for near-eye Purkinje imaging

A reliable Purkinje imaging pipeline requires the eye to be modeled as an optical system rather than an appearance object. Since P1–P4 are generated by reflection and refraction at corneal and lenticular surfaces, Arizona/ZEMAX-style schematic eye models are useful because they make accommodation, refractive interfaces, and ray paths physically controllable [Lu et al. 2020][Ozhan et al. 2023]. This also explains why eye-rendering methods often keep the eyeball or cornea as an explicit mesh: specular highlights, corneal refraction, and near-field glints are tied to surface geometry, while NeRF-like fields are more suitable for view synthesis, relighting, and periocular appearance modeling [Khademi et al. 2026; Li et al. 2022; Nair et al. 2020]. Existing Purkinje imaging systems also provide practical guidance for hardware geometry. Both Lu et al. and Ozhan et al. place infrared LEDs close to the camera optical axis to maximize Purkinje visibility while keeping the reflections inside the camera field of view. At the same time, camera positions must balance the visibility of higher-order Purkinje images against eyelid and eyelash occlusions, glint overlap, and sensor saturation. These observations suggest that LED and camera placement is not arbitrary but jointly determines the brightness, separation, and detectability of P1–P4. Once the capture geometry is determined, synthetic rendering provides an efficient way to evaluate different configurations before physical experiments. RIT-Eyes demonstrates that physically based rendering can generate realistic near-eye images under controllable illumination, while EyeNeRF and subsequent hybrid eye representations further show that explicit corneal geometry is necessary for reproducing specular reflections and refraction, whereas implicit neural representations are better suited for modeling complex periocular appearance and relighting. These observations motivate the use of explicit optical eye models for Purkinje simulation before subsequent NeRF or 3D Gaussian reconstruction, fall outside the field of view, or become unresolvable at the sensor resolution. Thus, the key background principle is that eye geometry, near-field illumination, camera focus/FOV, resolution, and reconstruction representation must be designed together before reliable Purkinje capture and later NeRF/3D Gaussian reconstruction can be expected [Kerbl et al. 2023].

5 Method

We adopt 3D Gaussian Splatting (3DGS) as the base representation for reconstructing the eye scene [Kerbl et al. 2023]. The scene is represented by a set of anisotropic 3D Gaussians, each parameterized by its position μ , covariance Σ defined by scale and rotation, opacity α , and spherical harmonics (SH) coefficients for view-dependent appearance [Jiang et al. 2024; Kerbl et al. 2023].

During rendering, the 3D Gaussians are projected onto the image plane, depth-sorted, and accumulated using front-to-back α -compositing [Kerbl et al. 2023]:

$$C(p) = \sum_i T_i(p) \alpha_i(p) c_i(v),$$

where $c_i(v)$ denotes the view-dependent color predicted from the SH coefficients. Training jointly optimizes Gaussian positions, scales, rotations, opacities, and SH coefficients using a combination of L_1 and D-SSIM reconstruction losses, while adaptive densification increases the number of Gaussians in regions requiring higher representational capacity [Kerbl et al. 2023]. We use this standard 3DGS formulation as our baseline and subsequently introduce Purkinje-specific local supervision.

5.1 3D Gaussian Splatting

3D Gaussian Splatting is an explicit 3D scene representation and differentiable rendering method designed for novel view synthesis. The core idea is modeling the geometric structure and viewpoint-dependent appearance of a scene in 3D space using a set of optimizable Gaussian primitives expressed as

$$\mathcal{G}_i = \{\mu_i, \Sigma_i, \alpha_i, c_i\}, \quad (1)$$

Here, μ_i denotes the 3D position of the i -th Gaussian, s_i its scale, R_i its rotation, α_i its opacity, and c_i the spherical harmonics coefficients used to represent view-dependent appearance.

The input to 3DGS consists of a set of multi-view images capturing the same scene from different viewpoints, structure-from-motion (SfM) estimates the camera parameters and reconstructs a sparse 3D point cloud, which is subsequently used to initialize the Gaussian primitives. [Jiang et al. 2024; Kerbl et al. 2023]. The scale and rotation jointly define the covariance matrix as

$$\Sigma_i = R_i S_i S_i^T R_i^T, \quad (2)$$

where S_i is a diagonal scaling matrix constructed from s_i , and R_i determines the orientation of the anisotropic Gaussian.

Once the Gaussian primitives are initialized and parameterized, they are projected onto the image plane, ordered according to depth, and accumulated using front-to-back alpha compositing to generate the rendered image. Standard 3DGS combines a pixel-wise L_1 loss with a D-SSIM loss [Kerbl et al. 2023]:

$$\mathcal{L}_{GS} = (1 - \lambda) \mathcal{L}_1 + \lambda \mathcal{L}_{D-SSIM}, \quad (3)$$

where $\mathcal{L}_1$ measures the pixel-wise photometric difference between the rendered and ground-truth images, $\mathcal{L}_{D-SSIM}$ measures their local structural dissimilarity, and λ controls the relative contribution of the two terms. The reconstruction loss is back-propagated to jointly optimize the Gaussian positions, scales, rotations, opacities, and SH coefficients.

In parallel with parameter optimization, 3DGS performs adaptive density control to dynamically refine the Gaussian population. Gaussians with large positional gradients are cloned when they are sufficiently small and split when they have a large spatial extent, introducing additional primitives in under-reconstructed regions. Conversely, Gaussians with very low opacity or excessively large spatial or screen-space extent are periodically removed. By alternating differentiable rendering, gradient-based optimization, and adaptive density control, the initially sparse Gaussian representation progressively evolves into a dense scene representation capable of high-quality novel-view rendering [Kerbl et al. 2023].

6 Results and Discussions

7 Results and Discussions

References

- Jinyeong Ahn and Eui Chul Lee. 2025. A Study on Correlation of Depth Fixation with Distance Between Dual Purkinje Images and Pupil Size. *Electronics* 14, 9 (2025), 1799. doi:10.3390/electronics14091799
- Jean-Cyriaque Barry, Mark Dunne, and Thomas Kirschkamp. 2001. Phakometric Measurement of Ocular Surface Radius of Curvature and Alignment: Evaluation of Method with Physical Model Eyes. *Ophthalmic and Physiological Optics* 21, 6 (2001), 450–460. doi:10.1046/j.1475-1313.2001.00612.x
- Jaya Surya Bontha and Mohammed Safayet Arefin. 2024. Effort to Replicate Custom-Made Augmented Reality Haploscope. In *2024 IEEE International Symposium on Mixed and Augmented Reality Adjunct (ISMAR-Adjunct)*. IEEE, 37–41.
- T. N. Cornsweet and H. D. Crane. 1973. Accurate Two-Dimensional Eye Tracker Using First and Fourth Purkinje Images. *Journal of the Optical Society of America* 63, 8 (1973), 921–928. doi:10.1364/JOSA.63.000921
- David M. Hoffman, Ahna R. Girshick, Kurt Akeley, and Martin S. Banks. 2008. Vergence–Accommodation Conflicts Hinder Visual Performance and Cause Visual Fatigue. *Journal of Vision* 8, 3 (2008), 33. doi:10.1167/8.3.33
- Anis Idrizović, Rueli-Jr Wu, Michele Rucci, and Jannick P. Rolland. 2025. Wide-Range High-Precision Eye-Tracking Based on Purkinje Reflections. In *Novel Optical Systems, Methods, and Applications XXVIII (Proceedings of SPIE, Vol. 13595)*. SPIE, 135950F. doi:10.1117/12.3065468
- Yingwenqi Jiang, Jiadong Tu, Yuan Liu, Xifeng Gao, Xiaoxiao Long, Wenping Wang, and Yuexin Ma. 2024. GaussianShader: 3D Gaussian Splatting with Shading Functions for Reflective Surfaces. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. 5322–5332.
- Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 2023. 3D Gaussian Splatting for Real-Time Radiance Field Rendering. *ACM Transactions on Graphics* 42, 4 (2023). doi:10.1145/3592433
- Wesley Khademi, Jogendra Kundu, Yatong An, Alexander Fix, and David Colmenares. 2026. Reconstructing Realistic and Relightable Eyes. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*.
- Joohwan Kim, Michael Stengel, Alexander Majercik, Shalini De Mello, David Dunn, Samuli Laine, Morgan McGuire, and David Luebke. 2019. NVGaze: An Anatomically-Informed Dataset for Low-Latency, Near-Eye Gaze Estimation. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems*. Association for Computing Machinery, Article 550, 12 pages. doi:10.1145/3290605.3300780
- Gengyan Li, Abhimitra Meka, Franziska Müller, Marcel C. Bühler, Otmar Hilliges, and Thabo Beeler. 2022. EyeNeRF: A Hybrid Representation for Photorealistic Synthesis, Animation and Relighting of Human Eyes. *ACM Transactions on Graphics* 41, 4 (2022). doi:10.1145/3528223.3530130
- Esther Y. H. Lin, Yimin Ding, Jogendra Kundu, Yatong An, Mohamed T. El-Haddad, and Alexander Fix. 2026. Digitally Prototype Your Eye Tracker: Simulating Hardware Performance Using 3D Synthetic Data. In *Proceedings of the 2026 Symposium on Eye Tracking Research and Applications (ETRA '26)*. Association for Computing Machinery, Article 6, 7 pages. doi:10.1145/3797246.3803040
- Conny Lu, Praneeth Chakravarthula, Ye Tao, Steven Chen, and Henry Fuchs. 2020. Improved Vergence and Accommodation via Purkinje Image Tracking with Multiple Cameras for AR Glasses. In *2020 IEEE International Symposium on Mixed and Augmented Reality (ISMAR)*. IEEE, 320–331. doi:10.1109/ISMAR50242.2020.00058
- Carlos H. Morimoto, Arnon Amir, and Myron Flickner. 2002. Detecting Eye Position and Gaze from a Single Camera and 2 Light Sources. In *Proceedings of the 16th International Conference on Pattern Recognition*, Vol. 4. IEEE, 314–317. doi:10.1109/ICPR.2002.1047459
- Mulun Na, Hector A. Jimenez Romero, Xinge Yang, Jonathan Klein, Dominik L. Michels, and Wolfgang Heidrich. 2024. End-to-End Optimization of Fluidic Lenses. In *SIGGRAPH Asia 2024 Conference Papers*. ACM. doi:10.1145/3680528.3687584
- Nitinraj Nair, Rakshit Kothari, Aayush K. Chaudhary, Zhizhuo Yang, Gabriel J. Diaz, Jeff B. Pelz, and Reynold J. Bailey. 2020. RIT-Eyes: Rendering of Near-Eye Images for Eye-Tracking Applications. In *Proceedings of the ACM Symposium on Applied Perception*. ACM. doi:10.1145/3385955.3407935
- Faik Ozan Ozhan, Ugur Aygun, Afsun Sahin, and Hakan Urey. 2023. Dynamic Accommodation Measurement Using Purkinje Reflections and Machine Learning. *Scientific Reports* 13, 21625 (2023). doi:10.1038/s41598-023-47572-0
- Ryan A. Ressmeyer, Jorge Otero-Millan, Gregory D. Horwitz, and Jacob L. Yates. 2026. OpenIrisDPI: An Open-Source Digital Dual Purkinje Image Eye Tracker for Visual Neuroscience. *Journal of Neuroscience Methods* (2026), 110693. doi:10.1016/j.jneumeth.2026.110693
- Mohsen Sharifzadeh. 2024. A Theoretical Approach for Diagnosing Keratoconus Using Purkinje Image Geometry: An Accessible Method for Low-Cost and Early Detection. doi:10.1364/opticaopen.27115606 Preprint, Version 2.
- Matthew Sturgeon, Dakota Kenoyer-Healy, Russell Cohen Hoffing, Steven Thurman, and Mohammed Safayet Arefin. 2025. Examining Eye Vergence During Perceived Depth Changes with Eye Tracking System in Optical See-Through Augmented Reality. In *2025 IEEE International Symposium on Mixed and Augmented Reality (ISMAR)*. IEEE, 1376–1386.
- Jiajun Tang, Fan Fei, Zhihao Li, Xiao Tang, Shiyong Liu, Youyu Chen, Bin Xiao Huang, Zhenyu Chen, Xiaofei Wu, and Boxin Shi. 2025. SpecTRe-GS: Modeling Highly Specular Surfaces with Reflected Nearby Objects by Tracing Rays in 3D Gaussian Splatting. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. 16133–16142.
- Erroll Wood, Tadas Baltrušaitis, Louis-Philippe Morency, Peter Robinson, and Andreas Bulling. 2016. Learning an Appearance-Based Gaze Estimator from One Million Synthesised Images. In *Proceedings of the Ninth Biennial ACM Symposium on Eye Tracking Research & Applications*. Association for Computing Machinery, 131–138. doi:10.1145/2857491.2857492
- Qi Wu, Janick Martinez Esturo, Ashkan Mirzaei, Nicolas Moënn-Loccoz, and Zan Gojcic. 2025. 3DGUT: Enabling Distorted Cameras and Secondary Rays in Gaussian Splatting. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. 26036–26046.
- Ruei-Jr Wu, Ashley M. Clark, Michele A. Cox, Janis Intoy, Paul C. Jolly, Zhetuo Zhao, and Michele Rucci. 2023. High-Resolution Eye-Tracking via Digital Imaging of Purkinje Reflections. *Journal of Vision* 23, 5 (2023), 4. doi:10.1167/jov.23.5.4
- Ruei-Jr Wu, Paul Jolly, Soma Mizobuchi, Ashley M. Clark, Zhetuo Zhao, Bin Yang, Janis Intoy, Michele A. Cox, and Michele Rucci. 2022. High-resolution oculomotor measurements via a digital Dual Purkinje Image eye-tracker. *Journal of Vision* 22, 14 (2022), 4203. doi:10.1167/jov.22.14.4203