

# Python Pandas - Quick Guide

## Python Pandas - Introduction

Pandas is an open-source Python Library providing high-performance data manipulation and analysis tool using its powerful data structures. The name Pandas is derived from the word Panel Data – an Econometrics from Multidimensional data.

In 2008, developer Wes McKinney started developing pandas when in need of high performance, flexible tool for analysis of data.

Prior to Pandas, Python was majorly used for data munging and preparation. It had very little contribution towards data analysis. Pandas solved this problem. Using Pandas, we can accomplish five typical steps in the processing and analysis of data, regardless of the origin of data — load, prepare, manipulate, model, and analyze.

Python with Pandas is used in a wide range of fields including academic and commercial domains including finance, economics, Statistics, analytics, etc.

### Key Features of Pandas

- Fast and efficient DataFrame object with default and customized indexing.
- Tools for loading data into in-memory data objects from different file formats.
- Data alignment and integrated handling of missing data.
- Reshaping and pivoting of date sets.
- Label-based slicing, indexing and subsetting of large data sets.
- Columns from a data structure can be deleted or inserted.
- Group by data for aggregation and transformations.
- High performance merging and joining of data.
- Time Series functionality.

## Python Pandas - Environment Setup

Standard Python distribution doesn't come bundled with Pandas module. A lightweight alternative is to install NumPy using popular Python package installer, **pip**.

```
pip install pandas
```

If you install Anaconda Python package, Pandas will be installed by default with the following –

## Windows

- **Anaconda** (from <https://www.continuum.io>) is a free Python distribution for SciPy stack. It is also available for Linux and Mac.
- **Canopy** (<https://www.enthought.com/products/canopy/>) is available as free as well as commercial distribution with full SciPy stack for Windows, Linux and Mac.
- **Python** (x,y) is a free Python distribution with SciPy stack and Spyder IDE for Windows OS. (Downloadable from <http://python-xy.github.io/>)

Learn **Python** in-depth with real-world projects through our **Python certification course**. Enroll and become a certified expert to boost your career.

## Linux

Package managers of respective Linux distributions are used to install one or more packages in SciPy stack.

### For Ubuntu Users

```
sudo apt-get install python-numpy python-scipy python-matplotlibpythonipythonnotebook
python-pandas python-sympy python-nose
```

### For Fedora Users

```
sudo yum install numpy scipy python-matplotlibpython python-pandas sympy
python-nose atlas-devel
```

# Introduction to Data Structures

Pandas deals with the following three data structures –

- Series
- DataFrame
- Panel

These data structures are built on top of Numpy array, which means they are fast.

## Dimension & Description

The best way to think of these data structures is that the higher dimensional data structure is a container of its lower dimensional data structure. For example, DataFrame is a container of Series, Panel is a container of DataFrame.

Data Structure	Dimensions	Description
Series	1	1D labeled homogeneous array, size immutable.
Data Frames	2	General 2D labeled, size-mutable tabular structure with potentially heterogeneously typed columns.
Panel	3	General 3D labeled, size-mutable array.

Building and handling two or more dimensional arrays is a tedious task, burden is placed on the user to consider the orientation of the data set when writing functions. But using Pandas data structures, the mental effort of the user is reduced.

For example, with tabular data (DataFrame) it is more semantically helpful to think of the **index** (the rows) and the **columns** rather than axis 0 and axis 1.

## Mutability

All Pandas data structures are value mutable (can be changed) and except Series all are size mutable. Series is size immutable.

**Note** – DataFrame is widely used and one of the most important data structures. Panel is used much less.

## Series

Series is a one-dimensional array like structure with homogeneous data. For example, the following series is a collection of integers 10, 23, 56, ...

10	23	56	17	52	61	73	90	26	72
----	----	----	----	----	----	----	----	----	----

## Key Points

- Homogeneous data
- Size Immutable
- Values of Data Mutable

## DataFrame

DataFrame is a two-dimensional array with heterogeneous data. For example,

Name	Age	Gender	Rating
Steve	32	Male	3.45
Lia	28	Female	4.6
Vin	45	Male	3.9
Katie	38	Female	2.78

The table represents the data of a sales team of an organization with their overall performance rating. The data is represented in rows and columns. Each column represents an attribute and each row represents a person.

## Data Type of Columns

The data types of the four columns are as follows –

Column	Type
Name	String
Age	Integer
Gender	String
Rating	Float

## Key Points

- Heterogeneous data
- Size Mutable
- Data Mutable

## Panel

Panel is a three-dimensional data structure with heterogeneous data. It is hard to represent the panel in graphical representation. But a panel can be illustrated as a container of DataFrame.

## Key Points

- Heterogeneous data
- Size Mutable
- Data Mutable

## Python Pandas - Series

Series is a one-dimensional labeled array capable of holding data of any type (integer, string, float, python objects, etc.). The axis labels are collectively called index.

### pandas.Series

A pandas Series can be created using the following constructor –

```
pandas.Series( data, index, dtype, copy)
```

The parameters of the constructor are as follows –

Sr.No	Parameter & Description
1	<b>data</b> data takes various forms like ndarray, list, constants
2	<b>index</b> Index values must be unique and hashable, same length as data. Default <b>np.arange(n)</b> if no index is passed.
3	<b>dtype</b> dtype is for data type. If None, data type will be inferred
4	<b>copy</b> Copy data. Default False

A series can be created using various inputs like –

- Array
- Dict
- Scalar value or constant

## Create an Empty Series

A basic series, which can be created is an Empty Series.

### Example

```
#import the pandas library and aliasing as pd  
import pandas as pd  
s = pd.Series()  
print s
```

[Live Demo](#)

Its **output** is as follows –

```
Series([], dtype: float64)
```

## Create a Series from ndarray

If data is an ndarray, then index passed must be of the same length. If no index is passed, then by default index will be **range(n)** where **n** is array length, i.e., [0,1,2,3....**range(len(array))-1**].

### Example 1

```
#import the pandas library and aliasing as pd  
import pandas as pd  
import numpy as np  
data = np.array(['a','b','c','d'])  
s = pd.Series(data)  
print s
```

[Live Demo](#)

Its **output** is as follows –

```
0  a  
1  b  
2  c  
3  d  
dtype: object
```

We did not pass any index, so by default, it assigned the indexes ranging from 0 to **len(data)-1**, i.e., 0 to 3.

## Example 2

```
#import the pandas library and aliasing as pd
import pandas as pd
import numpy as np
data = np.array(['a', 'b', 'c', 'd'])
s = pd.Series(data, index=[100, 101, 102, 103])
print s
```

[Live Demo](#)

Its **output** is as follows –

```
100 a
101 b
102 c
103 d
dtype: object
```

We passed the index values here. Now we can see the customized indexed values in the output.

## Create a Series from dict

A **dict** can be passed as input and if no index is specified, then the dictionary keys are taken in a sorted order to construct index. If **index** is passed, the values in data corresponding to the labels in the index will be pulled out.

## Example 1

```
#import the pandas library and aliasing as pd
import pandas as pd
import numpy as np
data = {'a' : 0., 'b' : 1., 'c' : 2.}
s = pd.Series(data)
print s
```

[Live Demo](#)

Its **output** is as follows –

```
a 0.0
b 1.0
c 2.0
dtype: float64
```

**Observe** – Dictionary keys are used to construct index.

## Example 2

```
#import the pandas library and aliasing as pd
import pandas as pd
import numpy as np
data = {'a' : 0., 'b' : 1., 'c' : 2.}
s = pd.Series(data, index=['b', 'c', 'd', 'a'])
print s
```

[Live Demo](#)

Its **output** is as follows –

```
b 1.0
c 2.0
d NaN
a 0.0
dtype: float64
```

**Observe** – Index order is persisted and the missing element is filled with NaN (Not a Number).

## Create a Series from Scalar

If data is a scalar value, an index must be provided. The value will be repeated to match the length of **index**

```
#import the pandas library and aliasing as pd
import pandas as pd
import numpy as np
s = pd.Series(5, index=[0, 1, 2, 3])
print s
```

[Live Demo](#)

Its **output** is as follows –



```
0 5
1 5
2 5
3 5
dtype: int64
```

## Accessing Data from Series with Position

Data in the series can be accessed similar to that in an **ndarray**.

### Example 1

Retrieve the first element. As we already know, the counting starts from zero for the array, which means the first element is stored at zero<sup>th</sup> position and so on.

```
import pandas as pd
s = pd.Series([1,2,3,4,5],index = ['a','b','c','d','e'])

#retrieve the first element
print s[0]
```

[Live Demo](#)

Its **output** is as follows –

```
1
```

### Example 2

Retrieve the first three elements in the Series. If a `:` is inserted in front of it, all items from that index onwards will be extracted. If two parameters (with `:` between them) is used, items between the two indexes (not including the stop index)

```
import pandas as pd
s = pd.Series([1,2,3,4,5],index = ['a','b','c','d','e'])

#retrieve the first three element
print s[:3]
```

[Live Demo](#)

Its **output** is as follows –

```
a 1
b 2
c 3
dtype: int64
```

## Example 3

Retrieve the last three elements.

```
import pandas as pd
s = pd.Series([1,2,3,4,5],index = ['a','b','c','d','e'])

#retrieve the last three element
print s[-3:]
```

[Live Demo](#)

Its **output** is as follows –

```
c 3
d 4
e 5
dtype: int64
```

## Retrieve Data Using Label (Index)

A Series is like a fixed-size **dict** in that you can get and set values by index label.

## Example 1

Retrieve a single element using index label value.

```
import pandas as pd
s = pd.Series([1,2,3,4,5],index = ['a','b','c','d','e'])

#retrieve a single element
print s['a']
```

[Live Demo](#)

Its **output** is as follows –

1

## Example 2

Retrieve multiple elements using a list of index label values.

```
import pandas as pd
s = pd.Series([1,2,3,4,5],index = ['a','b','c','d','e'])

#retrieve multiple elements
print s[['a','c','d']]
```

[Live Demo](#)

Its **output** is as follows –

```
a 1
c 3
d 4
dtype: int64
```

## Example 3

If a label is not contained, an exception is raised.

```
import pandas as pd
s = pd.Series([1,2,3,4,5],index = ['a','b','c','d','e'])

#retrieve multiple elements
print s['f']
```

Its **output** is as follows –

```
...
KeyError: 'f'
```

# Python Pandas - DataFrame


A Data frame is a two-dimensional data structure, i.e., data is aligned in a tabular fashion in rows and columns.

## Features of DataFrame

- Potentially columns are of different types
- Size – Mutable
- Labeled axes (rows and columns)
- Can Perform Arithmetic operations on rows and columns

## Structure

Let us assume that we are creating a data frame with student's data.



The diagram illustrates the structure of a DataFrame. It features a table with three columns: 'Regd. No', 'Name', and 'Marks%'. The rows are labeled with student IDs: 1000, 1001, 1002, 1003, and 1004. Blue arrows point from the labels 'Columns' and 'rows' to their respective axes in the table.

Columns		
Regd. No	Name	Marks%
1000	Steve	86.29
1001	Mathew	91.63
1002	Jose	72.90
1003	Patty	69.23
1004	Vin	88.30

You can think of it as an SQL table or a spreadsheet data representation.

## pandas.DataFrame

A pandas DataFrame can be created using the following constructor –

```
pandas.DataFrame( data, index, columns, dtype, copy)
```

The parameters of the constructor are as follows –

Sr.No	Parameter & Description
1	<b>data</b> data takes various forms like ndarray, series, map, lists, dict, constants and also another DataFrame.
2	<b>index</b> For the row labels, the Index to be used for the resulting frame is Optional Default np.arange(n) if no index is passed.
3	<b>columns</b> For column labels, the optional default syntax is - np.arange(n). This is only true if no index is passed.
4	<b>dtype</b> Data type of each column.
5	<b>copy</b> This command (or whatever it is) is used for copying of data, if the default is False.

## Create DataFrame

A pandas DataFrame can be created using various inputs like –

- Lists
- dict
- Series
- Numpy ndarrays
- Another DataFrame

In the subsequent sections of this chapter, we will see how to create a DataFrame using these inputs.

## Create an Empty DataFrame

A basic DataFrame, which can be created is an Empty Dataframe.

## Example

```
#import the pandas library and aliasing as pd  
import pandas as pd  
df = pd.DataFrame()  
print df
```

[Live Demo](#)

Its **output** is as follows –

```
Empty DataFrame  
Columns: []  
Index: []
```

## Create a DataFrame from Lists

The DataFrame can be created using a single list or a list of lists.

### Example 1

```
import pandas as pd  
data = [1,2,3,4,5]  
df = pd.DataFrame(data)  
print df
```

[Live Demo](#)

Its **output** is as follows –

```
0  
0  1  
1  2  
2  3  
3  4  
4  5
```

### Example 2

```
import pandas as pd  
data = [['Alex',10],['Bob',12],['Clarke',13]]  
df = pd.DataFrame(data,columns=['Name','Age'])  
print df
```

[Live Demo](#)

Its **output** is as follows –

	Name	Age
0	Alex	10
1	Bob	12
2	Clarke	13

### Example 3

```
import pandas as pd
data = [['Alex',10],['Bob',12],['Clarke',13]]
df = pd.DataFrame(data,columns=['Name','Age'],dtype=float)
print df
```

[Live Demo](#)

Its **output** is as follows –

	Name	Age
0	Alex	10.0
1	Bob	12.0
2	Clarke	13.0

**Note** – Observe, the **dtype** parameter changes the type of Age column to floating point.

## Create a DataFrame from Dict of ndarrays / Lists

All the **ndarrays** must be of same length. If index is passed, then the length of the index should equal to the length of the arrays.

If no index is passed, then by default, index will be range(n), where **n** is the array length.

### Example 1

```
import pandas as pd
data = {'Name':['Tom', 'Jack', 'Steve', 'Ricky'],'Age':[28,34,29,42]}
df = pd.DataFrame(data)
print df
```

[Live Demo](#)

Its **output** is as follows –

	Age	Name
0	28	Tom
1	34	Jack
2	29	Steve
3	42	Ricky

**Note** – Observe the values 0,1,2,3. They are the default index assigned to each using the function range(n).

## Example 2

Let us now create an indexed DataFrame using arrays.

```
import pandas as pd
data = {'Name': ['Tom', 'Jack', 'Steve', 'Ricky'], 'Age': [28, 34, 29, 42]}
df = pd.DataFrame(data, index=['rank1', 'rank2', 'rank3', 'rank4'])
print df
```

[Live Demo](#)

Its **output** is as follows –

	Age	Name
rank1	28	Tom
rank2	34	Jack
rank3	29	Steve
rank4	42	Ricky

**Note** – Observe, the **index** parameter assigns an index to each row.

## Create a DataFrame from List of Dicts

List of Dictionaries can be passed as input data to create a DataFrame. The dictionary keys are by default taken as column names.

### Example 1

The following example shows how to create a DataFrame by passing a list of dictionaries.

```
import pandas as pd
data = [{'a': 1, 'b': 2}, {'a': 5, 'b': 10, 'c': 20}]
```

[Live Demo](#)



```
df = pd.DataFrame(data)
print df
```

Its **output** is as follows –

```
   a  b   c
0  1  2 NaN
1  5 10 20.0
```

**Note** – Observe, NaN (Not a Number) is appended in missing areas.

## Example 2

The following example shows how to create a DataFrame by passing a list of dictionaries and the row indices.

```
import pandas as pd
data = [{'a': 1, 'b': 2}, {'a': 5, 'b': 10, 'c': 20}]
df = pd.DataFrame(data, index=['first', 'second'])
print df
```

[Live Demo](#)

Its **output** is as follows –

```
   a  b   c
first 1  2 NaN
second 5 10 20.0
```

## Example 3

The following example shows how to create a DataFrame with a list of dictionaries, row indices, and column indices.

```
import pandas as pd
data = [{'a': 1, 'b': 2}, {'a': 5, 'b': 10, 'c': 20}]

#With two column indices, values same as dictionary keys
df1 = pd.DataFrame(data, index=['first', 'second'], columns=['a', 'b'])

#With two column indices with one index with other name
df2 = pd.DataFrame(data, index=['first', 'second'], columns=['a', 'b1'])
```

[Live Demo](#)

```
print df1
print df2
```

Its **output** is as follows –

```
#df1 output
   a  b
first  1  2
second 5 10

#df2 output
   a  b1
first  1 NaN
second 5 NaN
```

**Note** – Observe, df2 DataFrame is created with a column index other than the dictionary key; thus, appended the NaN's in place. Whereas, df1 is created with column indices same as dictionary keys, so NaN's appended.

## Create a DataFrame from Dict of Series

Dictionary of Series can be passed to form a DataFrame. The resultant index is the union of all the series indexes passed.

### Example

```
import pandas as pd

d = {'one' : pd.Series([1, 2, 3], index=['a', 'b', 'c']),
     'two' : pd.Series([1, 2, 3, 4], index=['a', 'b', 'c', 'd'])}

df = pd.DataFrame(d)
print df
```

[Live Demo](#)

Its **output** is as follows –

```
   one  two
a   1.0    1
b   2.0    2
```

```
c    3.0    3
d    NaN    4
```

**Note** – Observe, for the series one, there is no label **'d'** passed, but in the result, for the **d** label, NaN is appended with NaN.

Let us now understand **column selection**, **addition**, and **deletion** through examples.

## Column Selection

We will understand this by selecting a column from the DataFrame.

### Example

```
import pandas as pd

d = {'one' : pd.Series([1, 2, 3], index=['a', 'b', 'c']),
     'two' : pd.Series([1, 2, 3, 4], index=['a', 'b', 'c', 'd'])}

df = pd.DataFrame(d)
print df ['one']
```

[Live Demo](#)

Its **output** is as follows –

```
a    1.0
b    2.0
c    3.0
d    NaN
Name: one, dtype: float64
```

## Column Addition

We will understand this by adding a new column to an existing data frame.

### Example

```
import pandas as pd

d = {'one' : pd.Series([1, 2, 3], index=['a', 'b', 'c']),
     'two' : pd.Series([1, 2, 3, 4], index=['a', 'b', 'c', 'd'])}
```

[Live Demo](#)

```

df = pd.DataFrame(d)

# Adding a new column to an existing DataFrame object with column label by passing as Series

print ("Adding a new column by passing as Series:")
df['three']=pd.Series([10,20,30],index=['a','b','c'])
print df

print ("Adding a new column using the existing columns in DataFrame:")
df['four']=df['one']+df['three']

print df

```

Its **output** is as follows –

Adding a new column by passing as Series:

	one	two	three
a	1.0	1	10.0
b	2.0	2	20.0
c	3.0	3	30.0
d	NaN	4	NaN

Adding a new column using the existing columns in DataFrame:

	one	two	three	four
a	1.0	1	10.0	11.0
b	2.0	2	20.0	22.0
c	3.0	3	30.0	33.0
d	NaN	4	NaN	NaN

## Column Deletion

Columns can be deleted or popped; let us take an example to understand how.

### Example

```

# Using the previous DataFrame, we will delete a column
# using del function
import pandas as pd

d = {'one' : pd.Series([1, 2, 3], index=['a', 'b', 'c']),

```

Live Demo

```

'two' : pd.Series([1, 2, 3, 4], index=['a', 'b', 'c', 'd']),
'three' : pd.Series([10,20,30], index=['a','b','c'])}

df = pd.DataFrame(d)
print ("Our dataframe is:")
print df

# using del function
print ("Deleting the first column using DEL function:")
del df['one']
print df

# using pop function
print ("Deleting another column using POP function:")
df.pop('two')
print df

```

Its **output** is as follows –

Our dataframe is:

	one	three	two
a	1.0	10.0	1
b	2.0	20.0	2
c	3.0	30.0	3
d	NaN	NaN	4

Deleting the first column using DEL function:

	three	two
a	10.0	1
b	20.0	2
c	30.0	3
d	NaN	4

Deleting another column using POP function:

	three
a	10.0
b	20.0
c	30.0
d	NaN

## Row Selection, Addition, and Deletion

We will now understand row selection, addition and deletion through examples. Let us begin with the concept of selection.

## Selection by Label

Rows can be selected by passing row label to a **loc** function.

```
import pandas as pd

d = {'one' : pd.Series([1, 2, 3], index=['a', 'b', 'c']),
     'two' : pd.Series([1, 2, 3, 4], index=['a', 'b', 'c', 'd'])}

df = pd.DataFrame(d)
print df.loc['b']
```

[Live Demo](#)

Its **output** is as follows –

```
one 2.0
two 2.0
Name: b, dtype: float64
```

The result is a series with labels as column names of the DataFrame. And, the Name of the series is the label with which it is retrieved.

## Selection by integer location

Rows can be selected by passing integer location to an **iloc** function.

```
import pandas as pd

d = {'one' : pd.Series([1, 2, 3], index=['a', 'b', 'c']),
     'two' : pd.Series([1, 2, 3, 4], index=['a', 'b', 'c', 'd'])}

df = pd.DataFrame(d)
print df.iloc[2]
```

[Live Demo](#)

Its **output** is as follows –

```
one 3.0
two 3.0
```

Name: c, dtype: float64

## Slice Rows

Multiple rows can be selected using `:` operator.

```
import pandas as pd
```

[Live Demo](#)

```
d = {'one' : pd.Series([1, 2, 3], index=['a', 'b', 'c']),
     'two' : pd.Series([1, 2, 3, 4], index=['a', 'b', 'c', 'd'])}
```

```
df = pd.DataFrame(d)
print df[2:4]
```

Its **output** is as follows –

```
   one  two
c  3.0    3
d  NaN    4
```

## Addition of Rows

Add new rows to a DataFrame using the **append** function. This function will append the rows at the end.

```
import pandas as pd
```

[Live Demo](#)

```
df = pd.DataFrame([[1, 2], [3, 4]], columns = ['a', 'b'])
df2 = pd.DataFrame([[5, 6], [7, 8]], columns = ['a', 'b'])
```

```
df = df.append(df2)
print df
```

Its **output** is as follows –

```
   a  b
0  1  2
1  3  4
```

```
0 5 6
1 7 8
```

## Deletion of Rows

Use index label to delete or drop rows from a DataFrame. If label is duplicated, then multiple rows will be dropped.

If you observe, in the above example, the labels are duplicate. Let us drop a label and will see how many rows will get dropped.

```
import pandas as pd

df = pd.DataFrame([[1, 2], [3, 4]], columns = ['a', 'b'])
df2 = pd.DataFrame([[5, 6], [7, 8]], columns = ['a', 'b'])

df = df.append(df2)

# Drop rows with label 0
df = df.drop(0)

print df
```

[Live Demo](#)

Its **output** is as follows –

```
a b
1 3 4
1 7 8
```

In the above example, two rows were dropped because those two contain the same label 0.

## Python Pandas - Panel

A **panel** is a 3D container of data. The term **Panel data** is derived from econometrics and is partially responsible for the name pandas – **pan(el)-da(ta)-s**.

The names for the 3 axes are intended to give some semantic meaning to describing operations involving panel data. They are –

- **items** – axis 0, each item corresponds to a DataFrame contained inside.



- **major\_axis** – axis 1, it is the index (rows) of each of the DataFrames.
- **minor\_axis** – axis 2, it is the columns of each of the DataFrames.

## pandas.Panel()

A Panel can be created using the following constructor –

```
pandas.Panel(data, items, major_axis, minor_axis, dtype, copy)
```

The parameters of the constructor are as follows –

Parameter	Description
data	Data takes various forms like ndarray, series, map, lists, dict, constants and also another DataFrame
items	axis=0
major_axis	axis=1
minor_axis	axis=2
dtype	Data type of each column
copy	Copy data. Default, <b>false</b>

## Create Panel

A Panel can be created using multiple ways like –

- From ndarrays
- From dict of DataFrames

## From 3D ndarray

```
# creating an empty panel
import pandas as pd
import numpy as np

data = np.random.rand(2,4,5)
```

[Live Demo](#)

```
p = pd.Panel(data)
print p
```

Its **output** is as follows –

```
<class 'pandas.core.panel.Panel'>
Dimensions: 2 (items) x 4 (major_axis) x 5 (minor_axis)
Items axis: 0 to 1
Major_axis axis: 0 to 3
Minor_axis axis: 0 to 4
```

**Note** – Observe the dimensions of the empty panel and the above panel, all the objects are different.

## From dict of DataFrame Objects

```
#creating an empty panel
import pandas as pd
import numpy as np

data = {'Item1' : pd.DataFrame(np.random.randn(4, 3)),
        'Item2' : pd.DataFrame(np.random.randn(4, 2))}
p = pd.Panel(data)
print p
```

[Live Demo](#)

Its **output** is as follows –

```
Dimensions: 2 (items) x 4 (major_axis) x 3 (minor_axis)
Items axis: Item1 to Item2
Major_axis axis: 0 to 3
Minor_axis axis: 0 to 2
```

## Create an Empty Panel

An empty panel can be created using the Panel constructor as follows –

```
#creating an empty panel
import pandas as pd
```

[Live Demo](#)

```
p = pd.Panel()
print p
```

Its **output** is as follows –

```
<class 'pandas.core.panel.Panel'>
Dimensions: 0 (items) x 0 (major_axis) x 0 (minor_axis)
Items axis: None
Major_axis axis: None
Minor_axis axis: None
```

## Selecting the Data from Panel

Select the data from the panel using –

- Items
- Major\_axis
- Minor\_axis

## Using Items

```
# creating an empty panel
import pandas as pd
import numpy as np
data = {'Item1' : pd.DataFrame(np.random.randn(4, 3)),
        'Item2' : pd.DataFrame(np.random.randn(4, 2))}
p = pd.Panel(data)
print p['Item1']
```

[Live Demo](#)

Its **output** is as follows –

	0	1	2
0	0.488224	-0.128637	0.930817
1	0.417497	0.896681	0.576657
2	-2.775266	0.571668	0.290082
3	-0.400538	-0.144234	1.110535

We have two items, and we retrieved item1. The result is a DataFrame with 4 rows and 3 columns, which are the **Major\_axis** and **Minor\_axis** dimensions.

## Using major\_axis

Data can be accessed using the method **panel.major\_axis(index)**.

```
# creating an empty panel
import pandas as pd
import numpy as np
data = {'Item1' : pd.DataFrame(np.random.randn(4, 3)),
        'Item2' : pd.DataFrame(np.random.randn(4, 2))}
p = pd.Panel(data)
print p.major_xs(1)
```

[Live Demo](#)

Its **output** is as follows –

	Item1	Item2
0	0.417497	0.748412
1	0.896681	-0.557322
2	0.576657	NaN

## Using minor\_axis

Data can be accessed using the method **panel.minor\_axis(index)**.

```
# creating an empty panel
import pandas as pd
import numpy as np
data = {'Item1' : pd.DataFrame(np.random.randn(4, 3)),
        'Item2' : pd.DataFrame(np.random.randn(4, 2))}
p = pd.Panel(data)
print p.minor_xs(1)
```

[Live Demo](#)

Its **output** is as follows –

	Item1	Item2
0	-0.128637	-1.047032
1	0.896681	-0.557322

```

2  0.571668  0.431953
3 -0.144234  1.302466

```

**Note** – Observe the changes in the dimensions.

## Python Pandas - Basic Functionality

By now, we learnt about the three Pandas DataStructures and how to create them. We will majorly focus on the DataFrame objects because of its importance in the real time data processing and also discuss a few other DataStructures.

### Series Basic Functionality

Sr.No.	Attribute or Method & Description
1	<b>axes</b> Returns a list of the row axis labels
2	<b>dtype</b> Returns the dtype of the object.
3	<b>empty</b> Returns True if series is empty.
4	<b>ndim</b> Returns the number of dimensions of the underlying data, by definition 1.
5	<b>size</b> Returns the number of elements in the underlying data.
6	<b>values</b> Returns the Series as ndarray.
7	<b>head()</b> Returns the first n rows.
8	<b>tail()</b> Returns the last n rows.

Let us now create a Series and see all the above tabulated attributes operation.

### Example

```
import pandas as pd
import numpy as np

#Create a series with 100 random numbers
s = pd.Series(np.random.randn(4))
print s
```

Its **output** is as follows –

```
0    0.967853
1   -0.148368
2   -1.395906
3   -1.758394
dtype: float64
```

## axes

Returns the list of the labels of the series.

```
import pandas as pd
import numpy as np

#Create a series with 100 random numbers
s = pd.Series(np.random.randn(4))
print ("The axes are:")
print s.axes
```

[Live Demo](#)

Its **output** is as follows –

```
The axes are:
[RangeIndex(start=0, stop=4, step=1)]
```

The above result is a compact format of a list of values from 0 to 5, i.e., [0,1,2,3,4].

## empty

Returns the Boolean value saying whether the Object is empty or not. True indicates that the object is empty.

```
import pandas as pd
import numpy as np

#Create a series with 100 random numbers
s = pd.Series(np.random.randn(4))
print ("Is the Object empty?")
print s.empty
```

[Live Demo](#)

Its **output** is as follows –

```
Is the Object empty?
False
```

## ndim

Returns the number of dimensions of the object. By definition, a Series is a 1D data structure, so it returns

```
import pandas as pd
import numpy as np

#Create a series with 4 random numbers
s = pd.Series(np.random.randn(4))
print s

print ("The dimensions of the object:")
print s.ndim
```

[Live Demo](#)

Its **output** is as follows –

```
0    0.175898
1    0.166197
2   -0.609712
3   -1.377000
dtype: float64
```

```
The dimensions of the object:
1
```

## size

Returns the size(length) of the series.

```
import pandas as pd
import numpy as np

#Create a series with 4 random numbers
s = pd.Series(np.random.randn(2))
print s
print ("The size of the object:")
print s.size
```

[Live Demo](#)

Its **output** is as follows –

```
0    3.078058
1   -1.207803
dtype: float64
```

```
The size of the object:
2
```

## values

Returns the actual data in the series as an array.

```
import pandas as pd
import numpy as np

#Create a series with 4 random numbers
s = pd.Series(np.random.randn(4))
print s

print ("The actual data series is:")
print s.values
```

[Live Demo](#)

Its **output** is as follows –

```
0    1.787373
1   -0.605159
```



```
2  0.180477
3 -0.140922
dtype: float64
```

The actual data series is:

```
[ 1.78737302 -0.60515881  0.18047664 -0.1409218 ]
```

## Head & Tail

To view a small sample of a Series or the DataFrame object, use the `head()` and the `tail()` methods.

**head()** returns the first **n** rows (observe the index values). The default number of elements to display is five, but you may pass a custom number.

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

*#Create a series with 4 random numbers*

```
s = pd.Series(np.random.randn(4))
```

```
print ("The original series is:")
```

```
print s
```

```
print ("The first two rows of the data series:")
```

```
print s.head(2)
```

Its **output** is as follows –

The original series is:

```
0  0.720876
1 -0.765898
2  0.479221
3 -0.139547
dtype: float64
```

The first two rows of the data series:

```
0  0.720876
1 -0.765898
dtype: float64
```

**tail()** returns the last **n** rows(observe the index values). The default number of elements to display is five, but you may pass a custom number.

```
import pandas as pd
import numpy as np

#Create a series with 4 random numbers
s = pd.Series(np.random.randn(4))
print ("The original series is:")
print s

print ("The last two rows of the data series:")
print s.tail(2)
```

[Live Demo](#)

Its **output** is as follows –

The original series is:

0 -0.655091

1 -0.881407

2 -0.608592

3 -2.341413

dtype: float64

The last two rows of the data series:

2 -0.608592

3 -2.341413

dtype: float64

## DataFrame Basic Functionality

Let us now understand what DataFrame Basic Functionality is. The following tables lists down the important attributes or methods that help in DataFrame Basic Functionality.

Sr.No.	Attribute or Method & Description
1	<b>T</b> Transposes rows and columns.
2	<b>axes</b> Returns a list with the row axis labels and column axis labels as the only members.

3	<b>dtypes</b> Returns the dtypes in this object.
4	<b>empty</b> True if NDFrame is entirely empty [no items]; if any of the axes are of length 0.
5	<b>ndim</b> Number of axes / array dimensions.
6	<b>shape</b> Returns a tuple representing the dimensionality of the DataFrame.
7	<b>size</b> Number of elements in the NDFrame.
8	<b>values</b> Numpy representation of NDFrame.
9	<b>head()</b> Returns the first n rows.
10	<b>tail()</b> Returns last n rows.

Let us now create a DataFrame and see all how the above mentioned attributes operate.

## Example

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

*#Create a Dictionary of series*

```
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}
```

*#Create a DataFrame*

```
df = pd.DataFrame(d)
print ("Our data series is:")
print df
```

Its **output** is as follows –

Our data series is:

	Age	Name	Rating
0	25	Tom	4.23
1	26	James	3.24
2	25	Ricky	3.98
3	23	Vin	2.56
4	30	Steve	3.20
5	29	Smith	4.60
6	23	Jack	3.80

## T (Transpose)

Returns the transpose of the DataFrame. The rows and columns will interchange.

```
import pandas as pd
import numpy as np

# Create a Dictionary of series
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}

# Create a DataFrame
df = pd.DataFrame(d)
print ("The transpose of the data series is:")
print df.T
```

[Live Demo](#)

Its **output** is as follows –

The transpose of the data series is:

	0	1	2	3	4	5	6
Age	25	26	25	23	30	29	23
Name	Tom	James	Ricky	Vin	Steve	Smith	Jack
Rating	4.23	3.24	3.98	2.56	3.2	4.6	3.8

## axes

Returns the list of row axis labels and column axis labels.

Live Demo

```
import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom', 'James', 'Ricky', 'Vin', 'Steve', 'Smith', 'Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}

#Create a DataFrame
df = pd.DataFrame(d)
print ("Row axis labels and column axis labels are:")
print df.axes
```

Its **output** is as follows –

Row axis labels and column axis labels are:

```
[RangeIndex(start=0, stop=7, step=1), Index([u'Age', u'Name', u'Rating'],
dtype='object')]
```

## dtypes

Returns the data type of each column.

Live Demo

```
import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom', 'James', 'Ricky', 'Vin', 'Steve', 'Smith', 'Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}

#Create a DataFrame
df = pd.DataFrame(d)
print ("The data types of each column are:")
print df.dtypes
```

Its **output** is as follows –

The data types of each column are:  
Age     int64

```
Name    object
Rating  float64
dtype: object
```

## empty

Returns the Boolean value saying whether the Object is empty or not; True indicates that the object is empty.

```
import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack']),
      'Age':pd.Series([25,26,25,23,30,29,23]),
      'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}

#Create a DataFrame
df = pd.DataFrame(d)
print ("Is the object empty?")
print df.empty
```

[Live Demo](#)

Its **output** is as follows –

```
Is the object empty?
False
```

## ndim

Returns the number of dimensions of the object. By definition, DataFrame is a 2D object.

```
import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack']),
      'Age':pd.Series([25,26,25,23,30,29,23]),
      'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}

#Create a DataFrame
```

[Live Demo](#)

```
df = pd.DataFrame(d)
print ("Our object is:")
print df
print ("The dimension of the object is:")
print df.ndim
```

Its **output** is as follows –

Our object is:

	Age	Name	Rating
0	25	Tom	4.23
1	26	James	3.24
2	25	Ricky	3.98
3	23	Vin	2.56
4	30	Steve	3.20
5	29	Smith	4.60
6	23	Jack	3.80

The dimension of the object is:

2

## shape

Returns a tuple representing the dimensionality of the DataFrame. Tuple (a,b), where **a** represents the number of rows and **b** represents the number of columns.

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

*#Create a Dictionary of series*

```
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}
```

*#Create a DataFrame*

```
df = pd.DataFrame(d)
print ("Our object is:")
print df
print ("The shape of the object is:")
print df.shape
```

Its **output** is as follows –

Our object is:

	Age	Name	Rating
0	25	Tom	4.23
1	26	James	3.24
2	25	Ricky	3.98
3	23	Vin	2.56
4	30	Steve	3.20
5	29	Smith	4.60
6	23	Jack	3.80

The shape of the object is:  
(7, 3)

## size

Returns the number of elements in the DataFrame.

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

*#Create a Dictionary of series*

```
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}
```

*#Create a DataFrame*

```
df = pd.DataFrame(d)
print ("Our object is:")
print df
print ("The total number of elements in our object is:")
print df.size
```

Its **output** is as follows –

Our object is:

	Age	Name	Rating
0	25	Tom	4.23
1	26	James	3.24
2	25	Ricky	3.98



```

3  23  Vin    2.56
4  30  Steve  3.20
5  29  Smith  4.60
6  23  Jack   3.80

```

The total number of elements in our object is:  
21

## values

Returns the actual data in the DataFrame as an **NDarray**.

```

import pandas as pd
import numpy as np

```

[Live Demo](#)

*#Create a Dictionary of series*

```

d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}

```

*#Create a DataFrame*

```

df = pd.DataFrame(d)
print ("Our object is:")
print df
print ("The actual data in our data frame is:")
print df.values

```

Its **output** is as follows –

Our object is:

	Age	Name	Rating
0	25	Tom	4.23
1	26	James	3.24
2	25	Ricky	3.98
3	23	Vin	2.56
4	30	Steve	3.20
5	29	Smith	4.60
6	23	Jack	3.80

The actual data in our data frame is:

```

[[25 'Tom' 4.23]
 [26 'James' 3.24]

```

```
[25 'Ricky' 3.98]
[23 'Vin' 2.56]
[30 'Steve' 3.2]
[29 'Smith' 4.6]
[23 'Jack' 3.8]]
```

## Head & Tail

To view a small sample of a DataFrame object, use the **head()** and **tail()** methods. **head()** returns the first **n** rows (observe the index values). The default number of elements to display is five, but you may pass a custom number.

```
import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}

#Create a DataFrame
df = pd.DataFrame(d)
print ("Our data frame is:")
print df
print ("The first two rows of the data frame is:")
print df.head(2)
```

[Live Demo](#)

Its **output** is as follows –

Our data frame is:

	Age	Name	Rating
0	25	Tom	4.23
1	26	James	3.24
2	25	Ricky	3.98
3	23	Vin	2.56
4	30	Steve	3.20
5	29	Smith	4.60
6	23	Jack	3.80

The first two rows of the data frame is:

	Age	Name	Rating
--	-----	------	--------

```
0 25 Tom 4.23
1 26 James 3.24
```

**tail()** returns the last **n** rows (observe the index values). The default number of elements to display is five, but you may pass a custom number.

```
import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom', 'James', 'Ricky', 'Vin', 'Steve', 'Smith', 'Jack']),
     'Age':pd.Series([25,26,25,23,30,29,23]),
     'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8])}

#Create a DataFrame
df = pd.DataFrame(d)
print ("Our data frame is:")
print df
print ("The last two rows of the data frame is:")
print df.tail(2)
```

[Live Demo](#)

Its **output** is as follows –

Our data frame is:

	Age	Name	Rating
0	25	Tom	4.23
1	26	James	3.24
2	25	Ricky	3.98
3	23	Vin	2.56
4	30	Steve	3.20
5	29	Smith	4.60
6	23	Jack	3.80

The last two rows of the data frame is:

	Age	Name	Rating
5	29	Smith	4.6
6	23	Jack	3.8

## Python Pandas - Descriptive Statistics

A large number of methods collectively compute descriptive statistics and other related operations on DataFrame. Most of these are aggregations like **sum()**, **mean()**, but some of them, like **sumsum()**, produce an object of the same size. Generally speaking, these methods take an **axis** argument, just like ndarray.{sum, std, ...}, but the axis can be specified by name or integer

### ■ DataFrame – “index” (axis=0, default), “columns” (axis=1)

Let us create a DataFrame and use this object throughout this chapter for all the operations.

## Example

```
import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack',
    'Lee','David','Gasper','Betina','Andres']),
    'Age':pd.Series([25,26,25,23,30,29,23,34,40,30,51,46]),
    'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8,3.78,2.98,4.80,4.10,3.65])
}

#Create a DataFrame
df = pd.DataFrame(d)
print df
```

[Live Demo](#)

Its **output** is as follows –

	Age	Name	Rating
0	25	Tom	4.23
1	26	James	3.24
2	25	Ricky	3.98
3	23	Vin	2.56
4	30	Steve	3.20
5	29	Smith	4.60
6	23	Jack	3.80
7	34	Lee	3.78
8	40	David	2.98
9	30	Gasper	4.80

```
10 51  Betina 4.10
11 46  Andres 3.65
```

## sum()

Returns the sum of the values for the requested axis. By default, axis is index (axis=0).

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

*#Create a Dictionary of series*

```
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack',
    'Lee','David','Gasper','Betina','Andres']),
    'Age':pd.Series([25,26,25,23,30,29,23,34,40,30,51,46]),
    'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8,3.78,2.98,4.80,4.10,3.65])
}
```

*#Create a DataFrame*

```
df = pd.DataFrame(d)
print df.sum()
```

Its **output** is as follows –

```
Age                                382
Name  TomJamesRickyVinSteveSmithJackLeeDavidGasperBe...
Rating                                44.92
dtype: object
```

Each individual column is added individually (Strings are appended).

## axis=1

This syntax will give the output as shown below.

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

*#Create a Dictionary of series*

```
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack',
```

```

'Lee', 'David', 'Gasper', 'Betina', 'Andres']]),
'Age':pd.Series([25,26,25,23,30,29,23,34,40,30,51,46]),
'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8,3.78,2.98,4.80,4.10,3.65])
}

#Create a DataFrame
df = pd.DataFrame(d)
print df.sum(1)

```

Its **output** is as follows –

```

0    29.23
1    29.24
2    28.98
3    25.56
4    33.20
5    33.60
6    26.80
7    37.78
8    42.98
9    34.80
10   55.10
11   49.65
dtype: float64

```

## mean()

Returns the average value

```

import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom', 'James', 'Ricky', 'Vin', 'Steve', 'Smith', 'Jack',
'Lee', 'David', 'Gasper', 'Betina', 'Andres']),
'Age':pd.Series([25,26,25,23,30,29,23,34,40,30,51,46]),
'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8,3.78,2.98,4.80,4.10,3.65])
}

#Create a DataFrame

```

Live Demo

```
df = pd.DataFrame(d)
print df.mean()
```

Its **output** is as follows –

```
Age      31.833333
Rating    3.743333
dtype: float64
```

## std()

Returns the Bressel standard deviation of the numerical columns.

```
import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack',
    'Lee','David','Gasper','Betina','Andres']),
    'Age':pd.Series([25,26,25,23,30,29,23,34,40,30,51,46]),
    'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8,3.78,2.98,4.80,4.10,3.65])
}

#Create a DataFrame
df = pd.DataFrame(d)
print df.std()
```

[Live Demo](#)

Its **output** is as follows –

```
Age      9.232682
Rating    0.661628
dtype: float64
```

## Functions & Description

Let us now understand the functions under Descriptive Statistics in Python Pandas. The following table list down the important functions –

Sr.No.	Function	Description
1	count()	Number of non-null observations
2	sum()	Sum of values
3	mean()	Mean of Values
4	median()	Median of Values
5	mode()	Mode of values
6	std()	Standard Deviation of the Values
7	min()	Minimum Value
8	max()	Maximum Value
9	abs()	Absolute Value
10	prod()	Product of Values
11	cumsum()	Cumulative Sum
12	cumprod()	Cumulative Product

**Note** – Since DataFrame is a Heterogeneous data structure. Generic operations don't work with all functions.

- Functions like **sum()**, **cumsum()** work with both numeric and character (or) string data elements without any error. Though **n** practice, character aggregations are never used generally, these functions do not throw any exception.
- Functions like **abs()**, **cumprod()** throw exception when the DataFrame contains character or string data because such operations cannot be performed.

## Summarizing Data

The **describe()** function computes a summary of statistics pertaining to the DataFrame columns.

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
#Create a Dictionary of series
```

```
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack',
```



```

'Lee', 'David', 'Gasper', 'Betina', 'Andres']]),
'Age':pd.Series([25,26,25,23,30,29,23,34,40,30,51,46]),
'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8,3.78,2.98,4.80,4.10,3.65])
}

#Create a DataFrame
df = pd.DataFrame(d)
print df.describe()

```

Its **output** is as follows –

	Age	Rating
count	12.000000	12.000000
mean	31.833333	3.743333
std	9.232682	0.661628
min	23.000000	2.560000
25%	25.000000	3.230000
50%	29.500000	3.790000
75%	35.500000	4.132500
max	51.000000	4.800000

This function gives the **mean**, **std** and **IQR** values. And, function excludes the character columns and given summary about numeric columns. '**include**' is the argument which is used to pass necessary information regarding what columns need to be considered for summarizing. Takes the list of values; by default, 'number'.

- **object** – Summarizes String columns
- **number** – Summarizes Numeric columns
- **all** – Summarizes all columns together (Should not pass it as a list value)

Now, use the following statement in the program and check the output –

```

import pandas as pd
import numpy as np

#Create a Dictionary of series
d = {'Name':pd.Series(['Tom', 'James', 'Ricky', 'Vin', 'Steve', 'Smith', 'Jack',
'Lee', 'David', 'Gasper', 'Betina', 'Andres']),
'Age':pd.Series([25,26,25,23,30,29,23,34,40,30,51,46]),
'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8,3.78,2.98,4.80,4.10,3.65])
}

```

Live Demo

```
#Create a DataFrame
df = pd.DataFrame(d)
print df.describe(include=['object'])
```

Its **output** is as follows –

```
      Name
count    12
unique    12
top      Ricky
freq      1
```

Now, use the following statement and check the output –

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
#Create a Dictionary of series
```

```
d = {'Name':pd.Series(['Tom','James','Ricky','Vin','Steve','Smith','Jack',
'Lee','David','Gasper','Betina','Andres']),
'Age':pd.Series([25,26,25,23,30,29,23,34,40,30,51,46]),
'Rating':pd.Series([4.23,3.24,3.98,2.56,3.20,4.6,3.8,3.78,2.98,4.80,4.10,3.65])
}
```

```
#Create a DataFrame
```

```
df = pd.DataFrame(d)
print df. describe(include='all')
```

Its **output** is as follows –

```
      Age      Name      Rating
count  12.000000      12  12.000000
unique      NaN      12      NaN
top      NaN  Ricky      NaN
freq      NaN      1      NaN
mean  31.833333      NaN  3.743333
std    9.232682      NaN  0.661628
min    23.000000      NaN  2.560000
25%    25.000000      NaN  3.230000
```

50%	29.500000	NaN	3.790000
75%	35.500000	NaN	4.132500
max	51.000000	NaN	4.800000

## Python Pandas - Function Application

To apply your own or another library's functions to Pandas objects, you should be aware of the three important methods. The methods have been discussed below. The appropriate method to use depends on whether your function expects to operate on an entire DataFrame, row- or column-wise, or element wise.

- Table wise Function Application: `pipe()`
- Row or Column Wise Function Application: `apply()`
- Element wise Function Application: `applymap()`

### Table-wise Function Application

Custom operations can be performed by passing the function and the appropriate number of parameters as pipe arguments. Thus, operation is performed on the whole DataFrame.

For example, add a value 2 to all the elements in the DataFrame. Then,

#### adder function

The adder function adds two numeric values as parameters and returns the sum.

```
def adder(ele1,ele2):
    return ele1+ele2
```

We will now use the custom function to conduct operation on the DataFrame.

```
df = pd.DataFrame(np.random.randn(5,3),columns=['col1','col2','col3'])
df.pipe(adder,2)
```

Let's see the full program –

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
def adder(ele1,ele2):
    return ele1+ele2

df = pd.DataFrame(np.random.randn(5,3),columns=['col1','col2','col3'])
df.pipe(adder,2)
print df.apply(np.mean)
```

Its **output** is as follows –

	col1	col2	col3
0	2.176704	2.219691	1.509360
1	2.222378	2.422167	3.953921
2	2.241096	1.135424	2.696432
3	2.355763	0.376672	1.182570
4	2.308743	2.714767	2.130288

## Row or Column Wise Function Application

Arbitrary functions can be applied along the axes of a DataFrame or Panel using the **apply()** method, which, like the descriptive statistics methods, takes an optional axis argument. By default, the operation performs column wise, taking each column as an array-like.

### Example 1

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5,3),columns=['col1','col2','col3'])
df.apply(np.mean)
print df.apply(np.mean)
```

[Live Demo](#)

Its **output** is as follows –

```
col1  -0.288022
col2   1.044839
col3  -0.187009
dtype: float64
```

By passing **axis** parameter, operations can be performed row wise.

## Example 2

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5,3),columns=['col1','col2','col3'])
df.apply(np.mean,axis=1)
print df.apply(np.mean)
```

[Live Demo](#)

Its **output** is as follows –

```
col1    0.034093
col2   -0.152672
col3   -0.229728
dtype: float64
```

## Example 3

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5,3),columns=['col1','col2','col3'])
df.apply(lambda x: x.max() - x.min())
print df.apply(np.mean)
```

[Live Demo](#)

Its **output** is as follows –

```
col1   -0.167413
col2   -0.370495
col3   -0.707631
dtype: float64
```

## Element Wise Function Application

Not all functions can be vectorized (neither the NumPy arrays which return another array nor any value), the methods **applymap()** on DataFrame and **analogously map()** on

Series accept any Python function taking a single value and returning a single value.

## Example 1

```
import pandas as pd
import numpy as np
df = pd.DataFrame(np.random.randn(5,3),columns=['col1','col2','col3'])

# My custom function
df['col1'].map(lambda x:x*100)
print df.apply(np.mean)
```

[Live Demo](#)

Its **output** is as follows –

```
col1    0.480742
col2    0.454185
col3    0.266563
dtype: float64
```

## Example 2

```
import pandas as pd
import numpy as np

# My custom function
df = pd.DataFrame(np.random.randn(5,3),columns=['col1','col2','col3'])
df.applymap(lambda x:x*100)
print df.apply(np.mean)
```

[Live Demo](#)

Its **output** is as follows –

```
col1    0.395263
col2    0.204418
col3   -0.795188
dtype: float64
```

# Python Pandas - Reindexing

**Reindexing** changes the row labels and column labels of a DataFrame. To reindex means to conform the data to match a given set of labels along a particular axis.

Multiple operations can be accomplished through indexing like –

- Reorder the existing data to match a new set of labels.
- Insert missing value (NA) markers in label locations where no data for the label existed.

## Example

```
import pandas as pd
import numpy as np

N=20

df = pd.DataFrame({
    'A': pd.date_range(start='2016-01-01', periods=N, freq='D'),
    'x': np.linspace(0, stop=N-1, num=N),
    'y': np.random.rand(N),
    'C': np.random.choice(['Low', 'Medium', 'High'], N).tolist(),
    'D': np.random.normal(100, 10, size=(N)).tolist()
})

#reindex the DataFrame
df_reindexed = df.reindex(index=[0,2,5], columns=['A', 'C', 'B'])

print df_reindexed
```

[Live Demo](#)

Its **output** is as follows –

	A	C	B
0	2016-01-01	Low	NaN
2	2016-01-03	High	NaN
5	2016-01-06	Low	NaN

## Reindex to Align with Other Objects

You may wish to take an object and reindex its axes to be labeled the same as another object. Consider the following example to understand the same.

## Example

```
import pandas as pd
import numpy as np

df1 = pd.DataFrame(np.random.randn(10,3),columns=['col1','col2','col3'])
df2 = pd.DataFrame(np.random.randn(7,3),columns=['col1','col2','col3'])

df1 = df1.reindex_like(df2)
print df1
```

[Live Demo](#)

Its **output** is as follows –

	col1	col2	col3
0	-2.467652	-1.211687	-0.391761
1	-0.287396	0.522350	0.562512
2	-0.255409	-0.483250	1.866258
3	-1.150467	-0.646493	-0.222462
4	0.152768	-2.056643	1.877233
5	-1.155997	1.528719	-1.343719
6	-1.015606	-1.245936	-0.295275

**Note** – Here, the **df1** DataFrame is altered and reindexed like **df2**. The column names should be matched or else NAN will be added for the entire column label.

## Filling while ReIndexing

**reindex()** takes an optional parameter method which is a filling method with values as follows –

- **pad/ffill** – Fill values forward
- **bfill/backfill** – Fill values backward
- **nearest** – Fill from the nearest index values

## Example

```
import pandas as pd
import numpy as np
```

[Live Demo](#)



```

df1 = pd.DataFrame(np.random.randn(6,3),columns=['col1','col2','col3'])
df2 = pd.DataFrame(np.random.randn(2,3),columns=['col1','col2','col3'])

# Padding NAN's
print df2.reindex_like(df1)

# Now Fill the NAN's with preceding Values
print ("Data Frame with Forward Fill:")
print df2.reindex_like(df1,method='ffill')

```

Its **output** is as follows –

	col1	col2	col3
0	1.311620	-0.707176	0.599863
1	-0.423455	-0.700265	1.133371
2	NaN	NaN	NaN
3	NaN	NaN	NaN
4	NaN	NaN	NaN
5	NaN	NaN	NaN

Data Frame with Forward Fill:

	col1	col2	col3
0	1.311620	-0.707176	0.599863
1	-0.423455	-0.700265	1.133371
2	-0.423455	-0.700265	1.133371
3	-0.423455	-0.700265	1.133371
4	-0.423455	-0.700265	1.133371
5	-0.423455	-0.700265	1.133371

**Note** – The last four rows are padded.

## Limits on Filling while Reindexing

The limit argument provides additional control over filling while reindexing. Limit specifies the maximum count of consecutive matches. Let us consider the following example to understand the same –

### Example

```

import pandas as pd
import numpy as np

df1 = pd.DataFrame(np.random.randn(6,3),columns=['col1','col2','col3'])
df2 = pd.DataFrame(np.random.randn(2,3),columns=['col1','col2','col3'])

# Padding NAN's
print df2.reindex_like(df1)

# Now Fill the NAN's with preceding Values
print ("Data Frame with Forward Fill limiting to 1:")
print df2.reindex_like(df1,method='ffill',limit=1)

```

Its **output** is as follows –

	col1	col2	col3
0	0.247784	2.128727	0.702576
1	-0.055713	-0.021732	-0.174577
2	NaN	NaN	NaN
3	NaN	NaN	NaN
4	NaN	NaN	NaN
5	NaN	NaN	NaN

Data Frame with Forward Fill limiting to 1:

	col1	col2	col3
0	0.247784	2.128727	0.702576
1	-0.055713	-0.021732	-0.174577
2	-0.055713	-0.021732	-0.174577
3	NaN	NaN	NaN
4	NaN	NaN	NaN
5	NaN	NaN	NaN

**Note** – Observe, only the 7th row is filled by the preceding 6th row. Then, the rows are left as they are.

## Renaming

The `rename()` method allows you to relabel an axis based on some mapping (a dict or Series) or an arbitrary function.

Let us consider the following example to understand this –

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
df1 = pd.DataFrame(np.random.randn(6,3),columns=['col1','col2','col3'])
print df1

print ("After renaming the rows and columns:")
print df1.rename(columns={'col1' : 'c1', 'col2' : 'c2'},
index = {0 : 'apple', 1 : 'banana', 2 : 'durian'})
```

Its **output** is as follows –

	col1	col2	col3
0	0.486791	0.105759	1.540122
1	-0.990237	1.007885	-0.217896
2	-0.483855	-1.645027	-1.194113
3	-0.122316	0.566277	-0.366028
4	-0.231524	-0.721172	-0.112007
5	0.438810	0.000225	0.435479

After renaming the rows and columns:

	c1	c2	col3
apple	0.486791	0.105759	1.540122
banana	-0.990237	1.007885	-0.217896
durian	-0.483855	-1.645027	-1.194113
3	-0.122316	0.566277	-0.366028
4	-0.231524	-0.721172	-0.112007
5	0.438810	0.000225	0.435479

The rename() method provides an **inplace** named parameter, which by default is False and copies the underlying data. Pass **inplace=True** to rename the data in place.

## Python Pandas - Iteration

The behavior of basic iteration over Pandas objects depends on the type. When iterating over a Series, it is regarded as array-like, and basic iteration produces the values. Other data structures, like DataFrame and Panel, follow the **dict-like** convention of iterating over the **keys** of the objects.

In short, basic iteration (for **i** in object) produces –

- **Series** – values
- **DataFrame** – column labels
- **Panel** – item labels

## Iterating a DataFrame

Iterating a DataFrame gives column names. Let us consider the following example to understand the same.

```
import pandas as pd
import numpy as np

N=20
df = pd.DataFrame({
    'A': pd.date_range(start='2016-01-01', periods=N, freq='D'),
    'x': np.linspace(0, stop=N-1, num=N),
    'y': np.random.rand(N),
    'C': np.random.choice(['Low', 'Medium', 'High'], N).tolist(),
    'D': np.random.normal(100, 10, size=(N)).tolist()
})

for col in df:
    print col
```

[Live Demo](#)

Its **output** is as follows –

```
A
C
D
x
y
```

To iterate over the rows of the DataFrame, we can use the following functions –

- **iteritems()** – to iterate over the (key,value) pairs
- **iterrows()** – iterate over the rows as (index,series) pairs
- **itertuples()** – iterate over the rows as namedtuples

iteritems()

Iterates over each column as key, value pair with label as key and column value as a Series object.

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(4,3),columns=['col1','col2','col3'])
for key,value in df.iteritems():
    print key,value
```

[Live Demo](#)

Its **output** is as follows –

```
col1 0    0.802390
1    0.324060
2    0.256811
3    0.839186
Name: col1, dtype: float64

col2 0    1.624313
1   -1.033582
2    1.796663
3    1.856277
Name: col2, dtype: float64

col3 0   -0.022142
1   -0.230820
2    1.160691
3   -0.830279
Name: col3, dtype: float64
```

Observe, each column is iterated separately as a key-value pair in a Series.

## iterrows()

iterrows() returns the iterator yielding each index value along with a series containing the data in each row.

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
df = pd.DataFrame(np.random.randn(4,3),columns = ['col1','col2','col3'])
for row_index,row in df.iterrows():
    print row_index,row
```

Its **output** is as follows –

```
0 col1    1.529759
  col2    0.762811
  col3   -0.634691
Name: 0, dtype: float64

1 col1   -0.944087
  col2    1.420919
  col3   -0.507895
Name: 1, dtype: float64

2 col1   -0.077287
  col2   -0.858556
  col3   -0.663385
Name: 2, dtype: float64

3 col1   -1.638578
  col2    0.059866
  col3    0.493482
Name: 3, dtype: float64
```

**Note** – Because **iterrows()** iterate over the rows, it doesn't preserve the data type across the row. 0,1,2 are the row indices and col1,col2,col3 are column indices.

## itertuples()

itertuples() method will return an iterator yielding a named tuple for each row in the DataFrame. The first element of the tuple will be the row's corresponding index value, while the remaining values are the row values.

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
df = pd.DataFrame(np.random.randn(4,3),columns = ['col1','col2','col3'])
for row in df.itertuples():
    print row
```

Its **output** is as follows –

```
Pandas(Index=0, col1=1.5297586201375899, col2=0.76281127433814944, col3=-0.6346908238310438)

Pandas(Index=1, col1=-0.94408735763808649, col2=1.4209186418359423, col3=-0.50789517967096232)

Pandas(Index=2, col1=-0.07728664756791935, col2=-0.85855574139699076, col3=-0.6633852507207626)

Pandas(Index=3, col1=0.65734942534106289, col2=-0.95057710432604969, col3=0.80344487462316527)
```

**Note** – Do not try to modify any object while iterating. Iterating is meant for reading and the iterator returns a copy of the original object (a view), thus the changes will not reflect on the original object.

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
df = pd.DataFrame(np.random.randn(4,3), columns = ['col1', 'col2', 'col3'])

for index, row in df.iterrows():
    row['a'] = 10
print df
```

Its **output** is as follows –

	col1	col2	col3
0	-1.739815	0.735595	-0.295589
1	0.635485	0.106803	1.527922
2	-0.939064	0.547095	0.038585
3	-1.016509	-0.116580	-0.523158

Observe, no changes reflected.

## Python Pandas - Sorting

There are two kinds of sorting available in Pandas. They are –

- By label
- By Actual Value

Let us consider an example with an output.

```
import pandas as pd
import numpy as np

unsorted_df=pd.DataFrame(np.random.randn(10,2),index=[1,4,6,2,3,5,9,8,0,7],columns=['col2','col1'])
print unsorted_df
```

Its **output** is as follows –

	col2	col1
1	-2.063177	0.537527
4	0.142932	-0.684884
6	0.012667	-0.389340
2	-0.548797	1.848743
3	-1.044160	0.837381
5	0.385605	1.300185
9	1.031425	-1.002967
8	-0.407374	-0.435142
0	2.237453	-1.067139
7	-1.445831	-1.701035

In **unsorted\_df**, the **labels** and the **values** are unsorted. Let us see how these can be sorted.

## By Label

Using the **sort\_index()** method, by passing the axis arguments and the order of sorting, DataFrame can be sorted. By default, sorting is done on row labels in ascending order.

```
import pandas as pd
import numpy as np

unsorted_df = pd.DataFrame(np.random.randn(10,2),index=[1,4,6,2,3,5,9,8,0,7],columns=['col2','col1'])
```



```
sorted_df=unsorted_df.sort_index()
print sorted_df
```

Its **output** is as follows –

	col2	col1
0	0.208464	0.627037
1	0.641004	0.331352
2	-0.038067	-0.464730
3	-0.638456	-0.021466
4	0.014646	-0.737438
5	-0.290761	-1.669827
6	-0.797303	-0.018737
7	0.525753	1.628921
8	-0.567031	0.775951
9	0.060724	-0.322425

## Order of Sorting

By passing the Boolean value to ascending parameter, the order of the sorting can be controlled. Let us consider the following example to understand the same.

```
import pandas as pd
import numpy as np

unsorted_df = pd.DataFrame(np.random.randn(10,2),index=[1,4,6,2,3,5,9,8,0,7],columns = ['col2','col1'])

sorted_df = unsorted_df.sort_index(ascending=False)
print sorted_df
```

Its **output** is as follows –

	col2	col1
9	0.825697	0.374463
8	-1.699509	0.510373
7	-0.581378	0.622958
6	-0.202951	0.954300
5	-1.289321	-1.551250

```

4  1.302561  0.851385
3 -0.157915 -0.388659
2 -1.222295  0.166609
1  0.584890 -0.291048
0  0.668444 -0.061294

```

## Sort the Columns

By passing the axis argument with a value 0 or 1, the sorting can be done on the column labels. By default, axis=0, sort by row. Let us consider the following example to understand the same.

```

import pandas as pd
import numpy as np

unsorted_df = pd.DataFrame(np.random.randn(10,2),index=[1,4,6,2,3,5,9,8,0,7],columns = ['col2', 'col1'])

sorted_df=unsorted_df.sort_index(axis=1)

print sorted_df

```

Its **output** is as follows –

	col1	col2
1	-0.291048	0.584890
4	0.851385	1.302561
6	0.954300	-0.202951
2	0.166609	-1.222295
3	-0.388659	-0.157915
5	-1.551250	-1.289321
9	0.374463	0.825697
8	0.510373	-1.699509
0	-0.061294	0.668444
7	0.622958	-0.581378

## By Value

Like index sorting, **sort\_values()** is the method for sorting by values. It accepts a 'by' argument which will use the column name of the DataFrame with which the values are to be sorted.

```
import pandas as pd
import numpy as np

unsorted_df = pd.DataFrame({'col1':[2,1,1,1], 'col2':[1,3,2,4]})
sorted_df = unsorted_df.sort_values(by='col1')

print sorted_df
```

Its **output** is as follows –

```
   col1  col2
1     1     3
2     1     2
3     1     4
0     2     1
```

Observe, col1 values are sorted and the respective col2 value and row index will alter along with col1. Thus, they look unsorted.

'by' argument takes a list of column values.

```
import pandas as pd
import numpy as np

unsorted_df = pd.DataFrame({'col1':[2,1,1,1], 'col2':[1,3,2,4]})
sorted_df = unsorted_df.sort_values(by=['col1', 'col2'])

print sorted_df
```

Its **output** is as follows –

```
   col1  col2
2     1     2
1     1     3
3     1     4
0     2     1
```

## Sorting Algorithm

**sort\_values()** provides a provision to choose the algorithm from mergesort, heapsort and quicksort. Mergesort is the only stable algorithm.

```
import pandas as pd
import numpy as np

unsorted_df = pd.DataFrame({'col1':[2,1,1,1], 'col2':[1,3,2,4]})
sorted_df = unsorted_df.sort_values(by='col1' ,kind='mergesort')

print sorted_df
```

[Live Demo](#)

Its **output** is as follows –

```
col1 col2
1    1    3
2    1    2
3    1    4
0    2    1
```

## Python Pandas - Working with Text Data

In this chapter, we will discuss the string operations with our basic Series/Index. In the subsequent chapters, we will learn how to apply these string functions on the DataFrame.

Pandas provides a set of string functions which make it easy to operate on string data. Most importantly, these functions ignore (or exclude) missing/NaN values.

Almost, all of these methods work with Python string functions (refer: <https://docs.python.org/3/library/stdtypes.html#string-methods>). So, convert the Series Object to String Object and then perform the operation.

Let us now see how each operation performs.

Sr.No	Function & Description
1	<b>lower()</b> Converts strings in the Series/Index to lower case.
2	<b>upper()</b> Converts strings in the Series/Index to upper case.
3	<b>len()</b> Computes String length().
4	<b>strip()</b>

	Helps strip whitespace(including newline) from each string in the Series/index from both the sides.
5	<b>split(' ')</b> Splits each string with the given pattern.
6	<b>cat(sep=' ')</b> Concatenates the series/index elements with given separator.
7	<b>get_dummies()</b> Returns the DataFrame with One-Hot Encoded values.
8	<b>contains(pattern)</b> Returns a Boolean value True for each element if the substring contains in the element, else False.
9	<b>replace(a,b)</b> Replaces the value <b>a</b> with the value <b>b</b> .
10	<b>repeat(value)</b> Repeats each element with specified number of times.
11	<b>count(pattern)</b> Returns count of appearance of pattern in each element.
12	<b>startswith(pattern)</b> Returns true if the element in the Series/Index starts with the pattern.
13	<b>endswith(pattern)</b> Returns true if the element in the Series/Index ends with the pattern.
14	<b>find(pattern)</b> Returns the first position of the first occurrence of the pattern.
15	<b>findall(pattern)</b> Returns a list of all occurrence of the pattern.
16	<b>swapcase</b> Swaps the case lower/upper.
17	<b>islower()</b> Checks whether all characters in each string in the Series/Index in lower case or not. Returns Boolean
18	<b>isupper()</b> Checks whether all characters in each string in the Series/Index in upper case or not. Returns Boolean.
19	<b>isnumeric()</b>

Checks whether all characters in each string in the Series/Index are numeric.  
Returns Boolean.

Let us now create a Series and see how all the above functions work.

```
import pandas as pd
import numpy as np

s = pd.Series(['Tom', 'William Rick', 'John', 'Alber@t', np.nan, '1234', 'SteveSm:
print s
```

[Live Demo](#)

Its **output** is as follows –

```
0      Tom
1  William Rick
2      John
3  Alber@t
4      NaN
5      1234
6  Steve Smith
dtype: object
```

## lower()

```
import pandas as pd
import numpy as np

s = pd.Series(['Tom', 'William Rick', 'John', 'Alber@t', np.nan, '1234', 'SteveSm:
print s.str.lower()
```

[Live Demo](#)

Its **output** is as follows –

```
0      tom
1  william rick
2      john
```

```

3     alber@t
4         NaN
5         1234
6  steve smith
dtype: object

```

## upper()

```

import pandas as pd
import numpy as np

```

[Live Demo](#)

```

s = pd.Series(['Tom', 'William Rick', 'John', 'Alber@t', np.nan, '1234', 'SteveSm:
print s.str.upper()

```

Its **output** is as follows –

```

0      TOM
1  WILLIAM RICK
2      JOHN
3   ALBER@T
4      NaN
5     1234
6  STEVE SMITH
dtype: object

```

## len()

```

import pandas as pd
import numpy as np

```

[Live Demo](#)

```

s = pd.Series(['Tom', 'William Rick', 'John', 'Alber@t', np.nan, '1234', 'SteveSm:
print s.str.len()

```

Its **output** is as follows –

```

0    3.0
1   12.0
2    4.0
3    7.0
4   NaN
5    4.0
6   10.0
dtype: float64

```

## strip()

```

import pandas as pd
import numpy as np
s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])
print s
print ("After Stripping:")
print s.str.strip()

```

[Live Demo](#)

Its **output** is as follows –

```

0      Tom
1 William Rick
2      John
3  Alber@t
dtype: object

```

After Stripping:

```

0      Tom
1 William Rick
2      John
3  Alber@t
dtype: object

```

## split(pattern)

```

import pandas as pd
import numpy as np
s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])

```

[Live Demo](#)



```
print s
print ("Split Pattern:")
print s.str.split(' ')
```

Its **output** is as follows –

```
0      Tom
1  William Rick
2      John
3  Alber@t
dtype: object

Split Pattern:
0 [Tom, , , , , , , , ]
1 [, , , , William, Rick]
2 [John]
3 [Alber@t]
dtype: object
```

## cat(sep=pattern)

```
import pandas as pd
import numpy as np

s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])

print s.str.cat(sep='_')
```

[Live Demo](#)

Its **output** is as follows –

```
Tom _ William Rick_John_Alber@t
```

## get\_dummies()

```
import pandas as pd
import numpy as np

s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])
```

[Live Demo](#)

```
print s.str.get_dummies()
```

Its **output** is as follows –

	William Rick	Alber@t	John	Tom
0	0	0	0	1
1	1	0	0	0
2	0	0	1	0
3	0	1	0	0

contains ()

```
import pandas as pd

s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])

print s.str.contains(' ')
```

[Live Demo](#)

Its **output** is as follows –

```
0    True
1    True
2   False
3   False
dtype: bool
```

replace(a,b)

```
import pandas as pd

s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])

print s
print ("After replacing @ with $:")
print s.str.replace('@','$')
```

[Live Demo](#)

Its **output** is as follows –

```
0 Tom
1 William Rick
2 John
3 Alber@t
dtype: object
```

After replacing @ with \$:

```
0 Tom
1 William Rick
2 John
3 Alber$t
dtype: object
```

## repeat(value)

```
import pandas as pd
```

[Live Demo](#)

```
s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])
```

```
print s.str.repeat(2)
```

Its **output** is as follows –

```
0 Tom      Tom
1 William Rick William Rick
2      JohnJohn
3      Alber@tAlber@t
dtype: object
```

## count(pattern)

```
import pandas as pd
```

[Live Demo](#)

```
s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])
```

```
print ("The number of 'm's in each string:")
```

```
print s.str.count('m')
```

Its **output** is as follows –

The number of 'm's in each string:

```
0  1
1  1
2  0
3  0
```

## startswith(pattern)

```
import pandas as pd
```

```
s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])
```

```
print ("Strings that start with 'T':")
```

```
print s.str.startswith ('T')
```

[Live Demo](#)

Its **output** is as follows –

```
0  True
1  False
2  False
3  False
dtype: bool
```

## endswith(pattern)

```
import pandas as pd
```

```
s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])
```

```
print ("Strings that end with 't':")
```

```
print s.str.endswith('t')
```

[Live Demo](#)

Its **output** is as follows –

Strings that end with 't':

```
0  False
1  False
2  False
```

```
3 True
dtype: bool
```

## find(pattern)

```
import pandas as pd

s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])

print s.str.find('e')
```

[Live Demo](#)

Its **output** is as follows –

```
0 -1
1 -1
2 -1
3 3
dtype: int64
```

"-1" indicates that there no such pattern available in the element.

## findall(pattern)

```
import pandas as pd

s = pd.Series(['Tom ', ' William Rick', 'John', 'Alber@t'])

print s.str.findall('e')
```

[Live Demo](#)

Its **output** is as follows –

```
0 []
1 []
2 []
3 [e]
dtype: object
```

Null list([ ]) indicates that there is no such pattern available in the element.

## swapcase()

```
import pandas as pd
```

[Live Demo](#)

```
s = pd.Series(['Tom', 'William Rick', 'John', 'Alber@t'])  
print s.str.swapcase()
```

Its **output** is as follows –

```
0  tOM  
1  wILLIAM rICK  
2  jOHN  
3  aLBER@T  
dtype: object
```

## islower()

```
import pandas as pd
```

[Live Demo](#)

```
s = pd.Series(['Tom', 'William Rick', 'John', 'Alber@t'])  
print s.str.islower()
```

Its **output** is as follows –

```
0  False  
1  False  
2  False  
3  False  
dtype: bool
```

## isupper()

```
import pandas as pd
```

[Live Demo](#)

```
s = pd.Series(['Tom', 'William Rick', 'John', 'Alber@t'])
```

```
print s.str.isupper()
```

Its **output** is as follows –

```
0 False
1 False
2 False
3 False
dtype: bool
```

isnumeric()

```
import pandas as pd

s = pd.Series(['Tom', 'William Rick', 'John', 'Alber@t'])

print s.str.isnumeric()
```

[Live Demo](#)

Its **output** is as follows –

```
0 False
1 False
2 False
3 False
dtype: bool
```

## Python Pandas - Options and Customization

Pandas provide API to customize some aspects of its behavior, display is being mostly used.

The API is composed of five relevant functions. They are –

- `get_option()`
- `set_option()`
- `reset_option()`
- `describe_option()`

## ■ option\_context()

Let us now understand how the functions operate.

### get\_option(param)

get\_option takes a single parameter and returns the value as given in the output below –

#### display.max\_rows

Displays the default number of value. Interpreter reads this value and displays the rows with this value as upper limit to display.

```
import pandas as pd
print pd.get_option("display.max_rows")
```

[Live Demo](#)

Its **output** is as follows –

```
60
```

#### display.max\_columns

Displays the default number of value. Interpreter reads this value and displays the rows with this value as upper limit to display.

```
import pandas as pd
print pd.get_option("display.max_columns")
```

[Live Demo](#)

Its **output** is as follows –

```
20
```

Here, 60 and 20 are the default configuration parameter values.

### set\_option(param,value)

set\_option takes two arguments and sets the value to the parameter as shown below –



## display.max\_rows

Using **set\_option()**, we can change the default number of rows to be displayed.

```
import pandas as pd

pd.set_option("display.max_rows",80)

print pd.get_option("display.max_rows")
```

[Live Demo](#)

Its **output** is as follows –

```
80
```

## display.max\_columns

Using **set\_option()**, we can change the default number of rows to be displayed.

```
import pandas as pd

pd.set_option("display.max_columns",30)

print pd.get_option("display.max_columns")
```

[Live Demo](#)

Its **output** is as follows –

```
30
```

## reset\_option(param)

**reset\_option** takes an argument and sets the value back to the default value.

## display.max\_rows

Using **reset\_option()**, we can change the value back to the default number of rows to be displayed.

[Live Demo](#)

```
import pandas as pd

pd.reset_option("display.max_rows")
print pd.get_option("display.max_rows")
```

Its **output** is as follows –

```
60
```

## describe\_option(param)

**describe\_option** prints the description of the argument.

## display.max\_rows

Using `reset_option()`, we can change the value back to the default number of rows to be displayed.

```
import pandas as pd
pd.describe_option("display.max_rows")
```

[Live Demo](#)

Its **output** is as follows –

```
display.max_rows : int
```

If `max_rows` is exceeded, switch to truncate view. Depending on 'large\_repr', objects are either centrally truncated or printed as a summary view. 'None' value means unlimited.

In case python/IPython is running in a terminal and 'large\_repr' equals 'truncate' this can be set to 0 and pandas will auto-detect the height of the terminal and print a truncated object which fits the screen height. The IPython notebook, IPython qtconsole, or IDLE do not run in a terminal and hence it is not possible to do correct auto-detection.

```
[default: 60] [currently: 60]
```

## option\_context()

option\_context context manager is used to set the option in **with statement** temporarily. Option values are restored automatically when you exit the **with block** –

## display.max\_rows

Using option\_context(), we can set the value temporarily.

```
import pandas as pd
with pd.option_context("display.max_rows",10):
    print(pd.get_option("display.max_rows"))
    print(pd.get_option("display.max_rows"))
```

[Live Demo](#)

Its **output** is as follows –

```
10
10
```

See, the difference between the first and the second print statements. The first statement prints the value set by **option\_context()** which is temporary within the **with context** itself. After the **with context**, the second print statement prints the configured value.

## Frequently used Parameters

Sr.No	Parameter & Description
1	<b>display.max_rows</b> Displays maximum number of rows to display
2	<b>display.max_columns</b> Displays maximum number of columns to display
3	<b>display.expand_frame_repr</b> Displays DataFrames to Stretch Pages
4	<b>display.max_colwidth</b> Displays maximum column width
5	<b>display.precision</b> Displays precision for decimal numbers

# Python Pandas - Indexing and Selecting Data

In this chapter, we will discuss how to slice and dice the data and generally get the subset of pandas object.

The Python and NumPy indexing operators "[ ]" and attribute operator "." provide quick and easy access to Pandas data structures across a wide range of use cases. However, since the type of the data to be accessed isn't known in advance, directly using standard operators has some optimization limits. For production code, we recommend that you take advantage of the optimized pandas data access methods explained in this chapter.

Pandas now supports three types of Multi-axes indexing; the three types are mentioned in the following table –

Sr.No	Indexing & Description
1	<b>.loc()</b> Label based
2	<b>.iloc()</b> Integer based
3	<b>.ix()</b> Both Label and Integer based

## .loc()

Pandas provide various methods to have purely **label based indexing**. When slicing, the start bound is also included. Integers are valid labels, but they refer to the label and not the position.

**.loc()** has multiple access methods like –

- A single scalar label
- A list of labels
- A slice object
- A Boolean array

**loc** takes two single/list/range operator separated by ','. The first one indicates the row and the second one indicates columns.

## Example 1

```
#import the pandas library and aliasing as pd
import pandas as pd
```

[Live Demo](#)

```
import numpy as np

df = pd.DataFrame(np.random.randn(8, 4),
index = ['a','b','c','d','e','f','g','h'], columns = ['A', 'B', 'C', 'D'])

#select all rows for a specific column
print df.loc[:, 'A']
```

Its **output** is as follows –

```
a    0.391548
b   -0.070649
c   -0.317212
d   -2.162406
e    2.202797
f    0.613709
g    1.050559
h    1.122680
Name: A, dtype: float64
```

## Example 2

```
# import the pandas library and aliasing as pd
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(8, 4),
index = ['a','b','c','d','e','f','g','h'], columns = ['A', 'B', 'C', 'D'])

# Select all rows for multiple columns, say list[]
print df.loc[:, ['A', 'C']]
```

[Live Demo](#)

Its **output** is as follows –

	A	C
a	0.391548	0.745623
b	-0.070649	1.620406
c	-0.317212	1.448365
d	-2.162406	-0.873557
e	2.202797	0.528067

```
f  0.613709  0.286414
g  1.050559  0.216526
h  1.122680 -1.621420
```

### Example 3

```
# import the pandas library and aliasing as pd
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(8, 4),
index = ['a','b','c','d','e','f','g','h'], columns = ['A', 'B', 'C', 'D'])

# Select few rows for multiple columns, say list[]
print df.loc[['a','b','f','h'],['A','C']]
```

[Live Demo](#)

Its **output** is as follows –

	A	C
a	0.391548	0.745623
b	-0.070649	1.620406
f	0.613709	0.286414
h	1.122680	-1.621420

### Example 4

```
# import the pandas library and aliasing as pd
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(8, 4),
index = ['a','b','c','d','e','f','g','h'], columns = ['A', 'B', 'C', 'D'])

# Select range of rows for all columns
print df.loc['a':'h']
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
a	0.391548	-0.224297	0.745623	0.054301
b	-0.070649	-0.880130	1.620406	1.419743
c	-0.317212	-1.929698	1.448365	0.616899
d	-2.162406	0.614256	-0.873557	1.093958
e	2.202797	-2.315915	0.528067	0.612482
f	0.613709	-0.157674	0.286414	-0.500517
g	1.050559	-2.272099	0.216526	0.928449
h	1.122680	0.324368	-1.621420	-0.741470

## Example 5

*# import the pandas library and aliasing as pd*

**import** pandas **as** pd

**import** numpy **as** np

df = pd.**DataFrame**(np.random.randn(8, 4),

index = ['a','b','c','d','e','f','g','h'], columns = ['A', 'B', 'C', 'D'])

*# for getting values with a boolean array*

**print** df.loc['a']>0

Live Demo

Its **output** is as follows –

A False

B True

C False

D False

Name: a, dtype: bool

## .iloc()

Pandas provide various methods in order to get purely integer based indexing. Like python and numpy, these are **0-based** indexing.

The various access methods are as follows –

- An Integer
- A list of integers

## ■ A range of values

### Example 1

```
# import the pandas library and aliasing as pd
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])

# select all rows for a specific column
print df.iloc[:4]
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
0	0.699435	0.256239	-1.270702	-0.645195
1	-0.685354	0.890791	-0.813012	0.631615
2	-0.783192	-0.531378	0.025070	0.230806
3	0.539042	-1.284314	0.826977	-0.026251

### Example 2

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])

# Integer slicing
print df.iloc[:4]
print df.iloc[1:5, 2:4]
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
0	0.699435	0.256239	-1.270702	-0.645195
1	-0.685354	0.890791	-0.813012	0.631615
2	-0.783192	-0.531378	0.025070	0.230806



```
3  0.539042 -1.284314  0.826977 -0.026251
```

	C	D
1	-0.813012	0.631615
2	0.025070	0.230806
3	0.826977	-0.026251
4	1.423332	1.130568

## Example 3

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])
```

```
# Slicing through List of values
```

```
print df.iloc[[1, 3, 5], [1, 3]]
```

```
print df.iloc[1:3, :]
```

```
print df.iloc[:,1:3]
```

Its **output** is as follows –

	B	D
1	0.890791	0.631615
3	-1.284314	-0.026251
5	-0.512888	-0.518930

	A	B	C	D
1	-0.685354	0.890791	-0.813012	0.631615
2	-0.783192	-0.531378	0.025070	0.230806

	B	C
0	0.256239	-1.270702
1	0.890791	-0.813012
2	-0.531378	0.025070
3	-1.284314	0.826977
4	-0.460729	1.423332
5	-0.512888	0.581409
6	-1.204853	0.098060
7	-0.947857	0.641358

## .ix()

Besides pure label based and integer based, Pandas provides a hybrid method for selections and subsetting the object using the `.ix()` operator.

### Example 1

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])

# Integer slicing
print df.ix[:4]
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
0	0.699435	0.256239	-1.270702	-0.645195
1	-0.685354	0.890791	-0.813012	0.631615
2	-0.783192	-0.531378	0.025070	0.230806
3	0.539042	-1.284314	0.826977	-0.026251

### Example 2

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])

# Index slicing
print df.ix[:, 'A']
```

[Live Demo](#)

Its **output** is as follows –

0	0.699435
1	-0.685354
2	-0.783192
3	0.539042
4	-1.044209

```

5 -1.415411
6  1.062095
7  0.994204
Name: A, dtype: float64

```

## Use of Notations

Getting values from the Pandas object with Multi-axes indexing uses the following notation –

Object	Indexers	Return Type
Series	s.loc[indexer]	Scalar value
DataFrame	df.loc[row_index,col_index]	Series object
Panel	p.loc[item_index,major_index,minor_index]	p.loc[item_index,major_index,minor_index]

**Note – .iloc() & .ix()** applies the same indexing options and Return value.

Let us now see how each operation can be performed on the DataFrame object. We will use the basic indexing operator '[' ]' –

### Example 1

```

import pandas as pd
import numpy as np
df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])
print df['A']

```

[Live Demo](#)

Its **output** is as follows –

```

0 -0.478893
1  0.391931
2  0.336825
3 -1.055102
4 -0.165218
5 -0.328641
6  0.567721

```

```
7 -0.759399
Name: A, dtype: float64
```

**Note** – We can pass a list of values to [ ] to select those columns.

## Example 2

```
import pandas as pd
import numpy as np
df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])

print df[['A', 'B']]
```

[Live Demo](#)

Its **output** is as follows –

	A	B
0	-0.478893	-0.606311
1	0.391931	-0.949025
2	0.336825	0.093717
3	-1.055102	-0.012944
4	-0.165218	1.550310
5	-0.328641	-0.226363
6	0.567721	-0.312585
7	-0.759399	-0.372696

## Example 3

```
import pandas as pd
import numpy as np
df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])
print df[2:2]
```

[Live Demo](#)

Its **output** is as follows –

```
Columns: [A, B, C, D]
Index: []
```

## Attribute Access

Columns can be selected using the attribute operator '.'.

### Example

```
import pandas as pd
import numpy as np
df = pd.DataFrame(np.random.randn(8, 4), columns = ['A', 'B', 'C', 'D'])

print df.A
```

[Live Demo](#)

Its **output** is as follows –

```
0   -0.478893
1    0.391931
2    0.336825
3   -1.055102
4   -0.165218
5   -0.328641
6    0.567721
7   -0.759399
Name: A, dtype: float64
```

## Python Pandas - Statistical Functions

Statistical methods help in the understanding and analyzing the behavior of data. We will now learn a few statistical functions, which we can apply on Pandas objects.

### Percent\_change

Series, DataFrames and Panel, all have the function **pct\_change()**. This function compares every element with its prior element and computes the change percentage.

```
import pandas as pd
import numpy as np
s = pd.Series([1,2,3,4,5,4])
print s.pct_change()
```

[Live Demo](#)

```
df = pd.DataFrame(np.random.randn(5, 2))
print df.pct_change()
```

Its **output** is as follows –

```
0      NaN
1  1.000000
2  0.500000
3  0.333333
4  0.250000
5 -0.200000
dtype: float64

      0      1
0     NaN     NaN
1 -15.151902  0.174730
2 -0.746374 -1.449088
3 -3.582229 -3.165836
4  15.601150 -1.860434
```

By default, the **pct\_change()** operates on columns; if you want to apply the same row wise, then use **axis=1()** argument.

## Covariance

Covariance is applied on series data. The Series object has a method cov to compute covariance between series objects. NA will be excluded automatically.

## Cov Series

```
import pandas as pd
import numpy as np
s1 = pd.Series(np.random.randn(10))
s2 = pd.Series(np.random.randn(10))
print s1.cov(s2)
```

[Live Demo](#)

Its **output** is as follows –

```
-0.12978405324
```

Covariance method when applied on a DataFrame, computes **cov** between all the columns.

```
import pandas as pd
import numpy as np
frame = pd.DataFrame(np.random.randn(10, 5), columns=['a', 'b', 'c', 'd', 'e'])
print frame['a'].cov(frame['b'])
print frame.cov()
```

[Live Demo](#)

Its **output** is as follows –

```
-0.58312921152741437
```

	a	b	c	d	e
a	1.780628	-0.583129	-0.185575	0.003679	-0.136558
b	-0.583129	1.297011	0.136530	-0.523719	0.251064
c	-0.185575	0.136530	0.915227	-0.053881	-0.058926
d	0.003679	-0.523719	-0.053881	1.521426	-0.487694
e	-0.136558	0.251064	-0.058926	-0.487694	0.960761

**Note** – Observe the **cov** between **a** and **b** column in the first statement and the same is the value returned by cov on DataFrame.

## Correlation

Correlation shows the linear relationship between any two array of values (series). There are multiple methods to compute the correlation like pearson(default), spearman and kendall.

```
import pandas as pd
import numpy as np
frame = pd.DataFrame(np.random.randn(10, 5), columns=['a', 'b', 'c', 'd', 'e'])

print frame['a'].corr(frame['b'])
print frame.corr()
```

[Live Demo](#)

Its **output** is as follows –

-0.383712785514

	a	b	c	d	e
a	1.000000	-0.383713	-0.145368	0.002235	-0.104405
b	-0.383713	1.000000	0.125311	-0.372821	0.224908
c	-0.145368	0.125311	1.000000	-0.045661	-0.062840
d	0.002235	-0.372821	-0.045661	1.000000	-0.403380
e	-0.104405	0.224908	-0.062840	-0.403380	1.000000

If any non-numeric column is present in the DataFrame, it is excluded automatically.

## Data Ranking

Data Ranking produces ranking for each element in the array of elements. In case of ties, assigns the mean rank.

```
import pandas as pd
import numpy as np

s = pd.Series(np.random.randn(5), index=list('abcde'))
s['d'] = s['b'] # so there's a tie
print s.rank()
```

[Live Demo](#)

Its **output** is as follows –

```
a 1.0
b 3.5
c 2.0
d 3.5
e 5.0
dtype: float64
```

Rank optionally takes a parameter `ascending` which by default is `true`; when `false`, data is reverse-ranked, with larger values assigned a smaller rank.

Rank supports different tie-breaking methods, specified with the `method` parameter –

- **average** – average rank of tied group
- **min** – lowest rank in the group
- **max** – highest rank in the group



- **first** – ranks assigned in the order they appear in the array

## Python Pandas - Window Functions

For working on numerical data, Pandas provide few variants like rolling, expanding and exponentially moving weights for window statistics. Among these are **sum, mean, median, variance, covariance, correlation**, etc.

We will now learn how each of these can be applied on DataFrame objects.

### .rolling() Function

This function can be applied on a series of data. Specify the **window=n** argument and apply the appropriate statistical function on top of it.

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
                  columns = ['A', 'B', 'C', 'D'])
print df.rolling(window=3).mean()
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
2000-01-01	NaN	NaN	NaN	NaN
2000-01-02	NaN	NaN	NaN	NaN
2000-01-03	0.434553	-0.667940	-1.051718	-0.826452
2000-01-04	0.628267	-0.047040	-0.287467	-0.161110
2000-01-05	0.398233	0.003517	0.099126	-0.405565
2000-01-06	0.641798	0.656184	-0.322728	0.428015
2000-01-07	0.188403	0.010913	-0.708645	0.160932
2000-01-08	0.188043	-0.253039	-0.818125	-0.108485
2000-01-09	0.682819	-0.606846	-0.178411	-0.404127
2000-01-10	0.688583	0.127786	0.513832	-1.067156

**Note** – Since the window size is 3, for first two elements there are nulls and from third the value will be the average of the **n**, **n-1** and **n-2** elements. Thus we can also apply various functions as mentioned above.

## .expanding() Function

This function can be applied on a series of data. Specify the **min\_periods=n** argument and apply the appropriate statistical function on top of it.

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
                  columns = ['A', 'B', 'C', 'D'])
print df.expanding(min_periods=3).mean()
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D	
2000-01-01	NaN	NaN	NaN	NaN	NaN
2000-01-02	NaN	NaN	NaN	NaN	NaN
2000-01-03	0.434553	-0.667940	-1.051718	-0.826452	
2000-01-04	0.743328	-0.198015	-0.852462	-0.262547	
2000-01-05	0.614776	-0.205649	-0.583641	-0.303254	
2000-01-06	0.538175	-0.005878	-0.687223	-0.199219	
2000-01-07	0.505503	-0.108475	-0.790826	-0.081056	
2000-01-08	0.454751	-0.223420	-0.671572	-0.230215	
2000-01-09	0.586390	-0.206201	-0.517619	-0.267521	
2000-01-10	0.560427	-0.037597	-0.399429	-0.376886	

## .ewm() Function

**ewm** is applied on a series of data. Specify any of the com, span, **halflife** argument and apply the appropriate statistical function on top of it. It assigns the weights exponentially.

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
```

[Live Demo](#)

```
columns = ['A', 'B', 'C', 'D'])
print df.ewm(com=0.5).mean()
```

Its **output** is as follows –

	A	B	C	D
2000-01-01	1.088512	-0.650942	-2.547450	-0.566858
2000-01-02	0.865131	-0.453626	-1.137961	0.058747
2000-01-03	-0.132245	-0.807671	-0.308308	-1.491002
2000-01-04	1.084036	0.555444	-0.272119	0.480111
2000-01-05	0.425682	0.025511	0.239162	-0.153290
2000-01-06	0.245094	0.671373	-0.725025	0.163310
2000-01-07	0.288030	-0.259337	-1.183515	0.473191
2000-01-08	0.162317	-0.771884	-0.285564	-0.692001
2000-01-09	1.147156	-0.302900	0.380851	-0.607976
2000-01-10	0.600216	0.885614	0.569808	-1.110113

Window functions are majorly used in finding the trends within the data graphically by smoothing the curve. If there is lot of variation in the everyday data and a lot of data points are available, then taking the samples and plotting is one method and applying the window computations and plotting the graph on the results is another method. By these methods, we can smooth the curve or the trend.

## Python Pandas - Aggregations

Once the rolling, expanding and **ewm** objects are created, several methods are available to perform aggregations on data.

### Applying Aggregations on DataFrame

Let us create a DataFrame and apply aggregations on it.

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
                  columns = ['A', 'B', 'C', 'D'])

print df
```

[Live Demo](#)

```
r = df.rolling(window=3,min_periods=1)
print r
```

Its **output** is as follows –

	A	B	C	D
2000-01-01	1.088512	-0.650942	-2.547450	-0.566858
2000-01-02	0.790670	-0.387854	-0.668132	0.267283
2000-01-03	-0.575523	-0.965025	0.060427	-2.179780
2000-01-04	1.669653	1.211759	-0.254695	1.429166
2000-01-05	0.100568	-0.236184	0.491646	-0.466081
2000-01-06	0.155172	0.992975	-1.205134	0.320958
2000-01-07	0.309468	-0.724053	-1.412446	0.627919
2000-01-08	0.099489	-1.028040	0.163206	-1.274331
2000-01-09	1.639500	-0.068443	0.714008	-0.565969
2000-01-10	0.326761	1.479841	0.664282	-1.361169

Rolling [window=3,min\_periods=1,center=False,axis=0]

We can aggregate by passing a function to the entire DataFrame, or select a column via the standard **get item** method.

## Apply Aggregation on a Whole Dataframe

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
                  columns = ['A', 'B', 'C', 'D'])
print df
r = df.rolling(window=3,min_periods=1)
print r.aggregate(np.sum)
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
2000-01-01	1.088512	-0.650942	-2.547450	-0.566858
2000-01-02	1.879182	-1.038796	-3.215581	-0.299575
2000-01-03	1.303660	-2.003821	-3.155154	-2.479355
2000-01-04	1.884801	-0.141119	-0.862400	-0.483331

2000-01-05	1.194699	0.010551	0.297378	-1.216695
2000-01-06	1.925393	1.968551	-0.968183	1.284044
2000-01-07	0.565208	0.032738	-2.125934	0.482797
2000-01-08	0.564129	-0.759118	-2.454374	-0.325454
2000-01-09	2.048458	-1.820537	-0.535232	-1.212381
2000-01-10	2.065750	0.383357	1.541496	-3.201469

	A	B	C	D
2000-01-01	1.088512	-0.650942	-2.547450	-0.566858
2000-01-02	1.879182	-1.038796	-3.215581	-0.299575
2000-01-03	1.303660	-2.003821	-3.155154	-2.479355
2000-01-04	1.884801	-0.141119	-0.862400	-0.483331
2000-01-05	1.194699	0.010551	0.297378	-1.216695
2000-01-06	1.925393	1.968551	-0.968183	1.284044
2000-01-07	0.565208	0.032738	-2.125934	0.482797
2000-01-08	0.564129	-0.759118	-2.454374	-0.325454
2000-01-09	2.048458	-1.820537	-0.535232	-1.212381
2000-01-10	2.065750	0.383357	1.541496	-3.201469

## Apply Aggregation on a Single Column of a Dataframe

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
                  columns = ['A', 'B', 'C', 'D'])
print df
r = df.rolling(window=3,min_periods=1)
print r['A'].aggregate(np.sum)
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
2000-01-01	1.088512	-0.650942	-2.547450	-0.566858
2000-01-02	1.879182	-1.038796	-3.215581	-0.299575
2000-01-03	1.303660	-2.003821	-3.155154	-2.479355
2000-01-04	1.884801	-0.141119	-0.862400	-0.483331
2000-01-05	1.194699	0.010551	0.297378	-1.216695
2000-01-06	1.925393	1.968551	-0.968183	1.284044

```

2000-01-07    0.565208    0.032738   -2.125934    0.482797
2000-01-08    0.564129   -0.759118   -2.454374   -0.325454
2000-01-09    2.048458   -1.820537   -0.535232   -1.212381
2000-01-10    2.065750    0.383357    1.541496   -3.201469
2000-01-01    1.088512
2000-01-02    1.879182
2000-01-03    1.303660
2000-01-04    1.884801
2000-01-05    1.194699
2000-01-06    1.925393
2000-01-07    0.565208
2000-01-08    0.564129
2000-01-09    2.048458
2000-01-10    2.065750
Freq: D, Name: A, dtype: float64

```

## Apply Aggregation on Multiple Columns of a DataFrame

```

import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
                  columns = ['A', 'B', 'C', 'D'])
print df
r = df.rolling(window=3,min_periods=1)
print r[['A','B']].aggregate(np.sum)

```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
2000-01-01	1.088512	-0.650942	-2.547450	-0.566858
2000-01-02	1.879182	-1.038796	-3.215581	-0.299575
2000-01-03	1.303660	-2.003821	-3.155154	-2.479355
2000-01-04	1.884801	-0.141119	-0.862400	-0.483331
2000-01-05	1.194699	0.010551	0.297378	-1.216695
2000-01-06	1.925393	1.968551	-0.968183	1.284044
2000-01-07	0.565208	0.032738	-2.125934	0.482797
2000-01-08	0.564129	-0.759118	-2.454374	-0.325454
2000-01-09	2.048458	-1.820537	-0.535232	-1.212381

2000-01-10	2.065750	0.383357	1.541496	-3.201469
	A	B		
2000-01-01	1.088512	-0.650942		
2000-01-02	1.879182	-1.038796		
2000-01-03	1.303660	-2.003821		
2000-01-04	1.884801	-0.141119		
2000-01-05	1.194699	0.010551		
2000-01-06	1.925393	1.968551		
2000-01-07	0.565208	0.032738		
2000-01-08	0.564129	-0.759118		
2000-01-09	2.048458	-1.820537		
2000-01-10	2.065750	0.383357		

## Apply Multiple Functions on a Single Column of a DataFrame

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
                  columns = ['A', 'B', 'C', 'D'])
print df
r = df.rolling(window=3,min_periods=1)
print r['A'].aggregate([np.sum,np.mean])
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D	
2000-01-01	1.088512	-0.650942	-2.547450	-0.566858	
2000-01-02	1.879182	-1.038796	-3.215581	-0.299575	
2000-01-03	1.303660	-2.003821	-3.155154	-2.479355	
2000-01-04	1.884801	-0.141119	-0.862400	-0.483331	
2000-01-05	1.194699	0.010551	0.297378	-1.216695	
2000-01-06	1.925393	1.968551	-0.968183	1.284044	
2000-01-07	0.565208	0.032738	-2.125934	0.482797	
2000-01-08	0.564129	-0.759118	-2.454374	-0.325454	
2000-01-09	2.048458	-1.820537	-0.535232	-1.212381	
2000-01-10	2.065750	0.383357	1.541496	-3.201469	
	sum	mean			
2000-01-01	1.088512	1.088512			

```

2000-01-02  1.879182  0.939591
2000-01-03  1.303660  0.434553
2000-01-04  1.884801  0.628267
2000-01-05  1.194699  0.398233
2000-01-06  1.925393  0.641798
2000-01-07  0.565208  0.188403
2000-01-08  0.564129  0.188043
2000-01-09  2.048458  0.682819
2000-01-10  2.065750  0.688583

```

## Apply Multiple Functions on Multiple Columns of a DataFrame

```

import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10, 4),
                  index = pd.date_range('1/1/2000', periods=10),
                  columns = ['A', 'B', 'C', 'D'])
print df
r = df.rolling(window=3,min_periods=1)
print r[['A','B']].aggregate([np.sum,np.mean])

```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D	
2000-01-01	1.088512	-0.650942	-2.547450	-0.566858	
2000-01-02	1.879182	-1.038796	-3.215581	-0.299575	
2000-01-03	1.303660	-2.003821	-3.155154	-2.479355	
2000-01-04	1.884801	-0.141119	-0.862400	-0.483331	
2000-01-05	1.194699	0.010551	0.297378	-1.216695	
2000-01-06	1.925393	1.968551	-0.968183	1.284044	
2000-01-07	0.565208	0.032738	-2.125934	0.482797	
2000-01-08	0.564129	-0.759118	-2.454374	-0.325454	
2000-01-09	2.048458	-1.820537	-0.535232	-1.212381	
2000-01-10	2.065750	0.383357	1.541496	-3.201469	
	A	B			
	sum	mean	sum	mean	
2000-01-01	1.088512	1.088512	-0.650942	-0.650942	
2000-01-02	1.879182	0.939591	-1.038796	-0.519398	
2000-01-03	1.303660	0.434553	-2.003821	-0.667940	



2000-01-04	1.884801	0.628267	-0.141119	-0.047040
2000-01-05	1.194699	0.398233	0.010551	0.003517
2000-01-06	1.925393	0.641798	1.968551	0.656184
2000-01-07	0.565208	0.188403	0.032738	0.010913
2000-01-08	0.564129	0.188043	-0.759118	-0.253039
2000-01-09	2.048458	0.682819	-1.820537	-0.606846
2000-01-10	2.065750	0.688583	0.383357	0.127786

## Apply Different Functions to Different Columns of a Dataframe

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(3, 4),
                  index = pd.date_range('1/1/2000', periods=3),
                  columns = ['A', 'B', 'C', 'D'])
print df
r = df.rolling(window=3,min_periods=1)
print r.aggregate({'A' : np.sum, 'B' : np.mean})
```

[Live Demo](#)

Its **output** is as follows –

	A	B	C	D
2000-01-01	-1.575749	-1.018105	0.317797	0.545081
2000-01-02	-0.164917	-1.361068	0.258240	1.113091
2000-01-03	1.258111	1.037941	-0.047487	0.867371

	A	B
2000-01-01	-1.575749	-1.018105
2000-01-02	-1.740666	-1.189587
2000-01-03	-0.482555	-0.447078

## Python Pandas - Missing Data

Missing data is always a problem in real life scenarios. Areas like machine learning and data mining face severe issues in the accuracy of their model predictions because of poor quality of data caused by missing values. In these areas, missing value treatment is a major point of focus to make their models more accurate and valid.

### When and Why Is Data Missed?

Let us consider an online survey for a product. Many a times, people do not share all the information related to them. Few people share their experience, but not how long they are using the product; few people share how long they are using the product, their experience but not their contact information. Thus, in some or the other way a part of data is always missing, and this is very common in real time.

Let us now see how we can handle missing values (say NA or NaN) using Pandas.

```
# import the pandas library
```

```
import pandas as pd
```

```
import numpy as np
```

```
df = pd.DataFrame(np.random.randn(5, 3), index=['a', 'c', 'e', 'f',  
'h'], columns=['one', 'two', 'three'])
```

```
df = df.reindex(['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h'])
```

```
print df
```

[Live Demo](#)

Its **output** is as follows –

	one	two	three
a	0.077988	0.476149	0.965836
b	NaN	NaN	NaN
c	-0.390208	-0.551605	-2.301950
d	NaN	NaN	NaN
e	-2.000303	-0.788201	1.510072
f	-0.930230	-0.670473	1.146615
g	NaN	NaN	NaN
h	0.085100	0.532791	0.887415

Using reindexing, we have created a DataFrame with missing values. In the output, **NaN** means **Not a Number**.

## Check for Missing Values

To make detecting missing values easier (and across different array dtypes), Pandas provides the **isnull()** and **notnull()** functions, which are also methods on Series and DataFrame objects –

### Example 1

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5, 3), index=['a', 'c', 'e', 'f',
'h'], columns=['one', 'two', 'three'])

df = df.reindex(['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h'])

print df['one'].isnull()
```

[Live Demo](#)

Its **output** is as follows –

```
a  False
b   True
c  False
d   True
e  False
f  False
g   True
h  False
Name: one, dtype: bool
```

## Example 2

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5, 3), index=['a', 'c', 'e', 'f',
'h'], columns=['one', 'two', 'three'])

df = df.reindex(['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h'])

print df['one'].notnull()
```

[Live Demo](#)

Its **output** is as follows –

```
a  True
b  False
c  True
```

```
d False
e True
f True
g False
h True
Name: one, dtype: bool
```

## Calculations with Missing Data

- When summing data, NA will be treated as Zero
- If the data are all NA, then the result will be NA

### Example 1

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5, 3), index=['a', 'c', 'e', 'f',
'h'], columns=['one', 'two', 'three'])

df = df.reindex(['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h'])

print df['one'].sum()
```

[Live Demo](#)

Its **output** is as follows –

```
2.02357685917
```

### Example 2

```
import pandas as pd
import numpy as np

df = pd.DataFrame(index=[0,1,2,3,4,5], columns=['one', 'two'])

print df['one'].sum()
```

[Live Demo](#)

Its **output** is as follows –

nan

## Cleaning / Filling Missing Data

Pandas provides various methods for cleaning the missing values. The `fillna` function can "fill in" NA values with non-null data in a couple of ways, which we have illustrated in the following sections.

### Replace NaN with a Scalar Value

The following program shows how you can replace "NaN" with "0".

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(3, 3), index=['a', 'c', 'e'], columns=['one',
'two', 'three'])

df = df.reindex(['a', 'b', 'c'])

print df
print ("NaN replaced with '0':")
print df.fillna(0)
```

[Live Demo](#)

Its **output** is as follows –

```
      one    two  three
a -0.576991 -0.741695  0.553172
b      NaN     NaN    NaN
c  0.744328 -1.735166  1.749580
```

NaN replaced with '0':

```
      one    two  three
a -0.576991 -0.741695  0.553172
b  0.000000  0.000000  0.000000
c  0.744328 -1.735166  1.749580
```

Here, we are filling with value zero; instead we can also fill with any other value.

### Fill NA Forward and Backward

Using the concepts of filling discussed in the ReIndexing Chapter we will fill the missing values.

Sr.No	Method & Action
1	<b>pad/fill</b> Fill methods Forward
2	<b>bfill/backfill</b> Fill methods Backward

## Example 1

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5, 3), index=['a', 'c', 'e', 'f',
'h'], columns=['one', 'two', 'three'])

df = df.reindex(['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h'])

print df.fillna(method='pad')
```

[Live Demo](#)

Its **output** is as follows –

```
   one    two    three
a  0.077988  0.476149  0.965836
b  0.077988  0.476149  0.965836
c -0.390208 -0.551605 -2.301950
d -0.390208 -0.551605 -2.301950
e -2.000303 -0.788201  1.510072
f -0.930230 -0.670473  1.146615
g -0.930230 -0.670473  1.146615
h  0.085100  0.532791  0.887415
```

## Example 2

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
df = pd.DataFrame(np.random.randn(5, 3), index=['a', 'c', 'e', 'f',
'h'], columns=['one', 'two', 'three'])

df = df.reindex(['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h'])

print df.fillna(method='backfill')
```

Its **output** is as follows –

	one	two	three
a	0.077988	0.476149	0.965836
b	-0.390208	-0.551605	-2.301950
c	-0.390208	-0.551605	-2.301950
d	-2.000303	-0.788201	1.510072
e	-2.000303	-0.788201	1.510072
f	-0.930230	-0.670473	1.146615
g	0.085100	0.532791	0.887415
h	0.085100	0.532791	0.887415

## Drop Missing Values

If you want to simply exclude the missing values, then use the **dropna** function along with the **axis** argument. By default, axis=0, i.e., along row, which means that if any value within a row is NA then the whole row is excluded.

### Example 1

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5, 3), index=['a', 'c', 'e', 'f',
'h'], columns=['one', 'two', 'three'])

df = df.reindex(['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h'])
print df.dropna()
```

[Live Demo](#)

Its **output** is as follows –

	one	two	three
a	0.077988	0.476149	0.965836
c	-0.390208	-0.551605	-2.301950

```
e -2.000303 -0.788201 1.510072
f -0.930230 -0.670473 1.146615
h 0.085100 0.532791 0.887415
```

## Example 2

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(5, 3), index=['a', 'c', 'e', 'f',
'h'], columns=['one', 'two', 'three'])

df = df.reindex(['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h'])
print df.dropna(axis=1)
```

[Live Demo](#)

Its **output** is as follows –

```
Empty DataFrame
Columns: [ ]
Index: [a, b, c, d, e, f, g, h]
```

## Replace Missing (or) Generic Values

Many times, we have to replace a generic value with some specific value. We can achieve this by applying the replace method.

Replacing NA with a scalar value is equivalent behavior of the **fillna()** function.

## Example 1

```
import pandas as pd
import numpy as np

df = pd.DataFrame({'one':[10,20,30,40,50,2000], 'two':[1000,0,30,40,50,60]})

print df.replace({1000:10,2000:60})
```

[Live Demo](#)

Its **output** is as follows –



```

    one two
0   10  10
1   20   0
2   30  30
3   40  40
4   50  50
5   60  60

```

## Example 2

```

import pandas as pd
import numpy as np

```

[Live Demo](#)

```

df = pd.DataFrame({'one':[10,20,30,40,50,2000], 'two':[1000,0,30,40,50,60]})
print df.replace({1000:10,2000:60})

```

Its **output** is as follows –

```

    one two
0   10  10
1   20   0
2   30  30
3   40  40
4   50  50
5   60  60

```

# Python Pandas - GroupBy

Any **groupby** operation involves one of the following operations on the original object. They are –

- **Splitting** the Object
- **Applying** a function
- **Combining** the results

In many situations, we split the data into sets and we apply some functionality on each subset. In the apply functionality, we can perform the following operations –

- **Aggregation** – computing a summary statistic
- **Transformation** – perform some group-specific operation
- **Filtration** – discarding the data with some condition

Let us now create a DataFrame object and perform all the operations on it –

```
#import the pandas library
```

```
import pandas as pd
```

[Live Demo](#)

```
ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
            'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
            'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}
df = pd.DataFrame(ipl_data)
```

```
print df
```

Its **output** is as follows –

	Points	Rank	Team	Year
0	876	1	Riders	2014
1	789	2	Riders	2015
2	863	2	Devils	2014
3	673	3	Devils	2015
4	741	3	Kings	2014
5	812	4	kings	2015
6	756	1	Kings	2016
7	788	1	Kings	2017
8	694	2	Riders	2016
9	701	4	Royals	2014
10	804	1	Royals	2015
11	690	2	Riders	2017

## Split Data into Groups

Pandas object can be split into any of their objects. There are multiple ways to split an object like –

- `obj.groupby('key')`

- `obj.groupby(['key1','key2'])`
- `obj.groupby(key,axis=1)`

Let us now see how the grouping objects can be applied to the DataFrame object

## Example

*# import the pandas library*

`import pandas as pd`

Live Demo

```
ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3,4 ,1 ,1,2 , 4,1,2],
            'Year': [2014,2015,2014,2015,2014,2015,2016,2017,2016,2014,2015,2017],
            'Points':[876,789,863,673,741,812,756,788,694,701,804,690]}
```

`df = pd.DataFrame(ipl_data)`

`print df.groupby('Team')`

Its **output** is as follows –

```
<pandas.core.groupby.DataFrameGroupBy object at 0x7fa46a977e50>
```

## View Groups

*# import the pandas library*

`import pandas as pd`

Live Demo

```
ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3,4 ,1 ,1,2 , 4,1,2],
            'Year': [2014,2015,2014,2015,2014,2015,2016,2017,2016,2014,2015,2017],
            'Points':[876,789,863,673,741,812,756,788,694,701,804,690]}
```

`df = pd.DataFrame(ipl_data)`

`print df.groupby('Team').groups`

Its **output** is as follows –

```
{'Kings': Int64Index([4, 6, 7],      dtype='int64'),
'Devils': Int64Index([2, 3],        dtype='int64'),
'Riders': Int64Index([0, 1, 8, 11], dtype='int64'),
'Royals': Int64Index([9, 10],       dtype='int64'),
'kings' : Int64Index([5],           dtype='int64')}
```

## Example

**Group by** with multiple columns –

```
# import the pandas library
import pandas as pd
```

[Live Demo](#)

```
ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
            'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
            'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}
df = pd.DataFrame(ipl_data)

print df.groupby(['Team', 'Year']).groups
```

Its **output** is as follows –

```
{('Kings', 2014): Int64Index([4], dtype='int64'),
 ('Royals', 2014): Int64Index([9], dtype='int64'),
 ('Riders', 2014): Int64Index([0], dtype='int64'),
 ('Riders', 2015): Int64Index([1], dtype='int64'),
 ('Kings', 2016): Int64Index([6], dtype='int64'),
 ('Riders', 2016): Int64Index([8], dtype='int64'),
 ('Riders', 2017): Int64Index([11], dtype='int64'),
 ('Devils', 2014): Int64Index([2], dtype='int64'),
 ('Devils', 2015): Int64Index([3], dtype='int64'),
 ('kings', 2015): Int64Index([5], dtype='int64'),
 ('Royals', 2015): Int64Index([10], dtype='int64'),
 ('Kings', 2017): Int64Index([7], dtype='int64')}
```

## Iterating through Groups

With the **groupby** object in hand, we can iterate through the object similar to `itertools.obj`.

```
# import the pandas library
```

```
import pandas as pd
```

[Live Demo](#)

```
ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
            'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
            'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}
```

```
df = pd.DataFrame(ipl_data)
```

```
grouped = df.groupby('Year')
```

```
for name, group in grouped:
```

```
    print name
```

```
    print group
```

Its **output** is as follows –

2014

	Points	Rank	Team	Year
0	876	1	Riders	2014
2	863	2	Devils	2014
4	741	3	Kings	2014
9	701	4	Royals	2014

2015

	Points	Rank	Team	Year
1	789	2	Riders	2015
3	673	3	Devils	2015
5	812	4	kings	2015
10	804	1	Royals	2015

2016

	Points	Rank	Team	Year
6	756	1	Kings	2016
8	694	2	Riders	2016

2017

	Points	Rank	Team	Year
--	--------	------	------	------

```
7   788   1   Kings   2017
11  690   2   Riders   2017
```

By default, the **groupby** object has the same label name as the group name.

## Select a Group

Using the **get\_group()** method, we can select a single group.

```
# import the pandas library
```

```
import pandas as pd
```

[Live Demo](#)

```
ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
            'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
            'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}
```

```
df = pd.DataFrame(ipl_data)
```

```
grouped = df.groupby('Year')
```

```
print grouped.get_group(2014)
```

Its **output** is as follows –

	Points	Rank	Team	Year
0	876	1	Riders	2014
2	863	2	Devils	2014
4	741	3	Kings	2014
9	701	4	Royals	2014

## Aggregations

An aggregated function returns a single aggregated value for each group. Once the **group by** object is created, several aggregation operations can be performed on the grouped data.

An obvious one is aggregation via the aggregate or equivalent **agg** method –

```
# import the pandas library
```

```
import pandas as pd
```

```
import numpy as np
```

[Live Demo](#)

```
ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
            'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
            'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}
df = pd.DataFrame(ipl_data)

grouped = df.groupby('Year')
print grouped['Points'].agg(np.mean)
```

Its **output** is as follows –

```
Year
2014    795.25
2015    769.50
2016    725.00
2017    739.00
Name: Points, dtype: float64
```

Another way to see the size of each group is by applying the size() function –

```
import pandas as pd
import numpy as np

ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
            'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
            'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}
df = pd.DataFrame(ipl_data)

Attribute Access in Python Pandas
grouped = df.groupby('Team')
print grouped.agg(np.size)
```

[Live Demo](#)

Its **output** is as follows –

	Points	Rank	Year
Team			
Devils	2	2	2

Kings	3	3	3
Riders	4	4	4
Royals	2	2	2
kings	1	1	1

## Applying Multiple Aggregation Functions at Once

With grouped Series, you can also pass a **list** or **dict of functions** to do aggregation with, and generate DataFrame as output –

```
# import the pandas library
```

```
import pandas as pd
```

```
import numpy as np
```

```
ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
            'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
            'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}
```

```
df = pd.DataFrame(ipl_data)
```

```
grouped = df.groupby('Team')
```

```
print grouped['Points'].agg([np.sum, np.mean, np.std])
```

[Live Demo](#)

Its **output** is as follows –

Team	sum	mean	std
Devils	1536	768.000000	134.350288
Kings	2285	761.666667	24.006943
Riders	3049	762.250000	88.567771
Royals	1505	752.500000	72.831998
kings	812	812.000000	NaN

## Transformations

Transformation on a group or a column returns an object that is indexed the same size of that is being grouped. Thus, the transform should return a result that is the same size as that of a group chunk.

[Live Demo](#)



```
# import the pandas library
import pandas as pd
import numpy as np

ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
            'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
            'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
            'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}

df = pd.DataFrame(ipl_data)

grouped = df.groupby('Team')
score = lambda x: (x - x.mean()) / x.std()*10
print grouped.transform(score)
```

Its **output** is as follows –

	Points	Rank	Year
0	12.843272	-15.000000	-11.618950
1	3.020286	5.000000	-3.872983
2	7.071068	-7.071068	-7.071068
3	-7.071068	7.071068	7.071068
4	-8.608621	11.547005	-10.910895
5	NaN	NaN	NaN
6	-2.360428	-5.773503	2.182179
7	10.969049	-5.773503	8.728716
8	-7.705963	5.000000	3.872983
9	-7.071068	7.071068	-7.071068
10	7.071068	-7.071068	7.071068
11	-8.157595	5.000000	11.618950

## Filtration

Filtration filters the data on a defined criteria and returns the subset of data. The **filter()** function is used to filter the data.

```
import pandas as pd
import numpy as np

ipl_data = {'Team': ['Riders', 'Riders', 'Devils', 'Devils', 'Kings',
                    'kings', 'Kings', 'Kings', 'Riders', 'Royals', 'Royals', 'Riders'],
```

Live Demo

```
'Rank': [1, 2, 2, 3, 3, 4, 1, 1, 2, 4, 1, 2],
'Year': [2014, 2015, 2014, 2015, 2014, 2015, 2016, 2017, 2016, 2014, 2015, 2017],
'Points': [876, 789, 863, 673, 741, 812, 756, 788, 694, 701, 804, 690]}
df = pd.DataFrame(ipl_data)

print df.groupby('Team').filter(lambda x: len(x) >= 3)
```

Its **output** is as follows –

	Points	Rank	Team	Year
0	876	1	Riders	2014
1	789	2	Riders	2015
4	741	3	Kings	2014
6	756	1	Kings	2016
7	788	1	Kings	2017
8	694	2	Riders	2016
11	690	2	Riders	2017

In the above filter condition, we are asking to return the teams which have participated three or more times in IPL.

## Python Pandas - Merging/Joining

Pandas has full-featured, high performance in-memory join operations idiomatically very similar to relational databases like SQL.

Pandas provides a single function, **merge**, as the entry point for all standard database join operations between DataFrame objects –

```
pd.merge(left, right, how='inner', on=None, left_on=None, right_on=None,
left_index=False, right_index=False, sort=True)
```

Here, we have used the following parameters –

- **left** – A DataFrame object.
- **right** – Another DataFrame object.
- **on** – Columns (names) to join on. Must be found in both the left and right DataFrame objects.
- **left\_on** – Columns from the left DataFrame to use as keys. Can either be column names or arrays with length equal to the length of the DataFrame.

- **right\_on** – Columns from the right DataFrame to use as keys. Can either be column names or arrays with length equal to the length of the DataFrame.
- **left\_index** – If **True**, use the index (row labels) from the left DataFrame as its join key(s). In case of a DataFrame with a MultiIndex (hierarchical), the number of levels must match the number of join keys from the right DataFrame.
- **right\_index** – Same usage as **left\_index** for the right DataFrame.
- **how** – One of 'left', 'right', 'outer', 'inner'. Defaults to inner. Each method has been described below.
- **sort** – Sort the result DataFrame by the join keys in lexicographical order. Defaults to True, setting to False will improve the performance substantially in many cases.

Let us now create two different DataFrames and perform the merging operations on it.

```
# import the pandas library
import pandas as pd
left = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id':['sub1','sub2','sub4','sub6','sub5']})
right = pd.DataFrame(
    {'id':[1,2,3,4,5],
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id':['sub2','sub4','sub3','sub6','sub5']})
print left
print right
```

[Live Demo](#)

Its **output** is as follows –

	Name	id	subject_id
0	Alex	1	sub1
1	Amy	2	sub2
2	Allen	3	sub4
3	Alice	4	sub6
4	Ayoung	5	sub5

	Name	id	subject_id
0	Billy	1	sub2
1	Brian	2	sub4
2	Bran	3	sub3

```
3 Bryce 4      sub6
4 Betty 5      sub5
```

## Merge Two DataFrames on a Key

```
import pandas as pd
left = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id':['sub1','sub2','sub4','sub6','sub5']})
right = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id':['sub2','sub4','sub3','sub6','sub5']})
print pd.merge(left,right,on='id')
```

[Live Demo](#)

Its **output** is as follows –

	Name_x	id	subject_id_x	Name_y	subject_id_y
0	Alex	1	sub1	Billy	sub2
1	Amy	2	sub2	Brian	sub4
2	Allen	3	sub4	Bran	sub3
3	Alice	4	sub6	Bryce	sub6
4	Ayoung	5	sub5	Betty	sub5

## Merge Two DataFrames on Multiple Keys

```
import pandas as pd
left = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id':['sub1','sub2','sub4','sub6','sub5']})
right = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id':['sub2','sub4','sub3','sub6','sub5']})
print pd.merge(left,right,on=['id','subject_id'])
```

[Live Demo](#)

Its **output** is as follows –

	Name_x	id	subject_id	Name_y
0	Alice	4	sub6	Bryce
1	Ayoung	5	sub5	Betty

## Merge Using 'how' Argument

The **how** argument to merge specifies how to determine which keys are to be included in the resulting table. If a key combination does not appear in either the left or the right tables, the values in the joined table will be NA.

Here is a summary of the **how** options and their SQL equivalent names –

Merge Method	SQL Equivalent	Description
left	LEFT OUTER JOIN	Use keys from left object
right	RIGHT OUTER JOIN	Use keys from right object
outer	FULL OUTER JOIN	Use union of keys
inner	INNER JOIN	Use intersection of keys

## Left Join

```
import pandas as pd
left = pd.DataFrame({
    'id': [1, 2, 3, 4, 5],
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id': ['sub1', 'sub2', 'sub4', 'sub6', 'sub5']})
right = pd.DataFrame({
    'id': [1, 2, 3, 4, 5],
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id': ['sub2', 'sub4', 'sub3', 'sub6', 'sub5']})
print pd.merge(left, right, on='subject_id', how='left')
```

[Live Demo](#)

Its **output** is as follows –

	Name_x	id_x	subject_id	Name_y	id_y
0	Alex	1	sub1	NaN	NaN
1	Amy	2	sub2	Billy	1.0
2	Allen	3	sub4	Brian	2.0

```
3  Alice    4      sub6  Bryce  4.0
4  Ayoungh  5      sub5   Betty  5.0
```

## Right Join

```
import pandas as pd
left = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id':['sub1','sub2','sub4','sub6','sub5']})
right = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id':['sub2','sub4','sub3','sub6','sub5']})
print pd.merge(left, right, on='subject_id', how='right')
```

[Live Demo](#)

Its **output** is as follows –

	Name_x	id_x	subject_id	Name_y	id_y
0	Amy	2.0	sub2	Billy	1
1	Allen	3.0	sub4	Brian	2
2	Alice	4.0	sub6	Bryce	4
3	Ayoung	5.0	sub5	Betty	5
4	NaN	NaN	sub3	Bran	3

## Outer Join

```
import pandas as pd
left = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id':['sub1','sub2','sub4','sub6','sub5']})
right = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id':['sub2','sub4','sub3','sub6','sub5']})
print pd.merge(left, right, how='outer', on='subject_id')
```

[Live Demo](#)

Its **output** is as follows –

	Name_x	id_x	subject_id	Name_y	id_y
0	Alex	1.0	sub1	NaN	NaN
1	Amy	2.0	sub2	Billy	1.0
2	Allen	3.0	sub4	Brian	2.0
3	Alice	4.0	sub6	Bryce	4.0
4	Ayoung	5.0	sub5	Betty	5.0
5	NaN	NaN	sub3	Bran	3.0

## Inner Join

Joining will be performed on index. Join operation honors the object on which it is called. So, **a.join(b)** is not equal to **b.join(a)**.

```
import pandas as pd
left = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id':['sub1','sub2','sub4','sub6','sub5']})
right = pd.DataFrame({
    'id':[1,2,3,4,5],
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id':['sub2','sub4','sub3','sub6','sub5']})
print pd.merge(left, right, on='subject_id', how='inner')
```

[Live Demo](#)

Its **output** is as follows –

	Name_x	id_x	subject_id	Name_y	id_y
0	Amy	2	sub2	Billy	1
1	Allen	3	sub4	Brian	2
2	Alice	4	sub6	Bryce	4
3	Ayoung	5	sub5	Betty	5

## Python Pandas - Concatenation

Pandas provides various facilities for easily combining together **Series**, **DataFrame**, and **Panel** objects.

```
pd.concat(objs,axis=0,join='outer',join_axes=None,
ignore_index=False)
```

- **objs** – This is a sequence or mapping of Series, DataFrame, or Panel objects.
- **axis** – {0, 1, ...}, default 0. This is the axis to concatenate along.
- **join** – {'inner', 'outer'}, default 'outer'. How to handle indexes on other axis(es). Outer for union and inner for intersection.
- **ignore\_index** – boolean, default False. If True, do not use the index values on the concatenation axis. The resulting axis will be labeled 0, ..., n - 1.
- **join\_axes** – This is the list of Index objects. Specific indexes to use for the other (n-1) axes instead of performing inner/outer set logic.

## Concatenating Objects

The **concat** function does all of the heavy lifting of performing concatenation operations along an axis. Let us create different objects and do concatenation.

```
import pandas as pd
```

[Live Demo](#)

```
one = pd.DataFrame({
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id': ['sub1', 'sub2', 'sub4', 'sub6', 'sub5'],
    'Marks_scored': [98, 90, 87, 69, 78]},
    index=[1, 2, 3, 4, 5])

two = pd.DataFrame({
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id': ['sub2', 'sub4', 'sub3', 'sub6', 'sub5'],
    'Marks_scored': [89, 80, 79, 97, 88]},
    index=[1, 2, 3, 4, 5])
print pd.concat([one, two])
```

Its **output** is as follows –

	Marks_scored	Name	subject_id
1	98	Alex	sub1
2	90	Amy	sub2
3	87	Allen	sub4
4	69	Alice	sub6
5	78	Ayoung	sub5
1	89	Billy	sub2
2	80	Brian	sub4
3	79	Bran	sub3



4	97	Bryce	sub6
5	88	Betty	sub5

Suppose we wanted to associate specific keys with each of the pieces of the chopped up DataFrame. We can do this by using the **keys** argument –

```
import pandas as pd
```

[Live Demo](#)

```
one = pd.DataFrame({
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id': ['sub1', 'sub2', 'sub4', 'sub6', 'sub5'],
    'Marks_scored': [98, 90, 87, 69, 78]},
    index=[1, 2, 3, 4, 5])

two = pd.DataFrame({
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id': ['sub2', 'sub4', 'sub3', 'sub6', 'sub5'],
    'Marks_scored': [89, 80, 79, 97, 88]},
    index=[1, 2, 3, 4, 5])
print pd.concat([one, two], keys=['x', 'y'])
```

Its **output** is as follows –

```
x 1 98  Alex  sub1
   2 90  Amy   sub2
   3 87  Allen sub4
   4 69  Alice sub6
   5 78  Ayoung sub5
y 1 89  Billy sub2
   2 80  Brian sub4
   3 79  Bran  sub3
   4 97  Bryce sub6
   5 88  Betty sub5
```

The index of the resultant is duplicated; each index is repeated.

If the resultant object has to follow its own indexing, set **ignore\_index** to **True**.

```
import pandas as pd
```

[Live Demo](#)

```
one = pd.DataFrame({
```

```

    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id':['sub1','sub2','sub4','sub6','sub5'],
    'Marks_scored':[98,90,87,69,78]},
    index=[1,2,3,4,5])

two = pd.DataFrame({
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id':['sub2','sub4','sub3','sub6','sub5'],
    'Marks_scored':[89,80,79,97,88]},
    index=[1,2,3,4,5])
print pd.concat([one,two],keys=['x','y'],ignore_index=True)

```

Its **output** is as follows –

	Marks_scored	Name	subject_id
0	98	Alex	sub1
1	90	Amy	sub2
2	87	Allen	sub4
3	69	Alice	sub6
4	78	Ayoung	sub5
5	89	Billy	sub2
6	80	Brian	sub4
7	79	Bran	sub3
8	97	Bryce	sub6
9	88	Betty	sub5

Observe, the index changes completely and the Keys are also overridden.

If two objects need to be added along **axis=1**, then the new columns will be appended.

```
import pandas as pd
```

[Live Demo](#)

```

one = pd.DataFrame({
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id':['sub1','sub2','sub4','sub6','sub5'],
    'Marks_scored':[98,90,87,69,78]},
    index=[1,2,3,4,5])

two = pd.DataFrame({
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id':['sub2','sub4','sub3','sub6','sub5'],
    'Marks_scored':[89,80,79,97,88]},

```

```
index=[1,2,3,4,5])
print pd.concat([one,two],axis=1)
```

Its **output** is as follows –

	Marks_scored	Name	subject_id	Marks_scored	Name	subject_id
1	98	Alex	sub1	89	Billy	sub2
2	90	Amy	sub2	80	Brian	sub4
3	87	Allen	sub4	79	Bran	sub3
4	69	Alice	sub6	97	Bryce	sub6
5	78	Ayoung	sub5	88	Betty	sub5

## Concatenating Using append

A useful shortcut to concat are the append instance methods on Series and DataFrame. These methods actually predated concat. They concatenate along **axis=0**, namely the index –

```
import pandas as pd
```

[Live Demo](#)

```
one = pd.DataFrame({
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id': ['sub1', 'sub2', 'sub4', 'sub6', 'sub5'],
    'Marks_scored': [98,90,87,69,78]},
    index=[1,2,3,4,5])

two = pd.DataFrame({
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id': ['sub2', 'sub4', 'sub3', 'sub6', 'sub5'],
    'Marks_scored': [89,80,79,97,88]},
    index=[1,2,3,4,5])
print one.append(two)
```

Its **output** is as follows –

	Marks_scored	Name	subject_id
1	98	Alex	sub1
2	90	Amy	sub2
3	87	Allen	sub4
4	69	Alice	sub6
5	78	Ayoung	sub5

1	89	Billy	sub2
2	80	Brian	sub4
3	79	Bran	sub3
4	97	Bryce	sub6
5	88	Betty	sub5

The **append** function can take multiple objects as well –

```
import pandas as pd
```

[Live Demo](#)

```
one = pd.DataFrame({
    'Name': ['Alex', 'Amy', 'Allen', 'Alice', 'Ayoung'],
    'subject_id': ['sub1', 'sub2', 'sub4', 'sub6', 'sub5'],
    'Marks_scored': [98, 90, 87, 69, 78]},
    index=[1, 2, 3, 4, 5])

two = pd.DataFrame({
    'Name': ['Billy', 'Brian', 'Bran', 'Bryce', 'Betty'],
    'subject_id': ['sub2', 'sub4', 'sub3', 'sub6', 'sub5'],
    'Marks_scored': [89, 80, 79, 97, 88]},
    index=[1, 2, 3, 4, 5])

print one.append([two, one, two])
```

Its **output** is as follows –

	Marks_scored	Name	subject_id
1	98	Alex	sub1
2	90	Amy	sub2
3	87	Allen	sub4
4	69	Alice	sub6
5	78	Ayoung	sub5
1	89	Billy	sub2
2	80	Brian	sub4
3	79	Bran	sub3
4	97	Bryce	sub6
5	88	Betty	sub5
1	98	Alex	sub1
2	90	Amy	sub2
3	87	Allen	sub4
4	69	Alice	sub6
5	78	Ayoung	sub5

1	89	Billy	sub2
2	80	Brian	sub4
3	79	Bran	sub3
4	97	Bryce	sub6
5	88	Betty	sub5

## Time Series

Pandas provide a robust tool for working time with Time series data, especially in the financial sector. While working with time series data, we frequently come across the following –

- Generating sequence of time
- Convert the time series to different frequencies

Pandas provides a relatively compact and self-contained set of tools for performing the above tasks.

## Get Current Time

**datetime.now()** gives you the current date and time.

```
import pandas as pd

print pd.datetime.now()
```

[Live Demo](#)

Its **output** is as follows –

```
2017-05-11 06:10:13.393147
```

## Create a TimeStamp

Time-stamped data is the most basic type of timeseries data that associates values with points in time. For pandas objects, it means using the points in time. Let's take an example –

```
import pandas as pd
```

[Live Demo](#)

```
print pd.Timestamp('2017-03-01')
```

Its **output** is as follows –

```
2017-03-01 00:00:00
```

It is also possible to convert integer or float epoch times. The default unit for these is nanoseconds (since these are how Timestamps are stored). However, often epochs are stored in another unit which can be specified. Let's take another example

```
import pandas as pd

print pd.Timestamp(1587687255,unit='s')
```

[Live Demo](#)

Its **output** is as follows –

```
2020-04-24 00:14:15
```

## Create a Range of Time

```
import pandas as pd

print pd.date_range("11:00", "13:30", freq="30min").time
```

[Live Demo](#)

Its **output** is as follows –

```
[datetime.time(11, 0) datetime.time(11, 30) datetime.time(12, 0)
datetime.time(12, 30) datetime.time(13, 0) datetime.time(13, 30)]
```

## Change the Frequency of Time

```
import pandas as pd

print pd.date_range("11:00", "13:30", freq="H").time
```

[Live Demo](#)

Its **output** is as follows –

```
[datetime.time(11, 0) datetime.time(12, 0) datetime.time(13, 0)]
```

## Converting to Timestamps

To convert a Series or list-like object of date-like objects, for example strings, epochs, or a mixture, you can use the **to\_datetime** function. When passed, this returns a Series (with the same index), while a **list-like** is converted to a **DatetimeIndex**. Take a look at the following example –

```
import pandas as pd
```

[Live Demo](#)

```
print pd.to_datetime(pd.Series(['Jul 31, 2009', '2010-01-10', None]))
```

Its **output** is as follows –

```
0 2009-07-31
1 2010-01-10
2      NaT
dtype: datetime64[ns]
```

**NaT** means **Not a Time** (equivalent to NaN)

Let's take another example.

```
import pandas as pd
```

[Live Demo](#)

```
print pd.to_datetime(['2005/11/23', '2010.12.31', None])
```

Its **output** is as follows –

```
DatetimeIndex(['2005-11-23', '2010-12-31', 'NaT'], dtype='datetime64[ns]', freq=None)
```

## Python Pandas - Date Functionality

Extending the Time series, Date functionalities play major role in financial data analysis. While working with Date data, we will frequently come across the following –

- Generating sequence of dates
- Convert the date series to different frequencies

## Create a Range of Dates

Using the **date.range()** function by specifying the periods and the frequency, we can create the date series. By default, the frequency of range is Days.

```
import pandas as pd

print pd.date_range('1/1/2011', periods=5)
```

[Live Demo](#)

Its **output** is as follows –

```
DatetimeIndex(['2011-01-01', '2011-01-02', '2011-01-03', '2011-01-04', '2011-01-05'],
              dtype='datetime64[ns]', freq='D')
```

## Change the Date Frequency

```
import pandas as pd

print pd.date_range('1/1/2011', periods=5, freq='M')
```

[Live Demo](#)

Its **output** is as follows –

```
DatetimeIndex(['2011-01-31', '2011-02-28', '2011-03-31', '2011-04-30', '2011-05-31'],
              dtype='datetime64[ns]', freq='M')
```

## bdate\_range

bdate\_range() stands for business date ranges. Unlike date\_range(), it excludes Saturday and Sunday.

```
import pandas as pd
```

[Live Demo](#)



```
print pd.date_range('1/1/2011', periods=5)
```

Its **output** is as follows –

```
DatetimeIndex(['2011-01-01', '2011-01-02', '2011-01-03', '2011-01-04', '2011-01-05'],
              dtype='datetime64[ns]', freq='D')
```

Observe, after 3rd March, the date jumps to 6th march excluding 4th and 5th. Just check your calendar for the days.

Convenience functions like **date\_range** and **bdate\_range** utilize a variety of frequency aliases. The default frequency for `date_range` is a calendar day while the default for `bdate_range` is a business day.

```
import pandas as pd
start = pd.datetime(2011, 1, 1)
end = pd.datetime(2011, 1, 5)

print pd.date_range(start, end)
```

[Live Demo](#)

Its **output** is as follows –

```
DatetimeIndex(['2011-01-01', '2011-01-02', '2011-01-03', '2011-01-04', '2011-01-05'],
              dtype='datetime64[ns]', freq='D')
```

## Offset Aliases

A number of string aliases are given to useful common time series frequencies. We will refer to these aliases as offset aliases.

Alias	Description	Alias	Description
B	business day frequency	BQS	business quarter start frequency
D	calendar day frequency	A	annual(Year) end frequency
W	weekly frequency	BA	business year end frequency
M	month end frequency	BAS	business year start frequency

SM	semi-month end frequency	BH	business hour frequency
BM	business month end frequency	H	hourly frequency
MS	month start frequency	T, min	minutely frequency
SMS	SMS semi month start frequency	S	secondly frequency
BMS	business month start frequency	L, ms	milliseconds
Q	quarter end frequency	U, us	microseconds
BQ	business quarter end frequency	N	nanoseconds
QS	quarter start frequency		

## Python Pandas - Timedelta

Timedeltas are differences in times, expressed in difference units, for example, days, hours, minutes, seconds. They can be both positive and negative.

We can create Timedelta objects using various arguments as shown below –

### String

By passing a string literal, we can create a timedelta object.

```
import pandas as pd

print pd.Timedelta('2 days 2 hours 15 minutes 30 seconds')
```

[Live Demo](#)

Its **output** is as follows –

```
2 days 02:15:30
```

### Integer

By passing an integer value with the unit, an argument creates a Timedelta object.

```
import pandas as pd
```

[Live Demo](#)

```
print pd.Timedelta(6,unit='h')
```

Its **output** is as follows –

```
0 days 06:00:00
```

## Data Offsets

Data offsets such as - weeks, days, hours, minutes, seconds, milliseconds, microseconds, nanoseconds can also be used in construction.

```
import pandas as pd
```

[Live Demo](#)

```
print pd.Timedelta(days=2)
```

Its **output** is as follows –

```
2 days 00:00:00
```

## to\_timedelta()

Using the top-level **pd.to\_timedelta**, you can convert a scalar, array, list, or series from a recognized timedelta format/ value into a Timedelta type. It will construct Series if the input is a Series, a scalar if the input is scalar-like, otherwise will output a **TimedeltaIndex**.

```
import pandas as pd
```

[Live Demo](#)

```
print pd.Timedelta(days=2)
```

Its **output** is as follows –

```
2 days 00:00:00
```

## Operations

You can operate on Series/ DataFrames and construct **timedelta64[ns]** Series through subtraction operations on **datetime64[ns]** Series, or Timestamps.

Let us now create a DataFrame with Timedelta and datetime objects and perform some arithmetic operations on it –

```
import pandas as pd
```

[Live Demo](#)

```
s = pd.Series(pd.date_range('2012-1-1', periods=3, freq='D'))
td = pd.Series([ pd.Timedelta(days=i) for i in range(3) ])
df = pd.DataFrame(dict(A = s, B = td))
```

```
print df
```

Its **output** is as follows –

	A	B
0	2012-01-01	0 days
1	2012-01-02	1 days
2	2012-01-03	2 days

## Addition Operations

```
import pandas as pd
```

[Live Demo](#)

```
s = pd.Series(pd.date_range('2012-1-1', periods=3, freq='D'))
td = pd.Series([ pd.Timedelta(days=i) for i in range(3) ])
df = pd.DataFrame(dict(A = s, B = td))
df['C']=df['A']+df['B']
```

```
print df
```

Its **output** is as follows –

	A	B	C
0	2012-01-01	0 days	2012-01-01
1	2012-01-02	1 days	2012-01-03
2	2012-01-03	2 days	2012-01-05

## Subtraction Operation

```
import pandas as pd
```

[Live Demo](#)

```
s = pd.Series(pd.date_range('2012-1-1', periods=3, freq='D'))
td = pd.Series([ pd.Timedelta(days=i) for i in range(3) ])
df = pd.DataFrame(dict(A = s, B = td))
df['C']=df['A']+df['B']
df['D']=df['C']+df['B']

print df
```

Its **output** is as follows –

	A	B	C	D
0	2012-01-01	0 days	2012-01-01	2012-01-01
1	2012-01-02	1 days	2012-01-03	2012-01-04
2	2012-01-03	2 days	2012-01-05	2012-01-07

## Python Pandas - Categorical Data

Often in real-time, data includes the text columns, which are repetitive. Features like gender, country, and codes are always repetitive. These are the examples for categorical data.

Categorical variables can take on only a limited, and usually fixed number of possible values. Besides the fixed length, categorical data might have an order but cannot perform numerical operation. Categorical are a Pandas data type.

The categorical data type is useful in the following cases –

- A string variable consisting of only a few different values. Converting such a string variable to a categorical variable will save some memory.
- The lexical order of a variable is not the same as the logical order ("one", "two", "three"). By converting to a categorical and specifying an order on the categories, sorting and min/max will use the logical order instead of the lexical order.
- As a signal to other python libraries that this column should be treated as a categorical variable (e.g. to use suitable statistical methods or plot types).

### Object Creation

Categorical object can be created in multiple ways. The different ways have been described below –

## category

By specifying the dtype as "category" in pandas object creation.

```
import pandas as pd

s = pd.Series(["a", "b", "c", "a"], dtype="category")
print s
```

[Live Demo](#)

Its **output** is as follows –

```
0 a
1 b
2 c
3 a
dtype: category
Categories (3, object): [a, b, c]
```

The number of elements passed to the series object is four, but the categories are only three. Observe the same in the output Categories.

## pd.Categorical

Using the standard pandas Categorical constructor, we can create a category object.

```
pandas.Categorical(values, categories, ordered)
```

Let's take an example –

```
import pandas as pd

cat = pd.Categorical(['a', 'b', 'c', 'a', 'b', 'c'])
print cat
```

[Live Demo](#)

Its **output** is as follows –

```
[a, b, c, a, b, c]
Categories (3, object): [a, b, c]
```

Let's have another example –

```
import pandas as pd

cat = cat=pd.Categorical(['a','b','c','a','b','c','d'], ['c', 'b', 'a'])
print cat
```

[Live Demo](#)

Its **output** is as follows –

```
[a, b, c, a, b, c, NaN]
Categories (3, object): [c, b, a]
```

Here, the second argument signifies the categories. Thus, any value which is not present in the categories will be treated as **NaN**.

Now, take a look at the following example –

```
import pandas as pd

cat = cat=pd.Categorical(['a','b','c','a','b','c','d'], ['c', 'b', 'a'],ordered=True)
print cat
```

[Live Demo](#)

Its **output** is as follows –

```
[a, b, c, a, b, c, NaN]
Categories (3, object): [c < b < a]
```

Logically, the order means that, **a** is greater than **b** and **b** is greater than **c**.

## Description

Using the **.describe()** command on the categorical data, we get similar output to a **Series** or **DataFrame** of the **type** string.

Live Demo

```
import pandas as pd
import numpy as np

cat = pd.Categorical(["a", "c", "c", np.nan], categories=["b", "a", "c"])
df = pd.DataFrame({"cat":cat, "s":["a", "c", "c", np.nan]})

print df.describe()
print df["cat"].describe()
```

Its **output** is as follows –

```
cat s
count  3 3
unique  2 2
top     c c
freq    2 2
count   3
unique  2
top     c
freq    2
Name: cat, dtype: object
```

## Get the Properties of the Category

**obj.cat.categories** command is used to get the **categories of the object**.

Live Demo

```
import pandas as pd
import numpy as np

s = pd.Categorical(["a", "c", "c", np.nan], categories=["b", "a", "c"])
print s.categories
```

Its **output** is as follows –

```
Index([u'b', u'a', u'c'], dtype='object')
```

**obj.ordered** command is used to get the order of the object.

Live Demo



```
import pandas as pd
import numpy as np

cat = pd.Categorical(["a", "c", "c", np.nan], categories=["b", "a", "c"])
print cat.ordered
```

Its **output** is as follows –

```
False
```

The function returned **false** because we haven't specified any order.

## Renaming Categories

Renaming categories is done by assigning new values to the **series.cat.categories** property.

```
import pandas as pd

s = pd.Series(["a","b","c","a"], dtype="category")
s.cat.categories = ["Group %s" % g for g in s.cat.categories]
print s.cat.categories
```

[Live Demo](#)

Its **output** is as follows –

```
Index([u'Group a', u'Group b', u'Group c'], dtype='object')
```

Initial categories **[a,b,c]** are updated by the **s.cat.categories** property of the object.

## Appending New Categories

Using the `Categorical.add.categories()` method, new categories can be appended.

```
import pandas as pd

s = pd.Series(["a","b","c","a"], dtype="category")
s = s.cat.add_categories([4])
print s.cat.categories
```

[Live Demo](#)

Its **output** is as follows –

```
Index([u'a', u'b', u'c', 4], dtype='object')
```

## Removing Categories

Using the **Categorical.remove\_categories()** method, unwanted categories can be removed.

```
import pandas as pd

s = pd.Series(["a", "b", "c", "a"], dtype="category")
print ("Original object:")
print s

print ("After removal:")
print s.cat.remove_categories("a")
```

[Live Demo](#)

Its **output** is as follows –

```
Original object:
0  a
1  b
2  c
3  a
dtype: category
Categories (3, object): [a, b, c]
```

```
After removal:
0  NaN
1  b
2  c
3  NaN
dtype: category
Categories (2, object): [b, c]
```

## Comparison of Categorical Data

Comparing categorical data with other objects is possible in three cases –

- comparing equality (== and !=) to a list-like object (list, Series, array, ...) of the same length as the categorical data.
- all comparisons (==, !=, >, >=, <, and <=) of categorical data to another categorical Series, when ordered==True and the categories are the same.
- all comparisons of a categorical data to a scalar.

Take a look at the following example –

```
import pandas as pd
```

[Live Demo](#)

```
cat = pd.Series([1,2,3]).astype("category", categories=[1,2,3], ordered=True)
cat1 = pd.Series([2,2,2]).astype("category", categories=[1,2,3], ordered=True)

print cat>cat1
```

Its **output** is as follows –

```
0 False
1 False
2 True
dtype: bool
```

## Python Pandas - Visualization

### Basic Plotting: plot


This functionality on Series and DataFrame is just a simple wrapper around the **matplotlib libraries plot()** method.

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10,4), index=pd.date_range('1/1/2000',
    periods=10), columns=list('ABCD'))

df.plot()
```

Its **output** is as follows –



If the index consists of dates, it calls **gct().autofmt\_xdate()** to format the x-axis as shown in the above illustration.

We can plot one column versus another using the **x** and **y** keywords.

Plotting methods allow a handful of plot styles other than the default line plot. These methods can be provided as the kind keyword argument to **plot()**. These include –

- bar or barh for bar plots
- hist for histogram
- box for boxplot
- 'area' for area plots
- 'scatter' for scatter plots


## Bar Plot

Let us now see what a Bar Plot is by creating one. A bar plot can be created in the following way –

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.rand(10,4),columns=['a','b','c','d'])
df.plot.bar()
```


Its **output** is as follows –



To produce a stacked bar plot, **pass stacked=True** –

```
import pandas as pd
df = pd.DataFrame(np.random.rand(10,4), columns=['a', 'b', 'c', 'd'])
df.plot.bar(stacked=True)
```

Its **output** is as follows –




To get horizontal bar plots, use the **barh** method –

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.rand(10,4), columns=['a', 'b', 'c', 'd'])

df.plot.barh(stacked=True)
```

Its **output** is as follows –



## Histograms


Histograms can be plotted using the **plot.hist()** method. We can specify number of bins.

```
import pandas as pd
import numpy as np

df = pd.DataFrame({'a':np.random.randn(1000)+1,'b':np.random.randn(1000),'c':
np.random.randn(1000) - 1}, columns=['a', 'b', 'c'])

df.plot.hist(bins=20)
```

Its **output** is as follows –




To plot different histograms for each column, use the following code –

```
import pandas as pd
import numpy as np

df=pd.DataFrame({'a':np.random.randn(1000)+1, 'b':np.random.randn(1000), 'c':
np.random.randn(1000) - 1}, columns=['a', 'b', 'c'])

df.diff.hist(bins=20)
```

Its **output** is as follows –




## Box Plots

Boxplot can be drawn calling **Series.box.plot()** and **DataFrame.box.plot()**, or **DataFrame.boxplot()** to visualize the distribution of values within each column.

For instance, here is a boxplot representing five trials of 10 observations of a uniform random variable on [0,1).

```
import pandas as pd
import numpy as np
df = pd.DataFrame(np.random.rand(10, 5), columns=['A', 'B', 'C', 'D', 'E'])
df.plot.box()
```

Its **output** is as follows –




## Area Plot

Area plot can be created using the **Series.plot.area()** or the **DataFrame.plot.area()** methods.

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.rand(10, 4), columns=['a', 'b', 'c', 'd'])
df.plot.area()
```

Its **output** is as follows –



## Scatter Plot


Scatter plot can be created using the **DataFrame.plot.scatter()** methods.

```
import pandas as pd
import numpy as np
```



```
df = pd.DataFrame(np.random.rand(50, 4), columns=['a', 'b', 'c', 'd'])
df.plot.scatter(x='a', y='b')
```

Its **output** is as follows –




## Pie Chart

Pie chart can be created using the **DataFrame.plot.pie()** method.

```
import pandas as pd
import numpy as np

df = pd.DataFrame(3 * np.random.rand(4), index=['a', 'b', 'c', 'd'], columns=['x'])
df.plot.pie(subplots=True)
```

Its **output** is as follows –



# Python Pandas - IO Tools

The **Pandas I/O API** is a set of top level reader functions accessed like **pd.read\_csv()** that generally return a Pandas object.

The two workhorse functions for reading text files (or the flat files) are **read\_csv()** and **read\_table()**. They both use the same parsing code to intelligently convert tabular data into a **DataFrame** object –

```
pandas.read_csv(filepath_or_buffer, sep=',', delimiter=None, header='infer',
names=None, index_col=None, usecols=None
```

```
pandas.read_csv(filepath_or_buffer, sep='\t', delimiter=None, header='infer',
names=None, index_col=None, usecols=None
```

Here is how the **csv** file data looks like –

```
S.No,Name,Age,City,Salary
1,Tom,28,Toronto,20000
2,Lee,32,HongKong,3000
3,Steven,43,Bay Area,8300
4,Ram,38,Hyderabad,3900
```

Save this data as **temp.csv** and conduct operations on it.

```
S.No,Name,Age,City,Salary
1,Tom,28,Toronto,20000
2,Lee,32,HongKong,3000
3,Steven,43,Bay Area,8300
4,Ram,38,Hyderabad,3900
```

Save this data as **temp.csv** and conduct operations on it.

## read.csv

**read.csv** reads data from the csv files and creates a DataFrame object.

```
import pandas as pd
```

```
df=pd.read_csv("temp.csv")
print df
```

Its **output** is as follows –

	S.No	Name	Age	City	Salary
0	1	Tom	28	Toronto	20000
1	2	Lee	32	HongKong	3000
2	3	Steven	43	Bay Area	8300
3	4	Ram	38	Hyderabad	3900

## custom index

This specifies a column in the csv file to customize the index using **index\_col**.

```
import pandas as pd

df=pd.read_csv("temp.csv",index_col=['S.No'])
print df
```

Its **output** is as follows –

	S.No	Name	Age	City	Salary
1	Tom	28	Toronto	20000	
2	Lee	32	HongKong	3000	
3	Steven	43	Bay Area	8300	
4	Ram	38	Hyderabad	3900	

## Converters

**dtype** of the columns can be passed as a dict.

```
import pandas as pd

df = pd.read_csv("temp.csv", dtype={'Salary': np.float64})
print df.dtypes
```

Its **output** is as follows –

```

S.No    int64
Name     object
Age      int64
City     object
Salary   float64
dtype: object

```

By default, the **dtype** of the Salary column is **int**, but the result shows it as **float** because we have explicitly casted the type.

Thus, the data looks like float –

```

  S.No  Name  Age  City  Salary
0  1    Tom   28  Toronto 20000.0
1  2    Lee   32  HongKong  3000.0
2  3  Steven   43  Bay Area  8300.0
3  4    Ram   38  Hyderabad  3900.0

```

## header\_names

Specify the names of the header using the names argument.

```

import pandas as pd

df=pd.read_csv("temp.csv", names=['a', 'b', 'c','d','e'])
print df

```

Its **output** is as follows –

```

      a    b  c    d    e
0  S.No  Name Age  City Salary
1    1   Tom  28  Toronto 20000
2    2   Lee  32  HongKong  3000
3    3 Steven  43  Bay Area  8300
4    4   Ram  38  Hyderabad  3900

```

Observe, the header names are appended with the custom names, but the header in the file has not been eliminated. Now, we use the header argument to remove that.

If the header is in a row other than the first, pass the row number to header. This will skip the preceding rows.

```
import pandas as pd

df=pd.read_csv("temp.csv",names=['a','b','c','d','e'],header=0)
print df
```

Its **output** is as follows –

	a	b	c	d	e
0	S.No	Name	Age	City	Salary
1	1	Tom	28	Toronto	20000
2	2	Lee	32	HongKong	3000
3	3	Steven	43	Bay Area	8300
4	4	Ram	38	Hyderabad	3900

## skiprows

skiprows skips the number of rows specified.

```
import pandas as pd

df=pd.read_csv("temp.csv", skiprows=2)
print df
```

Its **output** is as follows –

	2	Lee	32	HongKong	3000
0	3	Steven	43	Bay Area	8300
1	4	Ram	38	Hyderabad	3900

## Python Pandas - Sparse Data

Sparse objects are “compressed” when any data matching a specific value (NaN / missing value, though any value can be chosen) is omitted. A special SparseIndex object tracks where data has been “sparsified”. This will make much more sense in an example. All of the standard Pandas data structures apply the **to\_sparse** method –

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
ts = pd.Series(np.random.randn(10))
ts[2:-2] = np.nan
sts = ts.to_sparse()
print sts
```

Its **output** is as follows –

```
0 -0.810497
1 -1.419954
2      NaN
3      NaN
4      NaN
5      NaN
6      NaN
7      NaN
8  0.439240
9 -1.095910
dtype: float64
BlockIndex
Block locations: array([0, 8], dtype=int32)
Block lengths: array([2, 2], dtype=int32)
```

The sparse objects exist for memory efficiency reasons.

Let us now assume you had a large NA DataFrame and execute the following code –

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(10000, 4))
df.ix[:9998] = np.nan
sdf = df.to_sparse()

print sdf.density
```

[Live Demo](#)

Its **output** is as follows –

```
0.0001
```

Any sparse object can be converted back to the standard dense form by calling **to\_dense** –

```
import pandas as pd
import numpy as np
ts = pd.Series(np.random.randn(10))
ts[2:-2] = np.nan
sts = ts.to_sparse()
print sts.to_dense()
```

[Live Demo](#)

Its **output** is as follows –

```
0  -0.810497
1  -1.419954
2      NaN
3      NaN
4      NaN
5      NaN
6      NaN
7      NaN
8   0.439240
9  -1.095910
dtype: float64
```

## Sparse Dtypes

Sparse data should have the same dtype as its dense representation. Currently, **float64**, **int64** and **booldtypes** are supported. Depending on the original **dtype**, **fill\_value default** changes –

- **float64** – np.nan
- **int64** – 0
- **bool** – False

Let us execute the following code to understand the same –

```
import pandas as pd
import numpy as np

s = pd.Series([1, np.nan, np.nan])
print s
```

[Live Demo](#)

```
s.to_sparse()
print s
```

Its **output** is as follows –

```
0    1.0
1    NaN
2    NaN
dtype: float64

0    1.0
1    NaN
2    NaN
dtype: float64
```

## Python Pandas - Caveats & Gotchas

Caveats means warning and gotcha means an unseen problem.

### Using If/Truth Statement with Pandas

Pandas follows the numpy convention of raising an error when you try to convert something to a **bool**. This happens in an **if** or **when** using the Boolean operations, and, **or**, or **not**. It is not clear what the result should be. Should it be True because it is not zerolength? False because there are False values? It is unclear, so instead, Pandas raises a **ValueError** –

```
import pandas as pd

if pd.Series([False, True, False]):
    print 'I am True'
```

[Live Demo](#)

Its **output** is as follows –

```
ValueError: The truth value of a Series is ambiguous.
Use a.empty, a.bool(), a.item(), a.any() or a.all().
```

In **if** condition, it is unclear what to do with it. The error is suggestive of whether to use a **None** or **any of those**.



```
import pandas as pd

if pd.Series([False, True, False]).any():
    print("I am any")
```

[Live Demo](#)

Its **output** is as follows –

```
I am any
```

To evaluate single-element pandas objects in a Boolean context, use the method **.bool()** –

```
import pandas as pd

print pd.Series([True]).bool()
```

[Live Demo](#)

Its **output** is as follows –

```
True
```

## Bitwise Boolean

Bitwise Boolean operators like `==` and `!=` will return a Boolean series, which is almost always what is required anyways.

```
import pandas as pd

s = pd.Series(range(5))
print s==4
```

[Live Demo](#)

Its **output** is as follows –

```
0 False
1 False
2 False
3 False
```

```
4 True
dtype: bool
```

## isin Operation

This returns a Boolean series showing whether each element in the Series is exactly contained in the passed sequence of values.

```
import pandas as pd

s = pd.Series(list('abc'))
s = s.isin(['a', 'c', 'e'])
print s
```

[Live Demo](#)

Its **output** is as follows –

```
0 True
1 False
2 True
dtype: bool
```

## Reindexing vs ix Gotcha

Many users will find themselves using the **ix indexing capabilities** as a concise means of selecting data from a Pandas object –

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(6, 4), columns=['one', 'two', 'three',
'four'], index=list('abcdef'))

print df
print df.ix[['b', 'c', 'e']]
```

[Live Demo](#)

Its **output** is as follows –

```
      one      two      three      four
a -1.582025  1.335773  0.961417 -1.272084
```

b	1.461512	0.111372	-0.072225	0.553058
c	-1.240671	0.762185	1.511936	-0.630920
d	-2.380648	-0.029981	0.196489	0.531714
e	1.846746	0.148149	0.275398	-0.244559
f	-1.842662	-0.933195	2.303949	0.677641

	one	two	three	four
b	1.461512	0.111372	-0.072225	0.553058
c	-1.240671	0.762185	1.511936	-0.630920
e	1.846746	0.148149	0.275398	-0.244559

This is, of course, completely equivalent in this case to using the **reindex** method –

```
import pandas as pd
import numpy as np

df = pd.DataFrame(np.random.randn(6, 4), columns=['one', 'two', 'three',
'four'], index=list('abcdef'))

print df
print df.reindex(['b', 'c', 'e'])
```

[Live Demo](#)

Its **output** is as follows –

	one	two	three	four
a	1.639081	1.369838	0.261287	-1.662003
b	-0.173359	0.242447	-0.494384	0.346882
c	-0.106411	0.623568	0.282401	-0.916361
d	-1.078791	-0.612607	-0.897289	-1.146893
e	0.465215	1.552873	-1.841959	0.329404
f	0.966022	-0.190077	1.324247	0.678064

	one	two	three	four
b	-0.173359	0.242447	-0.494384	0.346882
c	-0.106411	0.623568	0.282401	-0.916361
e	0.465215	1.552873	-1.841959	0.329404

Some might conclude that **ix** and **reindex** are 100% equivalent based on this. This is true except in the case of integer indexing. For example, the above operation can alternatively be expressed as –

```
import pandas as pd
import numpy as np
```

[Live Demo](#)

```
df = pd.DataFrame(np.random.randn(6, 4), columns=['one', 'two', 'three',
'four'], index=list('abcdef'))
```

```
print df
print df.ix[[1, 2, 4]]
print df.reindex([1, 2, 4])
```

Its **output** is as follows –

```
      one      two      three      four
a -1.015695 -0.553847  1.106235 -0.784460
b -0.527398 -0.518198 -0.710546 -0.512036
c -0.842803 -1.050374  0.787146  0.205147
d -1.238016 -0.749554 -0.547470 -0.029045
e -0.056788  1.063999 -0.767220  0.212476
f  1.139714  0.036159  0.201912  0.710119
```

```
      one      two      three      four
b -0.527398 -0.518198 -0.710546 -0.512036
c -0.842803 -1.050374  0.787146  0.205147
e -0.056788  1.063999 -0.767220  0.212476
```

```
      one two three four
1  NaN NaN  NaN  NaN
2  NaN NaN  NaN  NaN
4  NaN NaN  NaN  NaN
```

It is important to remember that **reindex is strict label indexing only**. This can lead to some potentially surprising results in pathological cases where an index contains, say, both integers and strings.

## Python Pandas - Comparison with SQL

Since many potential Pandas users have some familiarity with SQL, this page is meant to provide some examples of how various SQL operations can be performed using pandas.

```
import pandas as pd
```

```
url = 'https://raw.githubusercontent.com/pandasdev/
pandas/master/pandas/tests/data/tips.csv'

tips=pd.read_csv(url)
print tips.head()
```

Its **output** is as follows –

	total_bill	tip	sex	smoker	day	time	size
0	16.99	1.01	Female	No	Sun	Dinner	2
1	10.34	1.66	Male	No	Sun	Dinner	3
2	21.01	3.50	Male	No	Sun	Dinner	3
3	23.68	3.31	Male	No	Sun	Dinner	2
4	24.59	3.61	Female	No	Sun	Dinner	4

## SELECT

In SQL, selection is done using a comma-separated list of columns that you select (or a \* to select all columns) –

```
SELECT total_bill, tip, smoker, time
FROM tips
LIMIT 5;
```

With Pandas, column selection is done by passing a list of column names to your DataFrame –

```
tips[['total_bill', 'tip', 'smoker', 'time']].head(5)
```

Let's check the full program –

```
import pandas as pd

url = 'https://raw.githubusercontent.com/pandasdev/
pandas/master/pandas/tests/data/tips.csv'

tips=pd.read_csv(url)
print tips[['total_bill', 'tip', 'smoker', 'time']].head(5)
```

Its **output** is as follows –

	total_bill	tip	smoker	time
0	16.99	1.01	No	Dinner
1	10.34	1.66	No	Dinner
2	21.01	3.50	No	Dinner
3	23.68	3.31	No	Dinner
4	24.59	3.61	No	Dinner

Calling the DataFrame without the list of column names will display all columns (akin to SQL's \*).

## WHERE

Filtering in SQL is done via a WHERE clause.

```
SELECT * FROM tips WHERE time = 'Dinner' LIMIT 5;
```

DataFrames can be filtered in multiple ways; the most intuitive of which is using Boolean indexing.

```
tips[tips['time'] == 'Dinner'].head(5)
```

Let's check the full program –

```
import pandas as pd

url = 'https://raw.githubusercontent.com/pandasdev/
pandas/master/pandas/tests/data/tips.csv'

tips=pd.read_csv(url)
print tips[tips['time'] == 'Dinner'].head(5)
```

Its **output** is as follows –

	total_bill	tip	sex	smoker	day	time	size
0	16.99	1.01	Female	No	Sun	Dinner	2
1	10.34	1.66	Male	No	Sun	Dinner	3
2	21.01	3.50	Male	No	Sun	Dinner	3
3	23.68	3.31	Male	No	Sun	Dinner	2
4	24.59	3.61	Female	No	Sun	Dinner	4

The above statement passes a Series of True/False objects to the DataFrame, returning all rows with True.

## GroupBy

This operation fetches the count of records in each group throughout a dataset. For instance, a query fetching us the number of tips left by sex –

```
SELECT sex, count(*)
FROM tips
GROUP BY sex;
```

The Pandas equivalent would be –

```
tips.groupby('sex').size()
```

Let's check the full program –

```
import pandas as pd

url = 'https://raw.githubusercontent.com/pandasdev/
pandas/master/pandas/tests/data/tips.csv'

tips=pd.read_csv(url)
print tips.groupby('sex').size()
```

Its **output** is as follows –

```
sex
Female  87
Male    157
dtype: int64
```

## Top N rows

SQL returns the **top n rows** using **LIMIT** –

```
SELECT * FROM tips
LIMIT 5 ;
```

The Pandas equivalent would be –

```
tips.head(5)
```

Let's check the full example –

```
import pandas as pd

url = 'https://raw.githubusercontent.com/pandas-dev/pandas/master/pandas/tests/data/tips.csv'

tips=pd.read_csv(url)
tips = tips[['smoker', 'day', 'time']].head(5)
print tips
```

Its **output** is as follows –

	smoker	day	time
0	No	Sun	Dinner
1	No	Sun	Dinner
2	No	Sun	Dinner
3	No	Sun	Dinner
4	No	Sun	Dinner

These are the few basic operations we compared are, which we learnt, in the previous chapters of the Pandas Library.