Bootstrap Inputs

Bootstrap offers a variety of input elements that you can use to create forms. Here's a brief overview of some of the most commonly used inputs in Bootstrap:

Basic Input Elements

```
Text Input
<div class="form-group">
<label for="exampleInputEmail1">Email address</label>
 <input type="email" class="form-control" id="exampleInputEmail1" aria-</pre>
describedby="emailHelp" placeholder="Enter email">
 <small id="emailHelp" class="form-text text-muted">We'll never share your email with
anyone else.</small>
</div>
```

Password Input

```
<div class="form-group">
<label for="exampleInputPassword1">Password</label>
<input type="password" class="form-control" id="exampleInputPassword1"</pre>
placeholder="Password">
</div>
```

File Input

```
<div class="form-group">
<label for="exampleFormControlFile1">Example file input</label>
<input type="file" class="form-control-file" id="exampleFormControlFile1">
</div>
```

Select Elements

Basic Select

```
<div class="form-group">
<label for="exampleFormControlSelect1">Example select</label>
<select class="form-control" id="exampleFormControlSelect1">
 <option>1</option>
 <option>2</option>
 <option>3</option>
 <option>4</option>
 <option>5</option>
</select>
</div>
```

```
Multiple Select
```

```
<div class="form-group">
  <label for="exampleFormControlSelect2">Example multiple select</label>
  <select multiple class="form-control" id="exampleFormControlSelect2">
        <option>1</option>
        <option>2</option>
        <option>3</option>
        <option>4</option>
        <option>5</option>
        </select>
</div>
```

Checkboxes and Radios

Checkboxes

```
<div class="form-check">
<input class="form-check-input" type="checkbox" value="" id="defaultCheck1">
 <label class="form-check-label" for="defaultCheck1">
 Default checkbox
</label>
</div>
Radio Buttons
<div class="form-check">
<input class="form-check-input" type="radio" name="exampleRadios"
id="exampleRadios1" value="option1" checked>
<label class="form-check-label" for="exampleRadios1">
 Default radio
</label>
</div>
<div class="form-check">
<input class="form-check-input" type="radio" name="exampleRadios"
id="exampleRadios2" value="option2">
<label class="form-check-label" for="exampleRadios2">
 Second default radio
</label>
</div>
```

Range Input

Range Input

```
<div class="form-group">
  <label for="formControlRange">Example Range input</label>
```

```
<input type="range" class="form-control-range" id="formControlRange">
</div>
```

Textarea

Textarea

```
<div class="form-group">
  <label for="exampleFormControlTextarea1">Example textarea</label>
  <textarea class="form-control" id="exampleFormControlTextarea1"
rows="3"></textarea>
  </div>
```

Input Groups

Input Group with Text

Input Group with Button

```
<div class="input-group mb-3">
  <input type="text" class="form-control" placeholder="Recipient's username" aria-label="Recipient's username" aria-describedby="button-addon2">
  <div class="input-group-append">
        <button class="btn btn-outline-secondary" type="button" id="button-addon2">Button</button>
  </div>
</div>
```