

Bootstrap Input Groups

Basic Example

HTML Code:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-
scale=1.0">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.
min.css">
  <title>Bootstrap Input Groups</title>
</head>
<body>
  <div class="container mt-5">
    <div class="input-group mb-3">
      <div class="input-group-prepend">
        <span class="input-group-text" id="basic-addon1">@</span>
      </div>
      <input type="text" class="form-control" placeholder="Username"
aria-label="Username" aria-describedby="basic-addon1">
    </div>
  </div>
</body>
</html>
```

Adding Buttons to Input Groups

HTML Code:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-
scale=1.0">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.
min.css">
  <title>Bootstrap Input Groups</title>
```

```

</head>
<body>
  <div class="container mt-5">
    <div class="input-group mb-3">
      <input type="text" class="form-control" placeholder="Recipient's
username" aria-label="Recipient's username" aria-describedby="basic-
addon2">
      <div class="input-group-append">
        <button class="btn btn-outline-secondary"
type="button">Button</button>
      </div>
    </div>
  </div>
</body>
</html>

```

Multiple Add-ons

HTML Code:

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-
scale=1.0">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.
min.css">
  <title>Bootstrap Input Groups</title>
</head>
<body>
  <div class="container mt-5">
    <div class="input-group mb-3">
      <div class="input-group-prepend">
        <span class="input-group-text">$</span>
        <span class="input-group-text">0.00</span>
      </div>
      <input type="text" class="form-control" aria-label="Dollar amount
(with dot and two decimal places)">
    </div>
  </div>
</body>
</html>

```

Input Group with Dropdowns

HTML Code:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-
scale=1.0">
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.
min.css">
  <title>Bootstrap Input Groups</title>
</head>
<body>
  <div class="container mt-5">
    <div class="input-group mb-3">
      <div class="input-group-prepend">
        <button class="btn btn-outline-secondary dropdown-toggle"
type="button" data-toggle="dropdown" aria-haspopup="true" aria-
expanded="false">Dropdown</button>
        <div class="dropdown-menu">
          <a class="dropdown-item" href="#">Action</a>
          <a class="dropdown-item" href="#">Another action</a>
          <a class="dropdown-item" href="#">Something else here</a>
          <div role="separator" class="dropdown-divider"></div>
          <a class="dropdown-item" href="#">Separated link</a>
        </div>
      </div>
      <input type="text" class="form-control" aria-label="Text input
with dropdown button">
    </div>
  </div>

  <script src="https://code.jquery.com/jquery-
3.3.1.slim.min.js"></script>
  <script
src="https://cdnjs.cloudflare.com/ajax/libs/popper.js/1.14.7/umd/popper
.min.js"></script>
  <script
src="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/js/bootstrap.mi
n.js"></script>
</body>
</html>
```