

# Uk3

Here we plot the correlation matrix and the first 3 eigenvectors of Uk3.

```
library('knitr')
```

```
## Warning: package 'knitr' was built under R version 3.2.5
```


```
knitr::opts_chunk$set(cache=TRUE)
#opts_chunk$set(fig.path = "/Users/sarahurbut/Dropbox/PaperEdits/Paper/ForNatureTechnicalReports/Figure")
covmat=readRDS("../Data_vhat/covmatwithvhat.rds")

z.stat=read.table("../Data/maxz.txt")
names=colnames(z.stat)
pis=readRDS("../Data_vhat/piswithvhat.rds")$pihat
pi.mat=matrix(pis[-length(pis)],ncol=54,nrow=22,byrow = T)

names=colnames(z.stat)
colnames(pi.mat)=c("ID","X'X","SVD","F1","F2","F3","F4","F5","SFA_Rank5",c(names,"ALL"))

barplot(colSums(pi.mat),main='WithVmat',las=2,cex.names=0.5)
```


## WithVmat



```
oldpis=readRDS("../Results_Data//piswithzero.rds")$pihat

pi.matold=matrix(oldpis[-length(oldpis)],ncol=54,nrow=22,byrow = T)
```

```
colnames(pi.matold)=c("ID","X'X","SVD","F1","F2","F3","F4","F5","SFA_Rank5",c(names,"ALL"))
barplot(colSums(pi.matold),main='OLD',las=2,cex.names=0.5)
```



```
library(gplots)
```

```
##
## Attaching package: 'gplots'

## The following object is masked from 'package:stats':
##
## lowess
```

```
library(ggplot2)
```

```
## Warning: package 'ggplot2' was built under R version 3.2.5
```

```
library('colorRamps')
#install.packages("fields")
library(fields)
```

```
## Warning: package 'fields' was built under R version 3.2.5
```

```
## Loading required package: spam
```

```
## Warning: package 'spam' was built under R version 3.2.5

## Loading required package: grid

## Spam version 1.4-0 (2016-08-29) is loaded.
## Type 'help( Spam)' or 'demo( spam)' for a short introduction
## and overview of this package.
## Help for individual functions is also obtained by adding the
## suffix '.spam' to the function name, e.g. 'help( chol.spam)'.

##
## Attaching package: 'spam'

## The following objects are masked from 'package:base':
##
##      backsolve, forwardsolve

## Loading required package: maps
```

```
## Warning: package 'maps' was built under R version 3.2.5
```

```
k=3
hclust.2=function (d, method = "average", members = NULL) {hclust(d, method, members)}
  x=cov2cor(covmat[[k]])
x[x<0]=0
  colnames(x)=names
  rownames(x)=names

h=read.table("../Analysis/uk3rowindices.txt")[,1]
```

Now we orduce the heatmap. Note that this is flipped in the paper:

```
smat=(x[(h),(h)])
smat[lower.tri(smat)] <- NA


library(lattice)
```

```
## Warning: package 'lattice' was built under R version 3.2.5
```

```
#print(levelplot(smat,col.regions = jet.colors,xlab = "",ylab = "",colorkey = TRUE))

#clrs <- colorRampPalette(rev(c("purple","#FC8D59","#FEE090","#FFFFBF","#E0F3F8","#91BFDB","#4575B4")))

clrs <- colorRampPalette(rev(c("#D73027","#FC8D59","#FEE090","#FFFFBF",
                             "#E0F3F8","#91BFDB","#4575B4")))(64)
#clrs[63:64] <- "darkviolet"
lat=x[rev(h),rev(h)]
lat[lower.tri(lat)] <- NA
print(levelplot(lat,col.regions = clrs,xlab = "",ylab = "",colorkey = TRUE))
```




Now let's do the eigenplots:

```
missing.tissues=c(7,8,19,20,24,25,31,34,37)
color.gtex=read.table("../Data/GTExColors.txt",sep = '\\t', comment.char = '\\')[-missing.tissues,]

k=3
vold=svd(covmat[[k]])$v;u=svd(covmat[[k]])$u

v=vold[h,]##shuffle so correct order
names=names[h]
color.gtex=color.gtex[h,]
for(j in 1:3){
  barplot(v[,j]/v[,j][which.max(abs(v[,j]))],names="",cex.names=0.5,las=2,main=paste0("EigenVector",j,"Uk"))
}
```

**EigenVector1Uk3**



**EigenVector3Uk3**

