Retrieving shift, personnel and drilled metre data from the CorePlan API

Status: draft for review. Last updated: 7 October 2026
This document is for Jitu at Recon Drilling. It describes the CorePlan API endpoints you need to retrieve employee names and shift presence, shift information and drilled metres, so your software can calculate site bonuses. It follows the call on 7 October 2026 where we agreed that the CorePlan API is the simplest option, because you only need to read data and not edit anything.
The authentication token instructions and the full CorePlan API documentation will be in the Recon Drilling API folder on SharePoint. This document is a short description of the endpoints you will use and how they fit together.

API access is part of the Enterprise package that Recon Drilling is on.

Before you start

All requests are GET requests and are read-only, so working directly against your live CorePlan account is fine. CorePlan does not have a separate sandbox server. If you later want to test something that writes data, we use the Gold Sands demo project in your own account.

- Base URL: https://www.coreplan.io/api/public/v1/
- Authentication: Test using the simple bearer token you will need to be setup as an Admin in CorePlan, The token set-up steps are in the SharePoint folder.
    - If you require more robust system to system authentication then we provide detail on hoe to set up OAuth2 client credentials. (Request a token from https://www.coreplan.io/api/oauth/token/ and send it as a Bearer token on each call. Tokens expire after about an hour, so use the expires_in value returned with the token to know when to request a new one.)
- Pagination: use pagination=cursor and page-size=1000 on list calls, then follow the next URL in each response until it is null.
- Rate limits: up to 20 requests per second and 600 per minute. If you exceed them you receive HTTP 429 with a Retry-After header. Wait that many seconds and retry.
- Timestamps are ISO 8601 in UTC with a trailing Z, for example 2026-10-01T00:00:00Z.

The endpoints at a glance

Three endpoints hold the shift data, and four reference endpoints turn the identifiers in that data into names.

What you need	Endpoint	Key fields
Shifts (a shift is a drilling plod)	/drilling-plods/	id, date, workshift, project_id, rig_id, status
Personnel present on each	/drilling-plods/people-present/	plod_id, person_id,

What you need	Endpoint	Key fields
shift		person_name, job_role, duration
Drilled metres	/drilling-plods/drilling-intervals/	plod_id, hole_id, type_id, depth_from, depth_to
Project names	/projects/	id, name
Rig names	/drilling-rigs/	id, name, type
Employee details	/people/	id, name, employee_id, employer, payroll_category, job_role
Drill types	/drill-types/	id, name, description, reference_name

Each list endpoint accepts updated_since, so on every run after the first you only fetch what changed since your last call. The people-present and drilling-intervals records both point back to their shift through plod_id.

Retrieve the shifts

Drilling plods are the shifts. Retrieve them for the period you are calculating, for example: https://www.coreplan.io/api/public/v1/drilling-plods/?updated_since=2026-10-01T00:00:00Z&pagination=cursor&page-size=1000
You can also filter by date, workshift (D for day, M for afternoon, N for night), project_id, rig_id and status. The date is the date the work was done, so filter out any shifts that fall outside your bonus period. A shift record looks like this:


```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "id": 1,
      "slug": "100211012D",
      "date": "20211012",
      "project_id": 1,
      "rig_id": 1,
      "contract_id": "a87fb69b-a118-45d2-a22e-50909091a706",
      "workshift": "D",
      "notes": "",
      "status": "client_approved",
      "created_by_id": 1,
      "updated_by_id": null,
      "created_at": "20211012T000000Z",
      "updated_at": "20211012T000000Z"
    }
```

```
  ]
}
```

The project_id and rig_id are identifiers only. Use the projects and rigs endpoints below to turn them into names.
The status field shows where the shift is in the approval process: supervisor_approval_pending, supervisor_approved, client_approval_pending, client_rejected, client_approved or invalid. You will need to decide which statuses should count towards bonuses. For example, you may want to ignore shifts that are still pending or invalid.

Retrieve the personnel present on each shift

This gives you the employees who worked each shift and for how long:
https://www.coreplan.io/api/public/v1/drilling-plods/people-present/?updated_since=2026-10-01T00:00:00Z&pagination=cursor&page-size=1000


```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "id": "3c1f0e52-8a4b-4d21-9a43-5e0b7a6d2f10",
      "plod_id": 1,
      "person_id": "9d2e6b14-0c57-4f3a-b8a1-72c4d1e5a0f3",
      "person_name": "Example Person",
      "job_role": "Driller",
      "duration": 43200,
      "sick_duration": 0,
      "travel_duration": 0,
      "notes": "",
      "created_at": "20211012T000000Z",
      "updated_at": "20211012T000000Z"
    }
  ]
}
```

The person_name field already gives you the employee name. For the employee number and other details, look up the person_id in the people endpoint below. Durations are in seconds, so divide by 3600 to get hours. The sick_duration and travel_duration fields are separate from duration.

Retrieve the drilled metres

Drilled metres come from drilling intervals. Each interval is a section drilled in one hole during one shift:
https://www.coreplan.io/api/public/v1/drilling-plods/drilling-intervals/?updated_since=2026-10-01T00:00:00Z&pagination=cursor&page-size=1000


```
{
  "count": 1,
```

```
  "next": null,
  "previous": null,
  "results": [
    {
      "id": "7d70f394-716a-4221-b986-2094d9e20652",
      "plod_id": 1,
      "hole_id": "52a0fefb-c37b-4b68-84fa-fc9f8dc65e63",
      "depth_from": "180.00",
      "depth_to": "210.00",
      "type_id": 1234,
      "end_of_hole": true,
      "duration": 14400,
      "notes": "",
      "created_at": "20211012T000000Z",
      "updated_at": "20211012T000000Z"
    }
  ]
}
```


The metres drilled in an interval are depth_to minus depth_from, which is 30 metres for the interval above. The depth values come back as text, so convert them to decimal numbers before subtracting. This endpoint does not carry the shift date, so join each interval to its shift using plod_id. The type_id is the drill type, which you can look up in the drill types endpoint below.

Look up the project names

https://www.coreplan.io/api/public/v1/projects/


```
[
  {
    "id": 1,
    "name": "Example Project",
    "reference_number": "EX-001",
    "is_active": true,
    "created_at": "20210101T000000Z",
    "updated_at": "20210101T000000Z"
  }
]
```


Use this to translate the project_id on each shift into a project name. The list is short, so you can retrieve it once per run.

Look up the rig names

https://www.coreplan.io/api/public/v1/drilling-rigs/


```
[
  {
    "id": 1,
    "name": "Example Rig 01",
```

```
    "type": "DD",
    "drill_company_id": 1,
    "is_active": true,
    "created_at": "20210101T000000Z",
    "updated_at": "20210101T000000Z"
  }
]
```

Use this to translate the rig_id on each shift into a rig name. The type field is the rig type, for example DD (diamond) or RC (reverse circulation). Add is_active=true if you only want active rigs.

Look up the employee details

https://www.coreplan.io/api/public/v1/people/?pagination=cursor&page-size=1000


```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
      "id": "9d2e6b14-0c57-4f3a-b8a1-72c4d1e5a0f3",
      "name": "Example Person",
      "job_role": "Driller",
      "employee_id": "E1234",
      "employer": "Example Employer",
      "payroll_category": "Example Category",
      "is_active": true,
      "location": "",
      "phone_number": "",
      "created_at": "20210101T000000Z",
      "updated_at": "20210101T000000Z"
    }
  ]
}
```

Match the id here to the person_id on each people-present record to get the employee number (employee_id), employer, payroll category and job role. Add is_active=true to list only current employees, and use updated_since after the first run to pick up changes.

Look up the drill types

https://www.coreplan.io/api/public/v1/drill-types/


```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    {
```

```
    "id": 1234,
    "name": "Example Drill Type",
    "description": "",
    "reference_name": "EX-DT",
    "rig_type": "DD",
    "created_at": "20210101T000000Z",
    "updated_at": "20210101T000000Z"
   }
  ]
}
```


Match the id here to the type_id on each drilling interval to get the drill type name. If your bonus rates differ by drill type, you can group the metres by this value. The reference_name field is a short code set in CorePlan that is useful for matching to your own categories.

Putting it together

1. Request an access token. (once off)
2. Retrieve the shifts (drilling plods) updated since your last run, and keep only those inside your bonus period and with the statuses you want to include.
3. Retrieve the people present and the drilling intervals updated since your last run.
4. Join the people present and the drilling intervals to their shift using plod_id.
5. Retrieve the reference lists (projects, rigs, people and drill types) and use them to turn project_id, rig_id, person_id and type_id into names and employee details.
6. For each shift, add up the metres (depth_to minus depth_from across its intervals, by drill type if needed) and list the personnel with their hours. This is the data your bonus calculation works from.
7. Store the time of this run and use it as updated_since next time.

Keeping your data up to date

CorePlan does not send notifications, so your software checks for changes on a schedule. Use updated_since to fetch only new and changed records. A shift or an entry can be edited after you have first retrieved it (for example when a supervisor corrects metres), so always overwrite your stored copy using the record id, and recalculate the affected bonuses.
Records that are deleted in CorePlan stop appearing in the normal lists. To find them, call the matching /deleted/ endpoint with deleted_since, for example /drilling-plods/deleted/, /drilling-plods/people-present/deleted/, /drilling-plods/drilling-intervals/deleted/, /people/deleted/ and /drill-types/deleted/, and remove those records from your copy.

A note on older endpoints

You may see similar endpoints under /plods/ and /rigs/, such as /plods/drilling-intervals/, /plods/people-present/ and /rigs/. These are older and deprecated. Please use the /drilling-plods/ and /drilling-rigs/ endpoints described above.

Questions

If anything is unclear once you have read this and the documentation in the SharePoint folder, send your questions to Simone, Derek or Yuri and we will get back to you.