





Comment	Description	Designator	Footprint	LibRef	Quantity
CAP CER 10uF/50V 5%	CAP CER 0.1uF/50V Ceramic Capacitor	C1 C2 CE	CAP CER 0.1uF/50V	CAP CER 0.1uF/50V	
0805	X7R 0805 (2012	C1, C3, C5	5%	5%	
	Metric) 10 ÂμF Molded				
	Tantalum Polymer				
TANT CAP 10uF/16V 5% 3528(B)	Capacitor 25 V 1411 (3528 Metric), 1210	C2	TANT CAP 3528(B)	TANT CAP 10uF/16V 5% 3528(B)	
	150mOhm			3.10 3320(b)	
	TCJB106M025R0150				
CAP CER 0.1uF/50V	CAP CER 0.1uF/50V Ceramic Capacitor		CAP CER 0.1uF/50V	CAP CER 0.1uF/50V	
5% 0805	X7R 0805 (2012	C4, C6, C7, C8, C9	5%	5%	
	Metric) Red 640nm LED				
LED-0805	Indication - Discrete				
	1.85V 0805 (2012 Metric)	D1, D2	LED-0805	LED-0805	
	APT2012SRCPRV				
Coroudiolo 2 7EmmD	SCREW HEAD DIA 4.5MM, SREW LEG	H1, H2, H3, H4	ScrewHole_3.75mmD	Coroudiolo 3 7EmmD	
ScrewHole_3.75mmD	DIA 3 MM	n I, nz, ns, n4	screwnore_s./smino	screwhole_s.7sminb	
	Bluetooth, WiFi				
ESP32-WROOM-32S	802.11b/g/n, Bluetooth v4.2 +EDR,				
	Class 1, 2 and 3	IC1	ESP32-WROOM-32S	ESP32-WROOM-32S	
	Transceiver Module 2.4GHz - 2.5GHz PCB				
	Trace Surface Mount				
	MOLEX,Screw Type, Horizontal, 5.08				
2 PIN Terminal Block Connector 5.08 mm	Pitch, 24-12 (AWG),	J1, J5		2 PIN Terminal Block	
	Terminal Block	31,33	Connector 5.08 mm	Connector 5.08 mm	
	Connector, TB007-508 02BE	<u></u>			
DUDGE E DIN 2.54-	MTSW-105-07-T-S-	12	RURGE 5 PIN	RURGE 5 PIN	
BURGE 5 PIN 2.54mm	048 BURGE 5 PIN 2.54mm	J2	BURGE 5 PIN	BURGE 5 PIN	
	Conn Unshrouded				
BURGE 4 PIN 2.54mm	Header HDR 4 POS 2.54mm Solder ST				
	Top Entry Thru-Hole	J3	BURGE 4 PIN 2.54mm	BURGE 4 PIN 2.54mm	
	Bulk TSW-104-17-G-S-				
	BOX HEADER MALE	J4	BOX HEADER MALE	BOX HEADER MALE	
8X2 2.54mm	8X2 2.54mm 16 pin Connector Header	-	8X2 2.54mm	8X2 2.54mm	
BURGE 2X2 PIN	Through Hole 4	16	BURGE 2X2 pin	4PIN BURGE	
	position 0.100	J6	DUNGE 2X2 pin	HEIN BUNGE	
	(2.54mm), 2X2 PIN RESISTOR, THICK				
	FILM, 10K, 5%, 0805,				
RES 0805 0E/0.25W	FRESISTOR, THICK FILM, 10K, 5%, 0805,	R1, R2, R3, R4, R5, R7, R11, R12, R13, R14,	RES 0805 10K/0.25W	RES 0805 10K/0.25W	
5%	FULL REEL Product	R11, R12, R13, R14, R15, R16	5%	5%	
	Range:PANASONIC - ERJ Series				
	RESISTOR, THICK				
RES 0805 470E/0.25W 9% RES 0805 10K/0.25W 9% RES 0805 220E/0.25W	FILM, 10K, 5%, 0805,				
	FRESISTOR, THICK FILM, 10K, 5%, 0805,	R6		RES 0805 10K/0.25W	
	FULL REEL Product		5%	5%	
	Range:PANASONIC - ERJ Series				
	RESISTOR, THICK				
	FILM, 10K, 5%, 0805, FRESISTOR, THICK				
	FILM, 10K, 5%, 0805,	R8, R9, R17, R18, R19, R20	RES 0805 10K/0.25W 5%	RES 0805 10K/0.25W 5%	
	FULL REEL Product	nzd	3.70	3.0	
	Range:PANASONIC - ERJ Series				
	RESISTOR, THICK				
	FILM, 10K, 5%, 0805, FRESISTOR, THICK				
	FILM, 10K, 5%, 0805,	R10	RES 0805 10K/0.25W 5%	RES 0805 10K/0.25W 5%	
	FULL REEL Product Range:PANASONIC -				
	ERJ Series				
	RESISTOR, THICK FILM, 10K, 5%, 0805,				
RES 0805 120E/0.25W	FRESISTOR, THICK		RES 0805 10K/0 25W	RES 0805 10K/0 25W	
5% RES 0805 20K/0.25W 5%	FILM, 10K, 5%, 0805,	R21	RES 0805 10K/0.25W 5%	RES 0805 10K/0.25W 5%	
	FULL REEL Product Range:PANASONIC -				
	ERJ Series				
	RESISTOR, THICK FILM, 10K, 5%, 0805,				
	FRESISTOR, THICK		RES 0805 10K/0.25W	RES 0805 10K/0.25W	
	FILM, 10K, 5%, 0805, FULL REEL Product	R22	5%	5%	
	Range:PANASONIC -				
	ERJ Series 6.1 x 3.7 mm, 2.5 mm				
	Actuator Height, 260				
PUSHBUTTON_SMD_6 1 x 3.7 mm, 2.5 mm	gf, Red, Surface	S1, S2	PUSHBUTTON_SMD_6	PUSHBUTTON_SMD_6	
	Mount, SPST, Tactile Switch, TS09-63-25-R-		.1 x 3.7 mm, 2.5 mm	.1 x 3.7 mm, 2.5 mm	
	260-SMT-TR				
Touch Points 1mm	Touch Points 0.75mm	TP1, TP2, TP4, TP8, TP10, TP12, TP_3.3V,	Touch Points 1mm	Touch Points	
Touch Points Imm	to1mm	TP_5V			
	MAX485CSA-RS- 485/RS-422	U1	MAN VADECCA	MAN VADECC *	
	485/RS-422 Transceivers, SOIC-8	UI	MAX485CSA	MAX485CSA	
LM1117IMPX-3.3V	LM1117IMPX-3.3V				
	800-mA 15-V linear	VR1	LM1117IMPX-3.3V	LM1117IMPX-3.3V	l
SOT-223	voltage regulator SOT		SOT-223	SOT-223	