

Slip17

Q.1) Read the current directory and display the name of the files, no of files in current directory

```
#include<stdio.h>
#include<stdlib.h>
#include<dirent.h>
#include<sys/stat.h>
#include<time.h>

int main()
{
    struct dirent *entry;
    DIR *dp;
    int count=0;
    dp=opendir(".");
    if(dp==NULL)
    {
        printf("not open");
    }
    else
    {
        while((entry=readdir(dp))!=NULL)
        {

            printf("\n name of file is : %s",entry->d_name);
            c++;

        }
        closedir(dp);
        printf("total file count is %d ",c);
    }
}
```

Q2)

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <sys/wait.h>

int main() {
    int fd[2];
    pid_t pid1, pid2;

    // Block Ctrl-C (SIGINT) and Ctrl-\ (SIGQUIT)
```

```

signal(SIGINT, SIG_IGN);
signal(SIGQUIT, SIG_IGN);

if (pipe(fd) == -1) {
    perror("pipe");
    exit(1);
}

pid1 = fork();
if (pid1 < 0) {
    perror("fork");
    exit(1);
}

if (pid1 == 0) {
    // ----- First Child: executes ls -l -----
    close(fd[0]); // Close read end
    dup2(fd[1], STDOUT_FILENO); // Redirect stdout → pipe write end
    close(fd[1]);

    execlp("ls", "ls", "-l", NULL);
    perror("execlp ls");
    exit(1);
}

pid2 = fork();
if (pid2 < 0) {
    perror("fork");
    exit(1);
}

if (pid2 == 0) {
    // ----- Second Child: executes wc -l -----
    close(fd[1]); // Close write end
    dup2(fd[0], STDIN_FILENO); // Redirect stdin ← pipe read end
    close(fd[0]);

    execlp("wc", "wc", "-l", NULL);
    perror("execlp wc");
    exit(1);
}

// ----- Parent -----
close(fd[0]);
close(fd[1]);

// Wait for both children
wait(NULL);

```

```
    wait(NULL);  
    return 0;  
}
```