

TECHNICAL DATA SHEET

BRSVR — Clay Viscosity Reducer

Clay Stripper and Clay-Dispersing Solution for Drilling Fluids

1. Product Description

BRSVR is a liquid drilling-mud additive specially formulated as an engineering mud aid for clayey and highly cohesive clay formations. It is suitable for directional drilling, pipe jacking, shield tunneling, and general drilling operations.

2. Main Functions

1. Disperses clay and prevents clay from sticking to and blinding the drill bit.
2. Rapidly reduces construction torque in clay formations.
3. Reduces the internal forces of the clay system, improves drilling efficiency, and stabilizes the boreholes.
4. Prevents bit balling and pipe sticking.



3. Composition

Chemical characterization: Mixture.

Component	Content (% by weight)
VAE emulsion	27.69
Styrene-acrylic emulsion	44.16
Methyl methacrylate	4.10
Composite dispersant	0.30
Emulsifier	0.20
Film-forming aid (coalescent)	2.00
Composite defoamer	0.30
Sodium persulfate	5.30
Composite thickener	1.50
Water	14.05

4. Physical and Chemical Properties

Property	Value
Appearance	Viscous liquid
Odor	Odorless

Property	Value
Molecular formula	Unknown
pH	Alkaline
Relative density	1.2–1.4 g/cm ³
Upper explosion limit	None
Lower explosion limit	None
Solubility	Readily soluble in water

5. Directions for Use

Application: Add this product directly into clean water, stir until fully dispersed, and then inject the solution into the clay formation.

Dosage: Add 0.5–2.0 kg of BRSVR per cubic meter of clean water. Use a higher dosage at the beginning of the operation; the dosage may be reduced appropriately once the torque has decreased.

6. Precautions

If this product accidentally comes into contact with skin or eyes during use, immediately rinse the affected area with plenty of clean water.

7. Packaging, Storage and Transport

Packaging: 25 kg per plastic drum.

Storage: Store in a cool, well-ventilated, and dry place. Avoid prolonged exposure to direct sunlight.

Transport: Not regulated as a dangerous good for transport. Handle packages gently to prevent damage to the containers.

8. Supplier Information

Manufacturer / Supplier: Brighter Star Drilling Fluids

Website: www.pcenigeria.com

9. Disclaimer

All data, recommendations, and information contained in this Technical Data Sheet are provided for reference only. They are derived from laboratory testing and field experience obtained under specific conditions, and actual product performance may vary with formation characteristics, water quality, equipment, and operating practices. Users are advised to verify the suitability of this product through on-site trials and to adjust the dosage according to actual working conditions. In all cases, the actual conditions and results of use shall prevail.

To the fullest extent permitted by applicable law, Brighter Star Drilling Fluids makes no warranties, express or implied, regarding the information herein, and assumes no responsibility or liability for any results, losses, or damages arising from the use of, or reliance on, this Technical Data Sheet. For health and safety information, please refer to the Safety Data Sheet (SDS) of this product.