

TABLE OF CONTENTS

ABSTRACT

SUPPLY NETWORK

ASSUMPTIONS

PARAMETERS

CALCULATIONS

RESULTS

CONCLUSION & RECOMMENDATIONS

ABSTRACT

- This is an Industrial Engineering graduate student case study and project supporting production of a biofuel company in the state of Texas, USA.
- With a purpose to minimize the investment and transportation costs by finding the optimal number of hubs and plants (biorefineries) that the company needs to install as well as the network between suppliers-hubs and hubs-plants.
- Using Python and its Linear Programming modeler (PuLP) for data analysis and optimization, as well as Tableau for data visualization to provide optimal results and suggest recommendations.


SUPPLY NETWORK




254 County Suppliers 1303 Potential Hubs

167
Potential
Biorefineries


Supply by County



Potential Hubs



Potential Plants



ASSUMPTIONS

- The centroid of the county is considered as the county supplier
- Road and Rail distances are not accounted for since they correlate with the costs
- 2nd Law of Thermodynamics is ignored since there is no energy loss from Biomass conversion to liters
- Cleaned data errors and redundancies are considered as supply, production, and policy issues

PARAMATERS

HUB PARAMETERS		
Investment cost	\$ 3,476,219	
Preprocessing capacity	300,000 Mg	
PLANT PARAMETERS		
Investment cost	\$ 130,956,797	
Annual conversion capacity	152,063,705 liters	
Conversion yield	232 liters/Mg	
DEMAND		
Network demand	1,476,310,602 liters	

Note: All the parameters are considered for a period of time of one year.

CALCULATIONS

From the datasets and parameters:

Total Supply = 3,053,377.71 Mg

Demand in Mg = Network demand in liters / Conversion yield

= 1,476,310,602 liters / 232 liters/Mg

= 6,363,407.77 Mg

Since the demand supersedes the total supply, a third-party supplier is to be introduced:

3rd party Supply = Demand - Total Supply = 3,310,030.06 Mg

CALCULATIONS


- The Average Road Cost is used as the estimated 3rd party cost per unit
 - = \$ 30,488,893.10 / 330,962 = \$92.122 \approx \$92
- Number of plants to meet demand
 - = Demand / Annual Conversion Capacity = 9.7085 ≈ 10 plants
- Total Plant Investment Cost = $10 \times $130,956,797 = $1,309,567,970$
- Number of hubs to meet plant requirement
 - = Demand / Hub Capacity = 21.21 ≈ 22 hubs
- Total Hub Investment Cost = $22 \times 3,476,219 = 76,476,818$

RESULTS


	hub_status	road_supply
hubs		
512	1.0	300000.000
17246	1.0	300000.000
17318	1.0	300000.000
17387	1.0	300000.000
17399	1.0	300000.000
17482	1.0	300000.000
17517	1.0	300000.000
17623	1.0	300000.000
17695	1.0	63407.767
17850	1.0	300000.000
17886	1.0	300000.000
17909	1.0	300000.000
17969	1.0	300000.000
18006	1.0	300000.000
18012	1.0	300000.000
18097	1.0	300000.000
18103	1.0	300000.000
18119	1.0	300000.000
18255	1.0	300000.000
18264	1.0	300000.000
18307	1.0	300000.000
18483	1.0	300000.000

	plt_status	rail_supply
plants		
543	1.0	655447.00
9088	1.0	655447.00
9091	1.0	655447.00
9104	1.0	655447.00
9142	1.0	655447.00
9167	1.0	464384.73
9188	1.0	655447.00
9203	1.0	655447.00
10060	1.0	655447.00
10061	1.0	655447.00
		1


Optimal Hubs and Plants




South East Map




East Map




North Map



West Map



South Map



CONCLUSION & RECOMMENDATIONS

- The optimal number of 22 hubs and 10 plants were obtained for an overall network (investment and transportation) cost of \$1,725,868,653,500
- With 0.025% and 0.215% error rate from the TX_roads and TX_railroad datasets these results were retrieved, but with more accurate data better results would have been reached.