

sixth EDITION

SIMULATION with Arena

W. David Kelton

Randall P. Sadowski

Nancy B. Zupick

Modeling Basic Operations and Inputs

Chapter 4

Last revision December 22, 2013


What We'll Do ...

- **Model 4-1: Electronic assembly/test system**
 - Modeling approaches
 - New Arena modules (Decide, Record)
- **Model 4-2: Enhanced electronic assembly/test**
 - Resource Schedules, States, and Failures
 - Frequency outputs
 - More on utilizations
- **Model 4-3: Enhancing the animation**
 - Queues, Entity Pictures, Resource Pictures
 - Adding Plots and Variables

What We'll Do ... (cont'd.)

- **Model 4-4: Adding entity travel times**
 - Stations, Transfers, Routes, animation of entity movement
- **Finding and fixing model errors**
- **Input analysis**
 - Specifying input distributions, parameters
 - Deterministic vs. random input
 - Collecting and using data
 - Fitting input distributions via Arena Input Analyzer
 - No data?
 - Nonstationary arrival processes
 - Multivariate and correlated input data

Electronic Assembly/Test System (Model 4-1)



- Produce two different sealed elect. units (A, B)
- Arriving parts: cast metal cases machined to accept electronic parts
- Part A, Part B – separate prep areas
- Both go to Sealer for assembly, testing – then to Shipping (out) if OK, or else to Rework
- Rework – Salvaged (and Shipped), or Scrapped

Part A

- **Interarrivals: expo (5) min.**
- **From arrival point, go immediately to Part A Prep**
 - Process = (machine + deburr + clean) ~ tria (1, 4, 8) min.
- **Go immediately to Sealer**
 - Process = (assemble + test) ~ tria (1, 3, 4) min.
 - 91% pass (i.e, 0.91 probability independently for each part), go to Shipped; Else go to Rework
- **Rework: (re-process + testing) ~ expo (45) min.**
 - 80% pass (i.e, 0.80 probability independently for each part), go to Salvaged; Else go to Scrapped

Part B

- Interarrivals: **batches** of 4, expo (30) min.
- Upon arrival, batch breaks into 4 individual parts
- Proceed immediately to Part B Prep area
 - Process = (machine + deburr + clean) ~ tria (3, 5, 10)
- Go to Sealer
 - Process = (assemble + test) ~ weib (2.5, 5.3) min. , **different** from Part A, though at same station
 - 91% pass, go to Shipped; Else go to Rework
- Rework: (re-process + test) = expo (45) min.
 - 80% pass (i.e, 0.80 probability independently for each part), go to Salvaged; Else go to Scrapped


Run Conditions, Output

- **Start empty & idle, run for 32 hours**
- **Collect statistics for each work area on**
 - Resource utilization
 - Number in queue
 - Time in queue
- **For each exit point (Shipped, Salvaged, Scrapped), collect total time in system (a.k.a. cycle time)**

Developing a Modeling Approach

- Define pieces of model, modules, data structures, control logic
- Appropriate level of detail – judgment call
- Often multiple ways to model, represent logic
- This model:
 - Entities are individual parts (two types)
 - Separate Create modules for two part types
 - Separate Process modules for each Prep area
 - Process modules for Sealer and Rework, each followed by a Decide module (2-way by Chance)
 - Depart modules for Shipped, Salvaged, Scrapped
 - Attribute **Sealer Time** assigned after Creates in Assign modules (parts have *different* times at *the* Sealer)
 - Record modules just before Departs for time in system

Building Model

- **New model window**
- **Attach Basic Process panel (if needed)**
- **Place modules**
 - Create (× 2)
 - Assign (× 2)
 - Process (× 4)
 - Decide (× 2)
 - Record (× 3)
 - Dispose (× 3)
- **Right click — repeat last action (place module)**
- **Auto-Connect, or manually connect via** 

*Alternate strategy –
place one module at a
time, fill it out completely*

Part A Create Module

- **Name: Part A Arrive**
- **Entity Type: Part A**
- **Time Between Arrivals**
 - **Type: Random (Expo)**
 - Pull-down list with options
 - **Value: 5**
 - **Units: Minutes**
 - Pull-down list with options
- **Default what's not mentioned above**

Once these entries are made, they are placed on list for names of that type (Module Name, Entity Type, etc.) and will appear on future pull-down lists for that type of name.

Part B Create Module

- **Name: Part B Arrive**
- **Entity Type: Part B**
- **Time Between Arrivals**
 - **Type: Random (Expo)**
 - Pull-down list with options
 - **Value: 30**
 - **Units: Minutes**
 - Pull-down list with options
- **Entities per Arrival: 4**

Part A Attributes Assign Module

- **Name:** Assign Part A Sealer and Arrive Time
- **Add button:**
 - Type: **Attribute**
 - Attribute Name: **Sealer Time**
 - New Value: **TRIA(1, 3, 4)**
- **Add button:**
 - Type: **Attribute**
 - Attribute Name: **Arrive Time**
 - New Value: **TNOW** (to compute time in system on exit)

*TNOW is internal Arena variable name for simulation clock; see
Help > Arena Help > Contents > Variables, Functions, and Distributions > Variables >
Date and Time Variables*

Part B Attributes Assign Module

- **Name:** Assign Part B Sealer and Arrive Time
- **Add button:**
 - Type: **Attribute**
 - Attribute Name: **Sealer Time**
 - New Value: **WEIB (2.5, 5.3)**
- **Add button:**
 - Type: **Attribute**
 - Attribute Name: **Arrive Time**
 - New Value: **TNOW**

Names for things in Arena

- *Default names usually suggested*
- *Names placed on appropriate pull-down lists for future reference*
- *All names in a model must be unique (even across different kinds of objects)*

Prep A Process Module

- **Name: Prep A Process**
- **Action: Seize Delay Release**
- **Resources subdialog (Add button):**
 - Type: **Resource** (a pull-down option)
 - Resource Name: **Prep A**
 - Quantity: 1 (default)
- **Delay Type: Triangular**
- **Units: Minutes**
- **Minimum: 1**
- **Value (Most Likely): 4**
- **Maximum: 8**

If several Resources were named (Add button), entity would have to Seize them all before Delay could start.

Prep B Process Module

- **Name: Prep B Process**
- **Action: Seize Delay Release**
- **Resources subdialog (Add button):**
 - Type: **Resource** (a pull-down option)
 - Resource Name: **Prep B**
 - Quantity: 1 (default)
- **Delay Type: Triangular**
- **Units: Minutes**
- **Minimum: 3**
- **Value (Most Likely): 5**
- **Maximum: 10**

Sealer Process Module

- **Name: Sealer Process**
- **Action: Seize Delay Release**
- **Resources subdialog (Add button):**
 - Type: **Resource** (a pull-down option)
 - Resource Name: **Sealer**
 - Quantity: **1** (default)
- **Delay Type: Expression**
- **Units: Minutes**
- **Expression: Sealer Time**

Recall – Sealer Time attribute was defined upstream for both Parts A and B ... now its value is being used ... allows for different distributions for A and B.

Sealer Inspection-Result *Decide* Module

- **Decide module provides branch points**
 - *By Condition* (entity Attributes, global Variables)
 - *By Chance* (multi-sided, possibly-biased hypercoin flip)
- **Name: Failed Sealer Inspection**
- **Type: 2-way by Chance (default)**
- **Percent True: 9**
- **Different exit points for True, False results – connect appropriately downstream**

- *Note it's **percent** true, not **probability** of true ... so “9” means probability of 0.09*
- *We arbitrarily decided “true” meant part failed inspection ... could have reversed (but would change numerical results ... why? ... does this upset you? ... why?)*
- *This is a rich, deep, versatile module ... explore its Help button*

Rework Process Module

- **Name: Rework Process**
- **Action: Seize Delay Release**
- **Resources subdialog (Add button):**
 - Type: **Resource** (a pull-down option)
 - Resource Name: **Rework**
 - Quantity: 1 (default)
- **Delay Type: Expression**
- **Units: Minutes**
- **Expression: EXPO (45)**

*Had to use general **Expression** choice for Delay Type since what we want (**EXPO**) is not directly on Delay Type pull-down list.*

Rework Inspection-Result Decide Module

- **Name: Failed Rework Inspection**
- **Type: 2-way by Chance (default)**
- **Percent True: 20**

*We arbitrarily decided “true”
meant part failed inspection*

Record Modules

- **Arena collects and reports many output statistics by default, but sometimes not all you want**
- **Want time in system (avg, max) of parts sorted by their exit point (Shipped, Salvaged, Scrapped)**
 - It's this sorting that Arena doesn't do by default ... it would automatically sort *by Entity Type* if we had Entities checked in *Run > Setup > Project Parameters* (which we don't)
- **Record module can be placed in flowchart to collect and report various kinds of statistics from within model run as entities pass through it**
- **For Tally-type output performance measures**

Shipped Parts *Record* Module

- **Name: Record Shipped Parts**
- **Type: Time Interval**
 - Records time elapsed up to now (**TNOW**) from when an entity attribute was marked with a time “stamp” upstream ... Attribute Name is below ...
 - There are several other options for Type ... explore via Record module’s Help button!
- **Attribute Name: Arrive Time**
 - Was defined upstream as clock value in Assign modules instantly after each entity was Created
- **Tally Name: Record Shipped Parts**
 - Determines label in reports

Other two Record modules – just like this except for Name and Tally Name.

Dispose Modules

- **Three separate exit points for three separate part disposition (Shipped, Salvaged, Scrapped)**
- **Could have directed all three exit types to a single Dispose module**
 - Separate ones gets animation counts of three dispositions
 - Separate Dispose modules allows for differentially checking boxes to Record Entity Statistics
 - Produces flow statistics separated by entity type (*if Entities Statistics Collection is checked in Run > Setup > Project Parameters*), *not* by final disposition of part ... so we *did* need our Record modules and Arrive Time attribute






Run > Setup for Run Control

- **Without this, model would run forever – no defaults for termination rule**
 - That's part of modeling, and generally affects results!
- **Project Parameters tab:**
 - Fill in Project Title, Analyst Name
 - Defaults for Statistics Collection, but we cleared check box for Entities
 - Not needed for what we want (we installed our own Record modules), and would slow execution
- **Replication Parameters tab:**
 - Replication length: **32**, accept **Hours** default for Time Units
 - Base Time Units: **Minutes** for inputs without Time Units option, internal arithmetic, and units on output reports

Different Part A, B Entity Pictures

- Entity data module (just single-click on it in Project Bar, edit via spreadsheet only)
- Row for each Entity Type (Part A, Part B)
- Pull down Initial Picture pull-down menu, select different pictures for each Entity Type
 - *Edit > Entity Pictures* to see, change list of pictures that's presented here ... more later

Running Model

- **Check**  (if desired)
 - Find button to help find errors
- **Go**  (**will automatically pre-Check if needed**)
 - Some graphics don't show during run ... will return when you End your run ... control via *View > Layers*
 - Status Bar shows run progress – replication number, simulation time, simulation status
- **Animation speed**
 - Slider bar at top, or increase (> key), decrease (< key)
- **Pause** (||) or **Esc** key;  **to resume**
- **Run > Step** () to debug
- **Run > Fast-Forward** () to turn off animation
 - *Run > Run Control > Batch Run (No Animation)* is fastest

Viewing Results

- **Counters during animation for modules**
 - Create, Dispose, Decide – incremented when entity leaves
 - Process – number of entities currently in module
- **Asked at end if you want to see reports**
 - What you get depends on *Run> Setup> Project Parameters*
 - Looks like Rework area is bottleneck ... more later
 - Navigate through report with browsing arrows, tree at left
 - Tally, Time-Persistent, and Counter statistics
 - Avg, Min, Max, and 95% Confidence Interval half-widths
 - Confidence intervals are for steady-state expectations ... Chapter 7
 - May not be produced if run is not long enough for reliable stats
- **Generally difficult/unreliable to draw conclusions from just one run ... more later**

Model 4-2: Enhanced Electronic Assembly and Test System

- **Original model shown to production manager**
 - Pointed out that this is only first shift of a two-shift day — on second shift there are two operators at Rework (bottleneck station) ... 16-hour days
 - Pointed out that Sealer fails sometimes
 - Uptimes ~ expo (2) hours
 - Repair times ~ expo (4) min.
 - Wants to buy racks to hold rework queue
 - A rack holds 10 parts
 - How many racks should be bought?
 - Run for 10 days (16-hour days)
- **Need: *Resource Schedules, Resource States, Resource Failures***

Run Conditions

- **Redefine a “day” to be 16 hours – *Run > Setup > Replication Parameters***
- **Change Replication Length to 10 (of these) days**

Schedules

- **Vary Capacity (no. units) of a resource over time**
- **In Resource Data module (spreadsheet view)**
 - For Rework Resource, change Type from **Fixed Capacity** to **Based on Schedule**
 - Two new columns – Schedule Name and Schedule Rule
 - Type in a Schedule Name (**Rework Schedule**)
 - Select a Schedule Rule – details of capacity decrease if Resource is allocated to an entity
 - *Wait* – Capacity decrease waits until entity releases Resource, and “break” will be full but maybe start/end late
 - *Ignore* – Capacity goes down immediately for stat collection, but work goes on until finished ... “break” could be shorter or gone
 - *Preempt* – Processing is interrupted, resumed at end of “break”

Schedules (cont'd.)

- **Define actual Schedule that Resource will follow**
 - **Schedule data module**
 - Row already there since we defined **Rework Schedule**
 - Format Type is Duration for entries based on elapsed time past simulation start time
 - Type is Capacity, for Resource schedule (more later on Arrival Type)
 - Click in Durations column, get Graphical Schedule Editor
 - X-axis is time, Y-axis is Resource Capacity
 - Click and drag to define graph
 - Options button to control axis scaling, time slots in editor, whether schedule loops or stays at a final level forever
 - Can use Graphical Schedule Editor only if time durations are integers, with no Variables or Expressions involved

Schedules (cont'd.)

- Alternatively, right-click in row, select Edit via Dialog
 - Enter schedule Name
 - Enter pairs for Capacity, Duration ... as many pairs as needed
 - If all durations are specified, schedule repeats forever
 - If any duration is empty, it defaults to infinity
 - *Can* involve Variables, Expressions
- Another alternative – right-click in row, select Edit via Spreadsheet
 - Enter capacity Value, Duration pairs

Resource Failures

- Usually for unplanned, random downtimes
- Can start definition in Resource or Failure module (Advanced Process panel) ... we'll start in Failure
- Attach Advanced Process panel if needed, single-click on Failure, get spreadsheet view
- To create new Failure, double-click – add new row
- Name the Failure
- Type – Time-based, Count-based (we'll do Time)
- Specify Up Time, Down Time, with Units for both

Resource Failures (cont'd.)

- **Attach this Failure to correct Resource**
 - Resource module, Failures column, Sealer row – click
 - Get pop-up Failures window, pick Failure Name **Sealer Failure** from pull-down list
 - Choose Failure Rule from **Wait**, **Ignore**, **Preempt** (as in Schedules)
- **Can have multiple Failures (separate names) acting on a resource**
- **Can re-use defined Failures for multiple Resources (operate independently if they involve random variables)**

Frequencies

- **Record time-persistent occurrence frequency of variable, expression, or resource state**
 - Use here to record % of time rework queue is of length 0, (0, 10], (10, 20], ... for info on number of racks needed
- **Statistic data module (Advanced Process panel)**
 - Five Types of statistics, of which Frequencies is one
 - Specify Name (**Rework Queue Stats**), Frequency Type (**Value**)
 - Specify Expression to track and categorize
 - Right-click in field to get to Expression Builder
 - Report Label (**Rework Queue Stats**)
 - Pop-up secondary spreadsheet for Categories (browse file)

Frequencies (cont'd.)

- **Add another Frequency (in Statistic module) to give a finer description of Sealer states**
 - Produces statistics on proportion of time Sealer is in each of its *three* possible states – Busy, Idle, and Failed
- **Frequencies are not part of default Category Overview report**
 - Open Frequencies report from Project Bar (get separate window)

Results of Model 4-2

- **Differ from those of Model 4-1 since this is a longer run, modeling assumptions are different**
 - All of which causes underlying random-number stream to be used differently (Chapter 12)
- **Prep A/B didn't change (other than run length and random variation) ... need statistical analysis of simulation output (Chapters 6, 7, 12)**
- **Sealer is more congested (it now fails)**
- **Rework is less congested (50% higher staffing)**
- **Frequencies report suggests one rack suffices about 95% of the time, two racks all the time**
 - Standard vs. Restricted Percents – see text

Utilizations – Fine Points

- **Two utilizations reported for each Resource**
 - *Instantaneous Utilization* is time-average of ratio of number of units that are busy to number of units that are scheduled
 - By definition, counts periods when zero units are scheduled as zero-utilization periods
 - *Scheduled Utilization* is average number busy divided by average number available
 - No division-by-zero problem, assuming there were ever any units of Resource scheduled at all (if not, it shouldn't be in model)
- **Identical for fixed-capacity Resource**
- **Can differ for Resources on a variable Schedule**
 - If Resource capacity varies among several different positive values, it's better to use Scheduled Utilization
 - More issues, even finer points – see text

Model 4-3: Enhancing the Animation

- **Get “Spartan” generic default animation for some things (queues, connector-animation movement)**
 - Usually sufficient for verification, validation
- **Often want to customize, enhance it a bit**
 - More realism, impact
- **Pull animation away from logic in model window**
 - Useful for big models, complex animation
 - Named Views for model logic, animation, or close-ups
- **Default animation objects are connected to model logic and move with the module**
 - Identifiers, physical location (Shift-drag to decouple)


Changing Animation Queues

- **Lengthen (click, drag, maybe hold shift) to “hold” more entities**
 - Simulation logic, results OK if animated queue overflows
- **Rotate to re-orient for realism**
- **Change “form” of queue from *Line* (default) to *Point* — fixed places for entities**
 - Double-click on queue
 - Select Type to be Point
 - Click Points... button
 - Successively click Add for points, then OK
 - Drag them around on screen
 - *Check* Rotate box to show entities turning


Changing Entity Pictures

- **Earlier – used Entity data module to assign different Initial Pictures to different Entity Types**
- **Can customize list, alter pictures in it**
 - *Edit > Entity Pictures*
 - Left column – names, pictures currently on list
 - Right column –picture libraries (.plb filename extension)
 - Add a hand-drawn picture – Add button on left, name it in Value field at top, double-click on blank depressed button, then artwork (or paste in a copied graphics image)
 - New name won't appear in Entity data module until you type it there
 - Edit an existing picture – double-click, artwork
 - Copy a picture over from picture library

Adding Resource Pictures

- **Animate a Resource – Resource button  in animate toolbar – get Resource Picture Placement window**
- **Left column – default pictures for different Resource states**
 - Attach logically to a Resource by Identifier pull-down list
 - Double-click to edit artwork by hand, or paste in previously copied graphics images
 - Seize area – where seizing entity will “reside”
 - Multiple seize areas for multi-capacity Resources
- **Right column – picture libraries (.plb files) – can copy over to selected (depressed) state pictures**
- **Accept window, cross hairs, click to place**
 - Resize, reposition later


Adding Variables and Plots

- **Variable animation – just show a value of something as a number, watch it change**
 - Variable object  from Animate toolbar
 - Double-click, specify Expression to be shown (Expression Builder), and cosmetics
 - Resize, reposition later
- **Dynamic animated plots – Chapter 3**
- **Other animation objects from Animate toolbar**
 - Clock (TNOW), variety of formats
 - Level (thermometer) animation
 - Others discussed later

Model 4-4: Electronic Assembly and Test System with Part Transfers

- **Generalize Model 4-3**
- **All part transfers now take 2 minutes (not instant)**
 - Model, animate this
 - Materially changes model logic, results
 - Two-minute transfer times for:
 - Arriving parts to prep areas
 - Departing parts to appropriate exit
 - All internal part transfers
 - Transfers take two minutes regardless of distance
 - Fix this (unrealistic) assumption in Chapter 8

New Arena Constructs

- ***Station*** – location where some process occurs
 - Arrivals, manufacturing cells, departures
 - Each Station given a unique name
 - Can serve as an entry point for a section of model logic
 - *Station marker*  represents a logical station in flowchart/animation
- ***Station Transfer*** – entities move between Stations without direct connection
 - Several different types – we'll use *Routes* here, which allow for positive transfer time, but no other delays like “room” on transitway or transporters
 - *Route paths* represent Routes in flowchart/animation

Adding Route Logic – From Arrival

- **Stations and Station Transfers affect both model logic and animation**
- **Start with Model 4-3 ... change to Model 4-4**
- **For incoming parts (A and B) delete connection from Assign modules to “Prep” Process modules**
 - Replace with Station/Route module pairs
 - Station module (Advanced Transfer panel) – define entity's location
Module Name vs. Station Name
 - Route module (Advanced Transfer panel) – send entity out
Route Time, Destination Station
 - No direct connections exiting from Route modules – Route module's Destination Station Name defines that


Adding Remaining Route Logic

- **Add Station modules for entry to each Prep area**
 - Station names are `Prep A Station`, `Prep B Station`, and are destination stations for Routes after arrivals
- **Process modules for Prep A, Prep B unchanged**
- **After prep, entities connected to Route module to send to next station (sealer)**
 - Don't need a separate Station module for outgoing side
- **Similar changes for rest of model**
 - Station modules for incoming parts into sealer, rework, each of three Record modules (entity exit points)
 - Route modules for outgoing parts out of sealer inspection, rework inspection (two for each Decide module – pass/fail)
- **Could run model now, get correct results ... but no animation of transfers ...**


Why Not Just Add Delays?

- **Simpler way to get two-minute transfer times:**
 - Insert a Process module with Action = Delay for 2 minutes on each relevant connection
 - Or, use Delay module from Advanced Process panel
- **This *would* work from modeling, numerical-output viewpoints**
- **But would not allow animation of part transfers, so we'll proceed with Stations and Routes**

Altering Animation – Stations

- **Add animation for Stations and Routes**
- **Station button , Animate Transfer toolbar**
 - Attach Identifier to it from pull-down list of station names
 - Get cross hairs, place (click) marker in animation
 - Can place several station markers for same logical station (e.g., to represent incoming, outgoing sides)
 - Can drag station markers around later

Altering Animation – Routes

- **Route button**  **from Animate Transfer toolbar**
 - Options for appearance of entities as they travel route
 - Get cross hairs; click in origin, destination Station Markers
 - Intermediate clicks for corners along route
 - Can drag around endpoints, corners later
 - Alternatively, use Route animation to create both Station markers and Route animation
 - Click for beginning Station marker
 - Intermediate clicks for route corners
 - Double-click for ending Station marker
 - Then go back and double-click on the two Station markers to define their logical Identifiers

Altering Animation – Entity Pictures

- **Part B arrivals are in batches of four parts/batch**
 - But constant travel time to Prep B implies they travel “on top of each other” so it looks like just one part B
 - Try – change Route time from 2 to **EXPO (2)**, see separation along route
- **Create a dishonest illusion to animate batch**
 - Assign module just after **Part B Arrive**
 - Add assignment of Entity Picture to **Picture.Batch B**
 - *Edit > Entity Pictures* to draw new picture
 - Copy **Picture.Part B** and rename it **Picture.Batch B**
 - Double-click on picture, use Picture Editor to get four circles
 - When batch arrives to Prep B, change to single circle
 - Add Assign module after **Prep B Arrival Station**

Finding and Fixing Model Errors

- **If error prevents model from running, Arena will try to detect and lead you to it in Check or Run**
 - Undefined (or inconsistently spelled) Variables, Attributes, Resources
 - Unconnected modules
 - Duplicate names
 - Examples – see text
- **Highlight Active Module – selects active module during run animation**
- ***View > Layers* while running – change what shows during run animation**

Finding and Fixing Model Errors (cont'd.)

- **Module Break – stop when entity reaches module**
- **Debug Bar**
 - *View > Debug Bar*
 - Breakpoints, Calendar, Active Entity, Watch
 - Run Controller
 - Examples – see text

Input Analysis: Specifying Model Parameters, Distributions

- **Structural** modeling: what we've done so far
 - Logical aspects – entities, resources, paths, etc.
- **Quantitative** modeling
 - Numerical, distributional specifications
 - Like structural modeling, need to observe system's operation, take data if possible

Deterministic vs. Random Inputs

- ***Deterministic***: nonrandom, fixed values
 - Number of units of a resource
 - Entity transfer time (?)
 - Interarrival, processing times (?)
- ***Random*** (a.k.a. ***stochastic***): model as a distribution, “draw” or “generate” values from to drive simulation
 - Transfer, Interarrival, Processing times
 - What distribution? What distributional parameters?
 - Causes simulation output to be random, too
- **Don't just assume randomness away – validity**

Collecting Data

- **Generally hard, expensive, frustrating, boring**
 - System might not exist
 - Data available on wrong things – might have to change model according to what's available
 - Incomplete, “dirty” data
 - Too much data (!)
- **Sensitivity of outputs to uncertainty in inputs**
- **Match model detail to quality of data**
- **Cost – should be budgeted in project**
- **Capture variability in data – model validity**
- **Garbage In, Garbage Out (GIGO)**

Using Data: Alternatives and Issues

- **Use data “directly” in simulation**
 - Read actual observed values to drive model inputs (interarrivals, service times, part types, ...)
 - Arena ReadWrite module ... see Model 10-2
 - All values will be “legal” and realistic
 - But can never go outside your observed data
 - May not have enough data for long or many runs
 - Computationally slow (reading disk files)
- **Or, fit probability distribution to data**
 - “Draw” or “generate” synthetic observations from this distribution to drive model inputs
 - We’ve done it this way so far
 - Can go beyond observed data (good and bad)
 - May not get a good “fit” to data – validity?



Fitting Distributions to Data with Arena Input Analyzer

- **Assume:**
 - Have sample data: Independent and Identically Distributed (IID) list of observed values from actual physical system
 - Want to select or fit a probability distribution for use in generating inputs for simulation model
- **Arena Input Analyzer**
 - Separate application, also via Tools menu in Arena
 - Fits distributions, gives valid Arena expression for generation to paste directly into simulation model

Fitting Distributions to Data with Arena Input Analyzer (cont'd.)

- **Fitting = deciding on distribution form (exponential, gamma, empirical, etc.) and estimating its parameters**
 - Several different methods (Maximum likelihood, moment matching, least squares, ...)
 - Assess goodness of fit via hypothesis tests
 - H_0 : fitted distribution adequately represents data
 - Get p value for test (small = poor fit)
- **Fitted “theoretical” vs. empirical distribution**
- **Continuous vs. discrete data, distribution**
- **“Best” fit from among several distributions**




Data Files for Arena Input Analyzer

- **Create data file**
 - Editor, word processor, spreadsheet, ...
 - Plain ASCII text – save as text or export)
 - Values separated by white space – blanks, tabs, linefeeds
 - Otherwise free format
- **Open data file from within Input Analyzer**
 - *File > New* or 
 - *File > Data File > Use Existing* or 
 - Get histogram, basic summary of data
 - To see data file: *Window > Input Data*
- **Generate “fake” data file to play around**
 - *File > Data File > Generate New*

Fit Menu

- **Fits distributions, does goodness-of-fit tests**
- **Fit a specific distribution form**
 - Plots density over histogram for visual “test”
 - Gives exact expression to Copy and Paste (Ctrl+C, Ctrl+V) over into simulation model
 - May include “offset” depending on distribution
 - Gives results of goodness-of-fit tests
 - Chi square, Kolmogorov-Smirnov tests
 - Most important part: *p-value*, always between 0 and 1:
Probability of getting a data set that’s more inconsistent with fitted distribution than data set you actually have, if fitted distribution is truly “the truth”
“Small” p (< 0.05 or so): poor fit (try again or give up)

Fit Menu (cont'd.)

- **Fit all of Arena's (theoretical) distributions at once**
 - *Fit > Fit All* or  
 - Returns *minimum square-error* distribution
 - Square error = sum of squared discrepancies between histogram frequencies and fitted-distribution frequencies
 - Can depend on histogram intervals chosen: different intervals can lead to different “best” distribution
 - Could still be a poor fit, though (check p value)
 - To see all distributions, ranked: *Window > Fit All Summary* or 

Fit Menu (cont'd.)

- **“Fit” Empirical distribution (continuous or discrete): *Fit > Empirical***
 - Used when “theoretical” distributions fit poorly, or used intentionally
 - Can interpret results as Discrete or Continuous distribution
 - Discrete: get pairs (*Cumulative Probability*, *Value*)
 - Continuous: Arena will linearly interpolate *within* data range according to these pairs (so you can never generate values outside range, which might be good or bad)
 - *Edit > Copy Expression* to paste the (sometimes-lengthy) expression to Windows clipboard, then paste this copied expression into destination field in Arena model
 - Need to edit end of expression slightly by adding an extra pair at the end still inside the parentheses, “ , 1.000 , **xmax**” where **xmax** is the largest value you ever want to generate

Issues in Fitting Input Distributions

- **Not an exact science – no “right” answer**
- **Consider theoretical vs. empirical**
- **Consider range of distribution**
 - Infinite both ways (e.g., normal)
 - Positive (e.g., exponential, gamma)
 - Bounded (e.g., beta, uniform)
- **Consider ease of parameter manipulation to affect means, variances**
- **Simulation model sensitivity analysis**
- **Outliers, multimodal data**
 - Maybe split data set (details in text)

No Data?

- **Happens more often than you'd like**
- **No good solution; some (bad) options:**
 - Interview “experts”
 - Min, Max: Uniform
 - Avg., % error or absolute error: Uniform
 - Min, Mode, Max: Triangular
 - Mode can be different from Mean – allows asymmetry
 - Interarrivals – independent, stationary
 - Exponential – still need some value for mean
 - Number of “random” events in an interval: Poisson
 - Sum of independent “pieces”: normal (heed left tail ...)
 - Product of independent “pieces”: lognormal

Cautions on Using Normal Distributions

- **Probably most familiar distribution – normal “bell curve” used widely in statistical inference**
- **But it has infinite tails in both directions ... in particular, has an infinite left tail so can always (theoretically) generate negative values**
 - Many simulation input quantities (e.g., time durations) must be positive to make sense – Arena truncates negatives to 0
- **If mean μ is big relative to standard deviation σ , then P(negative) value is small ... one in a million**
 - But in simulation, *one in a million can happen*
 - See text, Model 4-5
- **Moral – avoid normal as input distribution**

Nonstationary Arrival Processes

- **Events (often arrivals), rate varies over time**
 - Lunchtime at fast-food restaurants
 - Rush-hour traffic in cities
 - Telephone call centers
 - Seasonal demands for a manufactured product
- **It can be critical to model nonstationarity for model validity**
 - Ignoring peaks, valleys can mask important behavior
 - Can miss rush hours, etc.
- **Good model: *Nonstationary Poisson process***

Nonstationary Arrival Processes (cont'd.)

- **Two issues:**
 - How to specify/estimate *rate function*
 - How to generate from it properly during simulation
- **Several ways to estimate rate function – we'll just do *piecewise-constant***
 - Divide time frame of simulation into subintervals of time over which you think rate is fairly flat
 - Compute observed rate within each subinterval
 - In Arena, must convert to expected number of arrivals *per hour* on subintervals that need not be of one-hour length
 - Want expected 45 arrivals in a half hour; specify rate = 90 *per hour*
- **Example: Model 5-2 in Chapter 5**

Multivariate and Correlated Input Data

- **Usually assume all generated random observations in a simulation are independent (though from possibly different distributions)**
- **Sometimes not true:**
 - A “difficult” part requires long processing in both Prep and Sealer operations
 - This is positive correlation
- **Ignoring such relations can invalidate model**
- **See text for ideas, references**