

6. What is destructuring?

Destructuring allows extracting values from arrays or objects. It makes code shorter and cleaner. It improves readability. It is widely used in modern JavaScript.

27. What is the spread operator?

The spread operator (...) expands arrays or objects. It is used to copy or merge data. It helps avoid mutation. It simplifies code.

28. What is a ternary operator?

It is a shorthand for if-else. It has three parts: condition, true result, false result. It makes code concise. It improves readability when used properly.

29. What is strict mode?

Strict mode enforces better coding practices. It prevents the use of undeclared variables. It catches silent errors. It improves code security.

30. What is a single-page application (SPA)?

An SPA loads a single HTML page and updates content dynamically. It provides a fast user experience. It avoids full page reloads. React and Angular use this model.

1. Reverse a String

```
#include <stdio.h>

#include <string.h>

int main(){
    char s[100];
    scanf("%s", s);
    int i, j;
    char temp;
    for(i=0, j=strlen(s)-1; i<j; i++, j--){
        temp = s[i];
        s[i] = s[j];
        s[j] = temp;
    }
    printf("%s", s);
}
```

```
}
```

2. Check Palindrome

```
#include <stdio.h>
#include <string.h>
int main(){
    char s[100];
    scanf("%s", s);
    int i, n = strlen(s);
    for(i=0; i<n/2; i++){
        if(s[i] != s[n-i-1]){
            printf("Not Palindrome");
            return 0;
        }
    }
    printf("Palindrome");
}
```

3. Find Factorial (Recursive)

```
#include <stdio.h>
int fact(int n){
    if(n==0) return 1;
    return n * fact(n-1);
}
int main(){
    int n;
    scanf("%d", &n);
    printf("%d", fact(n));
}
```