

Sistemas Operativos. Práctica 1.

Pablo Cuesta Sierra y Álvaro Zamanillo Sáez

Semana 1

Ejercicio 1

a) Para buscar las funciones relacionadas con hilos, busquemos todas aquellas que contengan “pthread” usando la opción -k en el comando man. El comando a usar es:

```
$ man -k pthread
```

Lista de funciones resultante:

```
pthread_attr_destroy (3) - initialize and destroy thread attributes
    object
pthread_attr_getaffinity_np (3) - set/get CPU affinity attribute in
    thread attributes object
pthread_attr_getdetachstate (3) - set/get detach state attribute in
    thread attributes object
pthread_attr_getguardsize (3) - set/get guard size attribute in
    thread attributes object
pthread_attr_getinheritsched (3) - set/get inherit-scheduler
    attribute in thread attributes object
pthread_attr_getschedparam (3) - set/get scheduling parameter
    attributes in thread attributes object
pthread_attr_getschedpolicy (3) - set/get scheduling policy
    attribute in thread attributes object
pthread_attr_getscope (3) - set/get contention scope attribute in
    thread attributes object
pthread_attr_getstack (3) - set/get stack attributes in thread
    attributes object
pthread_attr_getstackaddr (3) - set/get stack address attribute in
    thread attributes object
pthread_attr_getstacksize (3) - set/get stack size attribute in
    thread attributes object
pthread_attr_init (3) - initialize and destroy thread attributes
    object
pthread_attr_setaffinity_np (3) - set/get CPU affinity attribute in
    thread attributes object
pthread_attr_setdetachstate (3) - set/get detach state attribute in
    thread attributes object
pthread_attr_setguardsize (3) - set/get guard size attribute in
    thread attributes object
pthread_attr_setinheritsched (3) - set/get inherit-scheduler
    attribute in thread attributes object
```

```
pthread_attr_setschedparam (3) - set/get scheduling parameter
    attributes in thread attributes object
pthread_attr_setschedpolicy (3) - set/get scheduling policy
    attribute in thread attributes object
pthread_attr_setscope (3) - set/get contention scope attribute in
    thread attributes object
pthread_attr_setstack (3) - set/get stack attributes in thread
    attributes object
pthread_attr_setstackaddr (3) - set/get stack address attribute in
    thread attributes object
pthread_attr_setstacksize (3) - set/get stack size attribute in
    thread attributes object
pthread_cancel (3) - send a cancellation request to a thread
pthread_cleanup_pop (3) - push and pop thread cancellation clean-up
    handlers
pthread_cleanup_pop_restore_np (3) - push and pop thread
    cancellation clean-up handlers while saving cancelability type
pthread_cleanup_push (3) - push and pop thread cancellation clean-
    up handlers
pthread_cleanup_push_defer_np (3) - push and pop thread
    cancellation clean-up handlers while saving cancelability type
pthread_create (3) - create a new thread
pthread_detach (3) - detach a thread
pthread_equal (3) - compare thread IDs
pthread_exit (3) - terminate calling thread
pthread_getaffinity_np (3) - set/get CPU affinity of a thread
pthread_getattr_default_np (3) - get or set default thread-creation
    attributes
pthread_getattr_np (3) - get attributes of created thread
pthread_getconcurrency (3) - set/get the concurrency level
pthread_getcpuclockid (3) - retrieve ID of a thread's CPU time
    clock
pthread_getname_np (3) - set/get the name of a thread
pthread_getschedparam (3) - set/get scheduling policy and
    parameters of a thread
pthread_join (3) - join with a terminated thread
pthread_kill (3) - send a signal to a thread
pthread_kill_other_threads_np (3) - terminate all other threads in
    process
pthread_mutex_consistent (3) - make a robust mutex consistent
pthread_mutex_consistent_np (3) - make a robust mutex consistent
pthread_mutexattr_getpshared (3) - get/set process-shared mutex
    attribute
pthread_mutexattr_getrobust (3) - get and set the robustness
    attribute of a mutex attributes object
pthread_mutexattr_getrobust_np (3) - get and set the robustness
    attribute of a mutex attributes object
pthread_mutexattr_setpshared (3) - get/set process-shared mutex
    attribute
pthread_mutexattr_setrobust (3) - get and set the robustness
    attribute of a mutex attributes object
pthread_mutexattr_setrobust_np (3) - get and set the robustness
    attribute of a mutex attributes object
pthread_rwlockattr_getkind_np (3) - set/get the read-write lock
    kind of the thread read-write lock attribute object
pthread_rwlockattr_setkind_np (3) - set/get the read-write lock
    kind of the thread read-write lock attribute object
```

```

pthread_self (3)      - obtain ID of the calling thread
pthread_setaffinity_np (3) - set/get CPU affinity of a thread
pthread_setattr_default_np (3) - get or set default thread-creation
    attributes
pthread_setcancelstate (3) - set cancelability state and type
pthread_setcanceltype (3) - set cancelability state and type
pthread_setconcurrency (3) - set/get the concurrency level
pthread_setname_np (3) - set/get the name of a thread
pthread_setschedparam (3) - set/get scheduling policy and
    parameters of a thread
pthread_setschedprio (3) - set scheduling priority of a thread
pthread_sigmask (3) - examine and change mask of blocked signals
pthread_sigqueue (3) - queue a signal and data to a thread
pthread_spin_destroy (3) - initialize or destroy a spin lock
pthread_spin_init (3) - initialize or destroy a spin lock
pthread_spin_lock (3) - lock and unlock a spin lock
pthread_spin_trylock (3) - lock and unlock a spin lock
pthread_spin_unlock (3) - lock and unlock a spin lock
pthread_testcancel (3) - request delivery of any pending
    cancellation request
pthread_timedjoin_np (3) - try to join with a terminated thread
pthread_tryjoin_np (3) - try to join with a terminated thread
pthread_yield (3)      - yield the processor
pthreads (7)          - POSIX threads

```

b) Consultar en el manual en qué sección se encuentran las llamadas a sistema y buscar información sobre write:

```
$ man man
```

Con este comando averiguamos que la sección relacionada a *system calls* es la 2. Por lo tanto usamos el comando:

```
$ man 2 write
```

Ejercicio 2

a) El comando empleado es:

```
$ grep -w molino "don quijote.txt" >> aventuras.txt
```

Usamos el comando grep para buscar las apariciones de “molino”. Como queremos que sea la palabra *molino* y no el grama *molino*, añadimos la opción -w. Finalmente redireccionamos la salida con >> en vez de > para que se añada al final del fichero, en lugar de reemplazarlo.

b) El *pipeline* es el siguiente:

```
$ ls | wc -l
```

La salida de ls es una lista (fichero) con los ficheros del actual directorio. Esta lista la usamos como input del comando wc, que acompañado de la opción -l, cuenta las líneas de dicha lista.

c) En este caso el *pipeline* es:

```
$ cat "lista de la compra Pepe.txt" "lista de la compra Elena.txt"
  2> /dev/null | sort | uniq | wc -l > "num compra.txt"
```

Primero concatenamos los dos ficheros (redirigiendo el mensaje error, en caso de haberlo). Después, dirigimos la salida para que sea el input de `sort`, para que luego `uniq` quite las líneas repetidas. Finalmente, contamos el número de líneas distintas con `wc -l` y dirigimos la salida al fichero `"num compra.txt"`.

Ejercicio 3

a) Si intentamos abrir un fichero inexistente recibimos el mensaje `"No such file or directory"`. El código `errno` asociado es 2.

b) En el caso de intentar abrir el fichero `/etc/shadow` el mensaje de error es `"Permission denied"`, que corresponde al valor de `errno` 13.

c) Justo después de la instrucción `fopen()` se debería guardar el valor de `errno` en otra variable ya que la llamada a `printf()` podría modificar la variable global `errno`.

```
pf=fopen(args[1], "r");
x=errno;
printf("El valor de errno es %i", x);
errno=x; /*Aquí aseguro que la función perror() va a
imprimir el código de error de fopen ya que hemos restaurado
el valor de errno asociado a fopen()*/
perror();
```

Ejercicio 4

a) Durante los 10 segundos de espera el proceso asociado al programa está en estado `"R"` (runnable), es decir se está ejecutando (intercalándose con otros).

b) En este caso el proceso está en estado `"S"` (interruptible sleep) o lo que es lo mismo, esperando a un suceso (el fin de la espera marcada por `sleep()`), mientras se ejecutan otros procesos.

Ejercicio 5

a) Si el proceso no hubiese esperado a los hilos, cuando el hilo principal llegase a `exit()`, el programa finalizaría matando los hilos que no tendrían por qué haber acabado. De hecho, si quitamos del código las instrucciones `pthread_join`, vemos que cada hilo solo tiene tiempo de escribir una letra antes de que el hilo principal llegue al `exit` y finalice, por tanto, la ejecución de todos los hilos.

b) En este caso, ocurre exactamente lo mismo que en anterior (se imprimen las dos primeras letras—una de cada hilo—, luego se imprime el mensaje de la línea 51 en el código dado). Sin embargo, después de esto, continúan ejecutándose los dos hilos hasta que cada uno de ellos llega a su función `exit()`.

Es decir, `pthread_exit()` termina la ejecución del hilo principal, pero permite que se terminen todos los hilos que del proceso antes de terminarlo. Lo cual no pasa si se llama directamente a `exit()`, como hemos visto en el apartado 5a).

c) Para que los otros hilos puedan terminar su ejecución, tenemos que sustituir la llamada en `main()` de `exit()` por una llamada a `pthread_exit()`.